

MSXE302x soap api functions

Generated by Doxygen 1.7.1

Mon Jun 17 2013 12:54:20

Contents

1	Introduction	1
1.1	Introduction	1
1.2	Remark: SOAP functions prototypes	1
2	Module Documentation	3
2.1	Software hints	3
2.2	SOAP function calls in C/C++ language	3
2.2.1	C/C++ language SOAP function prototypes	3
2.2.2	Rules and use of gSOAP calls in C/C++	4
2.2.3	SOAP calls sample	6
2.3	MSX-E systems servers	10
2.3.1	SOAP server	10
2.3.2	Event server	10
2.3.3	Modbus server	10
2.4	Common functions	10
2.5	Common general functions	11
2.5.1	Function Documentation	12
2.5.1.1	MXCommon__GetModuleType	12
2.5.1.2	MXCommon__GetHostname	12
2.5.1.3	MXCommon__SetHostname	13
2.5.1.4	MXCommon__GetClientConnections	13
2.5.1.5	MXCommon__Strerror	13
2.5.1.6	MXCommon__Reboot	15
2.5.1.7	MXCommon__ResetAllIIOFunctionalities	15
2.5.1.8	MXCommon__DataserverRestart	15
2.5.1.9	MXCommon__GetEthernetLinksStates	16
2.6	Common temperature functions	17
2.6.1	Detailed Description	17

2.6.2	Function Documentation	17
2.6.2.1	MXCommon__GetModuleTemperatureValueAndStatus	17
2.6.2.2	MXCommon__SetModuleTemperatureWarningLevels	18
2.7	Common hardware trigger functions	18
2.7.1	Function Documentation	19
2.7.1.1	MXCommon__SetHardwareTriggerFilterTime	19
2.7.1.2	MXCommon__GetHardwareTriggerFilterTime	19
2.7.1.3	MXCommon__GetHardwareTriggerState	20
2.8	Common security functions	20
2.8.1	Detailed Description	21
2.8.2	Function Documentation	21
2.8.2.1	MXCommon__SetCustomerKey	21
2.8.2.2	MXCommon__TestCustomerID	22
2.9	Common time functions	22
2.9.1	Detailed Description	23
2.9.2	Function Documentation	23
2.9.2.1	MXCommon__SetTime	23
2.9.2.2	MXCommon__SysToHardwareClock	23
2.9.2.3	MXCommon__HardwareClockToSys	24
2.9.2.4	MXCommon__GetTime	24
2.9.2.5	MXCommon__GetUpTime	25
2.10	Common I/O auto configuration functions	25
2.10.1	Detailed Description	25
2.10.2	Function Documentation	26
2.10.2.1	MXCommon__GetAutoConfigurationFile	26
2.10.2.2	MXCommon__SetAutoConfigurationFile	26
2.10.2.3	MXCommon__StartAutoConfiguration	27
2.11	Common synchronisation timer functions	27
2.11.1	Function Documentation	27
2.11.1.1	MXCommon__InitAndStartSynchroTimer	27
2.11.1.2	MXCommon__StopAndReleaseSynchroTimer	28
2.12	Set/Backup/Restore general system configuration	29
2.12.1	Detailed Description	29
2.12.2	Function Documentation	29
2.12.2.1	MXCommon__GetConfigurationBackupFile	29
2.12.2.2	MXCommon__ApplyConfigurationBackupFile	30

2.12.2.3	MXCommon__ChangePassword	30
2.13	System state management	31
2.13.1	Detailed Description	32
2.13.2	Function Documentation	32
2.13.2.1	MXCommon__GetSubSystemState	32
2.13.2.2	MXCommon__GetSubsystemIDFromName	32
2.13.2.3	MXCommon__GetStateIDFromName	33
2.13.2.4	MXCommon__GetSubsystemNameFromID	33
2.13.2.5	MXCommon__GetStateNameFromID	33
2.14	Customer option management	34
2.14.1	Function Documentation	34
2.14.1.1	MXCommon__GetOptionInformation	34
2.15	Synchronisation management	34
2.15.1	Function Documentation	35
2.15.1.1	MXCommon__SetToMaster	35
2.15.1.2	MXCommon__GetSynchronizationStatus	35
2.16	MSX-E302x functions	36
2.17	MSX-E302x Information functions	36
2.17.1	Function Documentation	37
2.17.1.1	MSXE302x__AnalogInputGetChannelType	37
2.17.1.2	MSXE302x__AnalogMeasureGetConfiguration	37
2.18	MSX-E302x Autorefresh functions	38
2.18.1	Detailed Description	38
2.18.2	Function Documentation	39
2.18.2.1	MSXE302x__AnalogInputInitAndStartAutoRefresh	39
2.18.2.2	MSXE302x__AnalogInputGetAutoRefreshValues	42
2.18.2.3	MSXE302x__AnalogInputStopAndReleaseAutoRefresh	42
2.19	MSX-E302x Sequence functions	43
2.19.1	Detailed Description	43
2.19.2	Function Documentation	44
2.19.2.1	MSXE302x__AnalogInputInitAndStartSequence	44
2.19.2.2	MSXE302x__AnalogInputStopAndReleaseSequence	47
2.20	MSX-E302x calibration functions	47
2.20.1	Detailed Description	47
2.20.2	Function Documentation	48
2.20.2.1	MSXE302x__CalibrationStart	48

2.20.2.2	MSXE302x__CalibrationGetCurrentStatus	49
2.20.2.3	MSXE302x__CalibrationNextStep	49
2.20.2.4	MSXE302x__CalibrationBreak	50
3	Data Structure Documentation	51
3.1	ByteArray Struct Reference	51
3.1.1	Field Documentation	51
3.1.1.1	__ptr	51
3.1.1.2	__size	51
3.1.1.3	__offset	51
3.2	DefaultResponse Struct Reference	51
3.2.1	Field Documentation	52
3.2.1.1	iReturnValue	52
3.2.1.2	syserrno	52
3.3	MSXE302x__AnalogInputGetAutoRefreshValuesResponse Struct Reference	52
3.3.1	Field Documentation	53
3.3.1.1	sResponse	53
3.3.1.2	ulTimeStampLow	53
3.3.1.3	ulTimeStampHigh	53
3.3.1.4	ulCounterValue	53
3.3.1.5	ulValue	53
3.4	MSXE302x__AnalogInputGetChannelTypeResponse Struct Reference	53
3.4.1	Field Documentation	53
3.4.1.1	sResponse	53
3.4.1.2	ulType	53
3.5	MSXE302x__AnalogMeasureGetConfigurationResponse Struct Reference	53
3.5.1	Field Documentation	55
3.5.1.1	iReturnValue	55
3.5.1.2	ulRunningMode	55
3.5.1.3	ulConvertTimeUnit	55
3.5.1.4	ulConvertTime	55
3.5.1.5	ulChannelInitialization	55
3.5.1.6	sAcquisition	55
3.5.1.7	ulChannelMask	55
3.5.1.8	ulAverageMode	55
3.5.1.9	ulAverageValue	55
3.5.1.10	ulDataFormat	55

3.5.1.11	sAutoRefresh	56
3.5.1.12	ulSequenceSize	56
3.5.1.13	ulSequence	56
3.5.1.14	ulSequenceInterrupt	56
3.5.1.15	ulNbrOfSequence	56
3.5.1.16	ulDelayFlag	57
3.5.1.17	ulDelayMode	57
3.5.1.18	ulDelayTimeUnit	57
3.5.1.19	ulDelayTime	57
3.5.1.20	sSequence	57
3.5.1.21	ulSequenceTriggerCount	57
3.5.1.22	ulFlag	57
3.5.1.23	ulLevel	57
3.5.1.24	ulAction	57
3.5.1.25	ulCount	57
3.5.1.26	sHardware	57
3.5.1.27	sSoftware	57
3.5.1.28	sSynchro	57
3.5.1.29	sTrigger	57
3.6	MSXE302x__CalibrationGetCurrentStatusResponse Struct Reference	57
3.6.1	Field Documentation	58
3.6.1.1	sResponse	58
3.6.1.2	ulStatus	58
3.6.1.3	dCurrentValue	58
3.6.1.4	ulError	58
3.7	MSXE302x__Response Struct Reference	59
3.7.1	Field Documentation	59
3.7.1.1	iReturnValue	59
3.7.1.2	syserrno	60
3.8	MSXE302x__unsignedLong16FixedArrayParam Struct Reference	60
3.8.1	Field Documentation	60
3.8.1.1	ulValue	60
3.9	MSXE302x__unsignedLongResponse Struct Reference	60
3.9.1	Field Documentation	60
3.9.1.1	sResponse	60
3.9.1.2	ulValue	60

3.10 MXCommon__ByteArrayResponse Struct Reference	60
3.10.1 Field Documentation	61
3.10.1.1 sResponse	61
3.10.1.2 sArray	61
3.11 MXCommon__FileResponse Struct Reference	61
3.11.1 Field Documentation	61
3.11.1.1 sResponse	61
3.11.1.2 sArray	61
3.11.1.3 ulEOF	61
3.12 MXCommon__GetAutoConfigurationFileResponse Struct Reference	61
3.12.1 Field Documentation	62
3.12.1.1 sResponse	62
3.12.1.2 bArray	62
3.12.1.3 ulEOF	62
3.13 MXCommon__GetEthernetLinksStatesResponse Struct Reference	62
3.13.1 Field Documentation	62
3.13.1.1 sResponse	62
3.13.1.2 sPort0	62
3.13.1.3 sPort1	62
3.14 MXCommon__GetHardwareTriggerFilterTimeResponse Struct Reference	62
3.14.1 Field Documentation	63
3.14.1.1 sResponse	63
3.14.1.2 ulFilterTime	63
3.14.1.3 ullInfo01	63
3.14.1.4 ullInfo02	63
3.15 MXCommon__GetHardwareTriggerStateResponse Struct Reference	63
3.15.1 Field Documentation	63
3.15.1.1 sResponse	63
3.15.1.2 ulState	63
3.15.1.3 ullInfo01	63
3.15.1.4 ullInfo02	63
3.16 MXCommon__GetModuleTemperatureValueAndStatusResponse Struct Reference	63
3.16.1 Field Documentation	64
3.16.1.1 sResponse	64
3.16.1.2 dTemperatureValue	64
3.16.1.3 ulTemperatureStatus	64

3.16.1.4	<ulinfo></ulinfo>	64
3.17	MXCommon__GetTimeResponse Struct Reference	64
3.17.1	Field Documentation	64
3.17.1.1	sResponse	64
3.17.1.2	ulLowTime	64
3.17.1.3	ulHighTime	64
3.18	MXCommon__GetUpTimeResponse Struct Reference	64
3.18.1	Field Documentation	65
3.18.1.1	sResponse	65
3.18.1.2	ulUpTime	65
3.19	MXCommon__Response Struct Reference	65
3.19.1	Field Documentation	65
3.19.1.1	iReturnValue	65
3.19.1.2	syserrno	65
3.20	MXCommon__TestCustomerIDResponse Struct Reference	65
3.20.1	Field Documentation	66
3.20.1.1	sResponse	66
3.20.1.2	bValueArray	66
3.20.1.3	bCryptedValueArray	66
3.21	MXCommon__unsignedLongResponse Struct Reference	66
3.21.1	Field Documentation	66
3.21.1.1	sResponse	66
3.21.1.2	ulValue	66
3.22	sGetEthernetLinksStatesPort Struct Reference	66
3.22.1	Field Documentation	67
3.22.1.1	ulState	67
3.22.1.2	ulSpeed	67
3.22.1.3	ulDuplex	67
3.22.1.4	ulInfo1	67
3.22.1.5	ulInfo2	67
3.23	UnsignedLongArray Struct Reference	67
3.23.1	Field Documentation	67
3.23.1.1	__ptr	67
3.23.1.2	__size	67
3.23.1.3	__offset	67
3.24	UnsignedShortArray Struct Reference	67

3.24.1	Field Documentation	68
3.24.1.1	__ptr	68
3.24.1.2	__size	68
3.24.1.3	__offset	68
3.25	xsd_base64Binary Struct Reference	68
3.25.1	Field Documentation	68
3.25.1.1	__ptr	68
3.25.1.2	__size	68
4	File Documentation	69
4.1	MSXE302x_public_doc.h File Reference	69
4.1.1	Typedef Documentation	75
4.1.1.1	xsd_string	75
4.1.1.2	xsd_char	75
4.1.1.3	xsd_float	75
4.1.1.4	xsd_double	75
4.1.1.5	xsd_int	75
4.1.1.6	xsd_long	75
4.1.1.7	xsd_unsignedByte	75
4.1.1.8	xsd_unsignedInt	75
4.1.1.9	xsd_unsignedShort	75
4.1.1.10	xsd_unsignedLong	75
4.1.2	Function Documentation	75
4.1.2.1	MXCommon_GetModuleType	75
4.1.2.2	MXCommon_GetHostname	75
4.1.2.3	MXCommon_SetHostname	76
4.1.2.4	MXCommon_GetClientConnections	76
4.1.2.5	MXCommon_Strerror	77
4.1.2.6	MXCommon_Reboot	78
4.1.2.7	MXCommon_ResetAllIIOFunctionalities	78
4.1.2.8	MXCommon_DataserverRestart	79
4.1.2.9	MXCommon_GetEthernetLinksStates	79
4.1.2.10	MXCommon_GetModuleTemperatureValueAndStatus	80
4.1.2.11	MXCommon_SetModuleTemperatureWarningLevels	81
4.1.2.12	MXCommon_SetHardwareTriggerFilterTime	81
4.1.2.13	MXCommon_GetHardwareTriggerFilterTime	81
4.1.2.14	MXCommon_GetHardwareTriggerState	82

4.1.2.15	MXCommon_SetCustomerKey	82
4.1.2.16	MXCommon_TestCustomerID	83
4.1.2.17	MXCommon_SetTime	83
4.1.2.18	MXCommon_SysToHardwareClock	83
4.1.2.19	MXCommon_HardwareClockToSys	84
4.1.2.20	MXCommon_GetTime	84
4.1.2.21	MXCommon_GetUpTime	85
4.1.2.22	MXCommon_GetAutoConfigurationFile	85
4.1.2.23	MXCommon_SetAutoConfigurationFile	85
4.1.2.24	MXCommon_StartAutoConfiguration	86
4.1.2.25	MXCommon_InitAndStartSynchroTimer	86
4.1.2.26	MXCommon_StopAndReleaseSynchroTimer	87
4.1.2.27	MXCommon_GetConfigurationBackupFile	87
4.1.2.28	MXCommon_ApplyConfigurationBackupFile	88
4.1.2.29	MXCommon_ChangePassword	89
4.1.2.30	MXCommon_GetSubSystemState	89
4.1.2.31	MXCommon_GetSubsystemIDFromName	90
4.1.2.32	MXCommon_GetStateIDFromName	90
4.1.2.33	MXCommon_GetSubsystemNameFromID	91
4.1.2.34	MXCommon_GetStateNameFromID	91
4.1.2.35	MXCommon_GetOptionInformation	91
4.1.2.36	MXCommon_SetToMaster	92
4.1.2.37	MXCommon_GetSynchronizationStatus	92
4.1.2.38	MSXE302x_AnalogInputGetChannelType	93
4.1.2.39	MSXE302x_AnalogMeasureGetConfiguration	93
4.1.2.40	MSXE302x_AnalogInputInitAndStartAutoRefresh	94
4.1.2.41	MSXE302x_AnalogInputGetAutoRefreshValues	96
4.1.2.42	MSXE302x_AnalogInputStopAndReleaseAutoRefresh	97
4.1.2.43	MSXE302x_AnalogInputInitAndStartSequence	97
4.1.2.44	MSXE302x_AnalogInputStopAndReleaseSequence	100
4.1.2.45	MSXE302x_CalibrationStart	100
4.1.2.46	MSXE302x_CalibrationGetCurrentStatus	101
4.1.2.47	MSXE302x_CalibrationNextStep	102
4.1.2.48	MSXE302x_CalibrationBreak	102

Chapter 1

Introduction

MainRevision:

1.1 Introduction

This documentation describes the SOAP functions and gives software hints to work with the MSX-E systems. Following documentations can be found under **Modules**.

SOAP means Simple Object Access Protocol. This protocol enables to use the MSX-E software functions over Ethernet. It is providing **Web Services** that can easily be consumed in many programming languages like C, C++, C#, VB.Net... With the SOAP functions, all functionalities of the MSX-E system can be managed / configured / monitored.

1.2 Remark: SOAP functions prototypes

In some programming languages, SOAP functions names and parameters could be different as those described in this documentation. Please see to [Software hints](#)

Chapter 2

Module Documentation

2.1 Software hints

Modules

- [SOAP function calls in C/C++ language](#)

Some hints on how to use the SOAP functions in a C/C++ program.

- [MSX-E systems servers](#)

The MSX-E embeds servers to provide configuration, management and monitoring over Ethernet.

2.2 SOAP function calls in C/C++ language

Some hints on how to use the SOAP functions in a C/C++ program.

2.2.1 C/C++ language SOAP function prototypes

In this documentation, functions are described as follows.

```
int MXCommon__GetModuleType(void * ___, struct MXCommon__ByteArrayResponse  
* Response);
```

Two main differences can be remarked in the function prototypes:

- The prefix:

`soap_call_`

- The first three parameters of the SOAP stub:

```
struct soap *soap  
const char *soap_endpoint  
const char *soap_action
```

The C function prototype has the following syntax:

```
int soap_call_MXCommon__GetModuleType(struct soap *soap, const char *soap_endpoin
t, const char *soap_action, void *_, struct MXCommon__ByteArrayResponse *Response
);
```

Functions to call in C/C++ are called **stubs** and can be found in the **MSXEXXXXStub.h** file.

2.2.2 Rules and use of gSOAP calls in C/C++

When programming with gSOAP in C/C++ language, some rules have to be followed to avoid memory leaks, slow socket disconnections and multi-threading compliancy.

Note: Software code pieces in this chapter comes from [SOAP calls sample](#)

- **Opening and initializing an SOAP connection (using the gSOAP functions)**

```
struct soap *soapContext;

// IP address of the MSX-E and after the ':' is the MSX-E SOAP server port number
char soap_endpoint[] = IP_ADDRESS":5555";

// Allocates and initialize a new runtime context
if ((soapContext = soap_new ()) == NULL)
    return EXIT_FAILURE;

// Initializes the SOAP context with options
soap_init2 (soapContext, SOAP_IO_KEEPALIVE, SOAP_IO_KEEPALIVE);

// Sets timeouts in seconds
soapContext->send_timeout = 1;
soapContext->recv_timeout = 1;
soapContext->accept_timeout = 1;
```

Remark: A new runtime context is required in each new thread!

- **Calling the MSX-E SOAP functions**

Important

- In C/C++, each MSX-E SOAP function call is allocating memory (to manage deserialized data) and is not deallocating it automatically. The allocated memory has to be deallocated explicitly by calling, in this order, the soap_destroy and soap_end functions. These functions can be called after each MSX-E SOAP function call or after several calls. It is important to call these functions regularly to prevents memory leaks.
- If the SOAP function is returning pointer, call the soap_destroy and soap_end functions only after working with the pointers. If soap_destroy and soap_end are called before working the pointers, the values pointed by the pointer will not be available. All dynamically allocated values are destroyed by soap_destroy and soap_end.

See [C/C++ language SOAP function prototypes](#) to call the MSX-E SOAP functions.

```
for ( ; ; )
{
    soap_error = soap_call_MXCommon__GetModuleTemperatureValueAndStatus (soap
Context, soap_endpoint, NULL, option, &tempResponse);

    ...
}
```

```

    // As gSOAP doesn't released automatically the memory that it allocates t
    o
    // deserialize SOAP data we have to released it explicitly.
    // There is no need to call the function in each loop cycle,
    // it depends on the application, and desired performance and
    // available memory.
    soap_destroy (soapContext);
    soap_end (soapContext);

    ...
}

```

- **Error management**

There are 3 types of errors that can be generated by the MSX-E SOAP functions:

- SOAP errors: It is the SOAP function return value. More details about the error can be obtained by using the `soap_faultstring` function.

```

soap_error = soap_call_MXCommon__GetModuleTemperatureValueAndStatus (soapContext,
    soap_endpoint, NULL, option, &tempResponse);

if (soap_error)
    printf ("message: %s\n", *soap_faultstring (soapContext));

```

Remark: `soap_faultstring` has to be called just after the SOAP function call that generates the SOAP error and before the call of `soap_destroy` and `soap_end`.

- The MSX-E error (iReturnValue): Returns errors that are not linux specific. The `iReturnValue` variable is located in the response structure. These errors are described in this documentation.

```

soap_error = soap_call_MXCommon__GetModuleTemperatureValueAndStatus (soapContext,
    soap_endpoint, NULL, option, &tempResponse);

// Check for errors, if there are, stop the loop
if (checkErrors (soapContext, soap_endpoint, NULL, soap_error, tempResponse.sResponse.iReturnValue, tempResponse.sResponse.syserrno))
    break;

```

- The MSX-E system error (syserrno): Returns linux specific errors. This variable has to be checked only if `iReturnValue` = -1 or `iReturnValue` <= -100. It returns the linux `errno` error. More details about the error can be obtained by using the `soap_call_MXCommon__Strerror` function.

```

struct MXCommon__ByteArrayResponse byteArrayResponse;

memset (&byteArrayResponse, 0, sizeof (struct MXCommon__ByteArrayResponse));

soap_error = soap_call_MXCommon__GetModuleTemperatureValueAndStatus (soapContext,
    soap_endpoint, NULL, option, &tempResponse);

if ((tempResponse.sResponse.iReturnValue == -1) || ((tempResponse.sResponse.iReturnValue <= -100) && tempResponse.sResponse.syserrno))
{
    soap_call_MXCommon__Strerror (soapContext, soap_endpoint, soap_action, tempResponse.sResponse.syserrno, &byteArrayResponse);

    // Display the system error
    printf ("\nSystem error: %s\n", byteArrayResponse.sArray.__ptr);
}

```

- **Close the SOAP connection**

Before to quit the application or when no MSX-E SOAP function calls are necessary, the SOAP connection has to be closed and the context has to be released. Call following functions in this order: `soap_destroy`, `soap_end`, `soap_free`.

```
// Release SOAP
soap_destroy (soapContext);
soap_end (soapContext);

// Close the socket an release the SOAP context
soap_free (soapContext);
```

2.2.3 SOAP calls sample

Here a sample code, and it's makefile, to read the MSX-E internal temperature.

To compile it, use `make IP_ADDRESS=YOUR_MSX-E_IP_ADDRESS` don't forget to set the **INTERFACE_COMMON_LIBRARY_DIR** to point on the MSX-E Common Interface_Library directory.

Remark: Don't use blank spaces in the directories and file names.

temperature.c file

```
#include <unistd.h>
#include <stdio.h>
#include <stdbool.h>
#include <string.h>
#include <errno.h>
#include <MXCommon.nsmap> // this file must be included only once in the project
#include <assert.h>
#include <sys/stat.h>
#include <termios.h>

//-----
//-----
//-----

/** kbhit for linux.

@retval 0: No key pressed.
@retval >0: Key pressed.
*/
int kbhit (void)
{
    struct termios oldt, newt;
    struct timeval tv;
    fd_set read_fd;
    int status;

    tcgetattr (STDIN_FILENO, &oldt);
    memcpy (&newt, &oldt, sizeof (newt));
    newt.c_lflag &= ~(ICANON | ECHO);
    tcsetattr (STDIN_FILENO, TCSANOW, &newt);

    tv.tv_sec = 0;
    tv.tv_usec = 0;
    FD_ZERO (&read_fd);
    FD_SET (0, &read_fd);

    status = select (1, &read_fd, NULL, NULL, &tv);
    tcsetattr (STDIN_FILENO, TCSANOW, &oldt);

    if (status < 0)
        return 0;
    else
        return (status);
}
```

```

//-----
-----


/** getch for linux.

@retval key: Key number.
*/
int getch (void)
{
    struct termios oldt, newt;
    int ch;

    tcgetattr (STDIN_FILENO, &oldt);
    memcpy (&newt, &oldt, sizeof (newt));
    newt.c_lflag &= ~(ICANON | ECHO);
    tcsetattr (STDIN_FILENO, TCSANOW, &newt);
    ch = getchar();
    tcsetattr (STDIN_FILENO, TCSANOW, &oldt);

    return (ch);
}

//-----
-----


/** Check if the SOAP call returns an error, display it.

@param[in] soapContext : SOAP context structure.
@param[in] soap_endpoint : IP and port number of the system to access.
@param[in] soap_action : SOAP action required by the Web service.
@param[in] soap_error: The SOAP function return value.
@param[in] msxe_error: The MSX-E system return value contained in the response s
tructure (iReturnValue).
@param[in] msxe_syserrno: The MSX-E system errno value contained in the response
structure (syserrno).

@retval 0: No error.
@retval 1: Error.
*/
int checkErrors (struct soap *soapContext, const char *soap_endpoint, const char
*soap_action, int soap_error, int msxe_error, int msxe_syserrno)
{
    if ((soap_error != 0) || (msxe_error != 0))
    {
        printf ("MSX-E function response error: %d\n", msxe_error);
        printf ("soap error: %d ", soap_error);

        // In case of an SOAP error, display it
        if (soap_error)
            printf ("message: %s\n", *soap_faultstring (soapContext));
    ;
        else
        {
            // It's not an SOAP error but a system error
            if ((msxe_error == -1) || ((msxe_error <= -100) && msxe_s
yserrno))
            {
                struct MXCommon__ByteArrayResponse byteArrayRespo
nse;
                memset (&byteArrayResponse, 0, sizeof (struct
MXCommon__ByteArrayResponse));

                // Get the system error
                if (soap_call_MXCommon__Strerror (soapContext, so
ap_endpoint, soap_action, msxe_syserrno, &byteArrayResponse))

```

```

                printf ("\nsoap_call_MXCommon__Strerror e
rror: %s\n", *soap_faultstring (soapContext));
                else // Display the system error
                    printf ("\nSystem error: %s\n", byteArray
Response.sArray.__ptr__);
            }
        }

        return 1;
    }

    return 0;
}

//-----
//-----
//-----
//-----



int main (void)
{
    struct soap *soapContext;
    unsigned long option = 0;
    struct MXCommon__GetModuleTemperatureValueAndStatusResponse tempResponse
    ;
    int soap_error = 0;
    char *tempStatus[] = {"NOT AVAILABLE", "TOO LOW", "LOW", "NOMINAL", "HIG
H", "TOO HIGH"};
    // IP address of the MSX-E and after the ':' is the MSX-E SOAP server po
rt number
    char soap_endpoint[] = IP_ADDRESS":5555";

    memset (&tempResponse, 0, sizeof (struct
MXCommon__GetModuleTemperatureValueAndStatusResponse));

    // Allocates and initialize a new runtime context
    if ((soapContext = soap_new ()) == NULL)
        return EXIT_FAILURE;

    // Initializes the SOAP context with options
    soap_init2 (soapContext, SOAP_IO_KEEPALIVE, SOAP_IO_KEEPALIVE);

    // Sets timeouts in seconds
    soapContext->send_timeout = 1;
    soapContext->recv_timeout = 1;
    soapContext->accept_timeout = 1;

    for ( ; ; )
    {
        soap_error = soap_call_MXCommon__GetModuleTemperatureValueAndSta
tus (soapContext, soap_endpoint, NULL, option, &tempResponse);

        // Check for errors, if there are, stop the loop
        if (checkErrors (soapContext, soap_endpoint, NULL, soap_error, t
empResponse.sResponse.iReturnValue, tempResponse.sResponse.syserrno))
            break;

        // There is no error
        printf ("MSX-E Temperature: %.2lf °C status: ", tempResponse.dTem
peratureValue);

        if (tempResponse.ulTemperatureStatus < 6)
            printf ("%s ", tempStatus[tempResponse.ulTemperatureStatu
s]);
        else
            printf ("unknown ");
    }
}

```

```

        printf ("(ESC to quit)\n");

        // As gSOAP doesn't released automatically the memory that it al-
        locates to
        // deserialize SOAP data we have to released it explicitly.
        // There is no need to call the function in each loop cycle,
        // it depends on the application, and desired performance and
        // available memory.
        soap_destroy (soapContext);
        soap_end (soapContext);

        // Listen on keyboard actions
        if (kbhit ())
            if (getch () == 27) // Check if ESC key has been used
                break;
        }

        // Release SOAP
        soap_destroy (soapContext);
        soap_end (soapContext);
        // Close the socket an release the SOAP context
        soap_free (soapContext);

        return EXIT_SUCCESS;
}

```

Makefile

```

TOPDIR           := $(shell pwd)

CC              := $(CROSS)$(CC)
LD              := $(CROSS)ld
STRIP           := $(CROSS)strip

ifeq ($(INTERFACE_COMMON_LIBRARY_DIR), "")
INTERFACE_COMMON_LIBRARY_DIR      := $(TOPDIR)/../../Interface_Library
endif

# The MSX-E IP address
ifeq ($(IP_ADDRESS), "")
IP_ADDRESS          := 192.168.99.99
endif

# File implementing SOAP client
SOAPSRCS         := $(INTERFACE_COMMON_LIBRARY_DIR)/MSXEClient.o \
                    $(INTERFACE_COMMON_LIBRARY_DIR)/MSXEC.o $(INTERFACE_COMMON_LIBRARY_DIR)/stdsoap2.o

CFLAGS           += -pipe -Wall -O0 -Winline -I$(INTERFACE_COMMON_LIBRARY_DIR) -DIP_ADDRESS=\"$(IP_ADDRESS)\"

TEMPERATURE_SRC   := temperature.o
BINS             := temperature

all: $(BINS)

temperature: $(SOAPSRCS) $(TEMPERATURE_SRC)
            $(CC) $(CFLAGS) -o $@ $^
            $(STRIP) $@

clean:
    -rm -f $(BINS)
    -rm -f $(INTERFACE_COMMON_LIBRARY_DIR)/*.o
    -rm -f *.o

```

2.3 MSX-E systems servers

The MSX-E embeds servers to provide configuration, management and monitoring over Ethernet.

2.3.1 SOAP server

SOAP means Simple Object Access Protocol. This protocol allows you to use the MSX-E software functions over Ethernet. It is providing **Web Services** that can easily be consumed in many programming languages like C, C++, C#, VB.Net... With the SOAP functions, all functionalities of the MSX-E system can be managed / configured / monitored. This server can be accessed on port 5555. All SOAP functions are described under Modules -> MSX-EXXXX functions.

2.3.2 Event server

MSX-E systems embed an event server that can be used to monitor the current MSX-E state. An MSX-E system is logically divided in subsystem states. A subsystem is uniquely identified by a number, as well as each possible state associated to it. These numerical identifiers can be monitored by using the event server, which signals when the state of a subsystem has changed. The MSX-E will send a new event frame as soon as a subsystem state changes on the MSX-E.

2.3.3 Modbus server

A Modbus server, accessible on port 512 permits, for example, to manage MSX-E systems from a PLC. The port number, endianness (Intel / Motorola) and protocol (TCP/UDP) can be configured through the MSX-E web interface.

2.4 Common functions

Modules

- [Common general functions](#)

Various utility functions, mainly to identify a remote system.

- [Common temperature functions](#)

These functions deals with the internal temperature sub-system.

- [Common hardware trigger functions](#)

These functions allow to set and request the current value of the hardware trigger.

- [Common security functions](#)

The "customer key" feature may for instance be used by a customer to be sure that his application communicates only with certified MSX-E modules.

- [Common time functions](#)

A MSX-E module provides a "system clock" that may be in the simplest case set by the function `MXCommon_SetTime()`.

- [Common I/O auto configuration functions](#)

On the web site of some MSX-E module, there is the possibility to define an auto-configuration and auto start of the I/O.

- **Common synchronisation timer functions**

When modules are linked through a "synchronisation bus", the master can run a timer that generate a "synchro signal" on the slaves when overrun.

- **Set/Backup/Restore general system configuration**

Distinct of the I/O auto-configuration/auto-start functionality, these functions allows to manipulate the general system configuration.

- **System state management**

Every MSX-E modules are composed of several sub-systems that work together to provide the system functionalities.

- **Customer option management**

Enable to get informations about the options of the system.

- **Synchronisation management**

Manage the synchronisation state of the system.

2.5 Common general functions

Various utility functions, mainly to identify a remote system.

Functions

- int **MXCommon__GetModuleType** (void *_, struct **MXCommon__ByteArrayResponse** *Response)
This function return the type of the MSX-E Module.
- int **MXCommon__GetHostname** (void *_, struct **MXCommon__ByteArrayResponse** *Response)
This function return the hostname of the MSX-E Module.
- int **MXCommon__SetHostname** (struct **xsd__base64Binary** *bHostname, struct **MXCommon__Response** *Response)
This function allows to set the hostname of the MSX-E Module.
- int **MXCommon__GetClientConnections** (void *_, struct **MXCommon__ByteArrayResponse** *Response)
This function return the client connection list.
- int **MXCommon__Strerror** (xsd__int errnum, struct **MXCommon__ByteArrayResponse** *Response)
Call the libc strerror() on the remote device (actually this is a call to strerror_r()).
- int **MXCommon__Reboot** (void *_, struct **MXCommon__Response** *Response)
Ask the MSX-E module to reboot.

- int **MXCommon__ResetAllIOPFunctionalities** (xsd__unsignedLong ulOption, struct **MXCommon__Response** *Response)

Reset the I/O functionalities of the MSX-E system.
- int **MXCommon__DataserverRestart** (xsd__unsignedLong ulAction, xsd__unsignedLong ulOption, struct **MXCommon__Response** *Response)

Restart the data-server service.
- int **MXCommon__GetEthernetLinksStates** (void *_, struct **MXCommon__GetEthernetLinksStatesResponse** *Response)

Get MSX-E Ethernet links states.

2.5.1 Function Documentation

2.5.1.1 int **MXCommon__GetModuleType** (void * _, struct **MXCommon__ByteArrayResponse** * **Response**)

Parameters

- [in] _ : no input parameter
- [out] **Response**
 - sArray : Module type string
 - sResponse Composed of iReturnValue and syserrno

Return values

- SOAP_OK** SOAP call success
otherwise SOAP protocol error

2.5.1.2 int **MXCommon__GetHostname** (void * _, struct **MXCommon__ByteArrayResponse** * **Response**)

Parameters

- [in] _ : no input parameter
- [out] **Response**
 - sArray : Hostname of the module
 - iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - syserrno : System-error code. The value of the libc "errno" code, see **MXCommon__Strerror()**.

Return values

- SOAP_OK** SOAP call success
otherwise SOAP protocol error

2.5.1.3 int MXCommon_SetHostname (struct xsd_base64Binary * *bHostname*, struct MXCommon_Response * *Response*)

Parameters

- [in] *bHostname* : Hostname
- [out] *Response*
 - iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - syserrno : System-error code. The value of the libc "errno" code, see [MXCommon_Strerror\(\)](#).

Return values

- SOAP_OK* SOAP call success
otherwise SOAP protocol error

2.5.1.4 int MXCommon_GetClientConnections (void * *_*, struct MXCommon_ByteArrayResponse * *Response*)

Parameters

- [in] *_* : no input parameter
- [out] *Response*
 - sArray : string containing the list of connected clients.
 - sResponse Composed of iReturnValue and syserrno

The sArray string is of the form IP-Address:first connection-second connection---- IP-Address:first connection-second connection----

Sample: 172.16.3.43:8989-5555 172.16.3.200:8989

Return values

- SOAP_OK* SOAP call success
otherwise SOAP protocol error

2.5.1.5 int MXCommon_Strerror (xsd_int *errnum*, struct MXCommon_ByteArrayResponse * *Response*)

Usually SOAP functions return this value in a variable named syserror, which is meaningful only when the function return value, usually called iReturnValue, indicate an error (that is, have a value of -1 or -100, depending of the case).

Parameters

- [in] *errnum* : Error number
- [out] *Response*
 - sArray : See the description below.
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno).

- `sResponse.syserrno` : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

`STRERROR(3)`
`STRERROR(3)`

Linux Programmer's Manual

NAME
`strerror`, `strerror_r` - return string describing error code

SYNOPSIS

```
#include <string.h>

char *strerror(int errnum);

#define _XOPEN_SOURCE 600
#include <string.h>

int strerror_r(int errnum, char *buf, size_t n);
```

DESCRIPTION

The `strerror()` function returns a string describing the error code passed in the argument `errnum`, possibly using the `LC_MESSAGES` part of the current locale to select the appropriate language. This string must not be modified by the application, but may be modified by a subsequent call to `perror()` or `strerror()`. No library function will modify this string.

The `strerror_r()` function is similar to `strerror()`, but is thread safe. It returns the string in the user-supplied buffer `buf` of length `n`.

RETURN VALUE

The `strerror()` function returns the appropriate error description string, or an unknown error message if the error code is unknown. The value of `errno` is not changed for a successful call, and is set to a non-zero value upon error. The `strerror_r()` function returns 0 on success and -1 on failure, setting `errno`.

ERRORS

`EINVAL` The value of `errnum` is not a valid error number.

`ERANGE` Insufficient storage was supplied to contain the error description string.

CONFORMING TO

SVID 3, POSIX, 4.3BSD, ISO/IEC 9899:1990 (C89). `strerror_r()` with prototype as given above is specified by SUSv3, and was in use under Digital Unix and HP Unix. An incompatible function, with prototype

```
char *strerror_r(int errnum, char *buf, size_t n);
```

is a GNU extension used by glibc (since 2.0), and must be regarded as obsolete in view of SUSv3.

The GNU version may, but need not, use the user-supplied buffer.

If it does, the result may be truncated in case the supplied buffer is too small. The result is always NUL-terminated.

SEE ALSO

`errno(3)`, `perror(3)`, `strsignal(3)`

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

2.5.1.6 int MXCommon__Reboot (void * *_*, struct MXCommon__Response * *Response*)**Parameters**

- [in] *_* : no input parameter
- [out] ***Response*** • *iReturnValue* : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - *syserrno* : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

2.5.1.7 int MXCommon__ResetAllIOFunctionalities (xsd__unsignedLong *ulOption*, struct MXCommon__Response * *Response*)

The behavior of the function depends on the MSX-E system that is used.

On MSX-E3511: Stop the watchdogs and stop the generators

On MSX-E3601: Stop the sequence acquisition and stop the calibration

On MSX-E3701: Stop the acquisition

Parameters

- [in] ***ulOption*** Reserved. Set to 0
- [out] ***Response iReturnValue***
 - **0** The remote function performed OK
 - **-1** Internal system error occurred. See value of syserrno
 - **-100** Function not supported by the system

syserrno system error code (the value of the libc "errno" code)

Return values

0 ***SOAP_OK***

Others See SOAP error

2.5.1.8 int MXCommon__DataserverRestart (xsd__unsignedLong *ulAction*, xsd__unsignedLong *ulOption*, struct MXCommon__Response * *Response*)**Parameters**

- [in] ***ulAction*** : action
 - 0: normal restart
 - 1: with cache file reset
 - 2: with cache file deletion

[in] ***ulOption*** : Reserved

[out] ***Response iReturnValue*** : Return value

- 0 : success
- -1: system error (see syserrno)
- syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

Note

(revision>6386) Depending on the system type, can be used to restart the data-recv service as well. In this case, parameter action is ignored.

2.5.1.9 int MXCommon__GetEthernetLinksStates (void * __, struct MXCommon__GetEthernetLinksStatesResponse * Response)

Parameters

[in] __ : no input parameter

[out] **Response** Structure that contains the MSX-E Ethernet links states and errors:

sResponse.iReturnValue

- **0** The remote function performed OK
- **-1** System error occurred
- **-2** Fail to get Ethernet links states
- **-100** Internal system error occurred. See value of syserrno

sResponse.syserrno system error code (the value of the libc "errno" code)

sPort0: First port informations

- **ulState**
 - **0** Link down
 - **1** Link up
- **ulSpeed**
 - **10** 10 Mb/s
 - **100** 100 Mb/s
- **ulDuplex**
 - **0** Half duplex
 - **1** Full duplex
- **ulInfo1** Reserverd
- **ulInfo2** Reserverd

sPort1: Second port informations

- **ulState**
 - **0** Link down
 - **1** Link up
- **ulSpeed**
 - **10** 10 Mb/s
 - **100** 100 Mb/s
- **ulDuplex**

- **0** Half duplex
- **1** Full duplex
- **ulInfo1** Reserverd
- **ulInfo2** Reserverd

Return values

0 SOAP_OK

Others See SOAP error

2.6 Common temperature functions

These functions deals with the internal temperature sub-system.

Data Structures

- struct [MXCommon__GetModuleTemperatureValueAndStatusResponse](#)

Functions

- int [MXCommon__GetModuleTemperatureValueAndStatus](#) ([xsd__unsignedLong](#) ulOption, struct [MXCommon__GetModuleTemperatureValueAndStatusResponse](#) *Response)
Read the temperature on the module.
- int [MXCommon__SetModuleTemperatureWarningLevels](#) ([xsd__double](#) dMinimalWarningLevel, [xsd__double](#) dMaximalWarningLevel, [xsd__unsignedLong](#) ulOption, struct [MXCommon__Response](#) *Response)
Set the temperature warning level on the module.

2.6.1 Detailed Description

The role of this sub-system is to monitor the internal temperature of a module and issue a warning if it is below or above a threshold. If the internal temperature reaches a domain where the system is endangered, it switches automatically in a degraded working mode.

2.6.2 Function Documentation

2.6.2.1 int [MXCommon__GetModuleTemperatureValueAndStatus](#) ([xsd__unsignedLong](#) ulOption, struct [MXCommon__GetModuleTemperatureValueAndStatusResponse](#) * Response)

Parameters

- [in] **ulOption** : Reserved
- [out] **Response** • sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)

- `sResponse.syserrno` : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - `dValue` : Temperature value in Degree Celsius
- `ulTemperatureStatus` : Temperature Status :
 - `TEMPERATURE_INITIAL` = 0 : Temperature not ready
 - `TEMPERATURE_TOOWLOW` = 1 : Temperature too low !
 - `TEMPERATURE_LOW` = 2 : Temperature under the min warning value
 - `TEMPERATURE_NOMINAL` = 3 : Temperature in the nominal range
 - `TEMPERATURE_HIGH` = 4 : Temperature over the max warning value
 - `TEMPERATURE_TOOHIGH` = 5 : Temperature too high !
- `ulInfo` : Reserved

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

2.6.2.2 `int MXCommon__SetModuleTemperatureWarningLevels (xsd__double dMinimalWarningLevel, xsd__double dMaximalWarningLevel, xsd__unsignedLong ulOption, struct MXCommon__Response * Response)`

Parameters

- [in] `dMinimalWarningLevel` : Minimal temperature warning level in Degree : 5 to 60 Degree Celsius
- [in] `dMaximalWarningLevel` : Maximal temperature warning level in Degree : 5 to 60 Degree Celsius
- [in] `ulOption` : Reserved
- [out] `Response`
 - `sResponse.iReturnValue` : Return value
 - 0 : success
 - -1: system error (see `syserrno`)
 - `sResponse.syserrno` : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

2.7 Common hardware trigger functions

These functions allow to set and request the current value of the hardware trigger.

Data Structures

- struct [MXCommon__GetHardwareTriggerFilterTimeResponse](#)
- struct [MXCommon__GetHardwareTriggerStateResponse](#)

Functions

- int `MXCommon_SetHardwareTriggerFilterTime` (`xsd_unsignedLong ulFilterTime, xsd_-
unsignedLong ulOption, struct MXCommon_Response *Response`)
Set the filter time for the hardware trigger input in 250 ns step (max value : 65535).
- int `MXCommon_GetHardwareTriggerFilterTime` (`xsd_unsignedLong ulOption, struct
MXCommon_GetHardwareTriggerFilterTimeResponse *Response`)
Get the filter time for the hardware trigger input in 250 ns step (max value : 65535).
- int `MXCommon_GetHardwareTriggerState` (`xsd_unsignedLong ulOption, struct MXCommon_-
_GetHardwareTriggerStateResponse *Response`)
Get the hardware trigger state after the filter.

2.7.1 Function Documentation

2.7.1.1 int `MXCommon_SetHardwareTriggerFilterTime` (`xsd_unsignedLong ulFilterTime, xsd_unsignedLong ulOption, struct MXCommon_Response * Response`)

Parameters

[in] ***ulFilterTime*** : filter time for the hardware trigger input = multiplier from 250 ns step (max value : 65535).

- 0 : disable the filter
- >1: enable the filter and set the filter time

[out] ***Response*** • `sResponse.iReturnValue` : Return value

- 0 : success
- -1: system error (see syserrno)
- `sResponse.syserrno` : System-error code. The value of the libc "errno" code, see `MXCommon_Strerror()`.

[in] ***ulOption*** Reserved

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

2.7.1.2 int `MXCommon_GetHardwareTriggerFilterTime` (`xsd_unsignedLong ulOption, struct MXCommon_GetHardwareTriggerFilterTimeResponse * Response`)

Parameters

[in] ***ulOption*** : Reserved

[out] ***Response*** • `ulFilterTime` : filter time for the hardware trigger input = multiplier from 250 ns step (max value : 65535).

- 0 : filter disabled
- >1: Filter enabled.

- `sResponse.iReturnValue` : Return value
- 0 : success

- -1: system error (see syserrno)
- sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

2.7.1.3 int MXCommon__GetHardwareTriggerState (xsd__unsignedLong *ulOption*, struct MXCommon__GetHardwareTriggerStateResponse * *Response*)

Parameters

- [in] *ulOption* : Reserved
- [out] **Response**
 - ulState : Hardware trigger input state.
 - 0: Hardware trigger input is low
 - 1: Hardware trigger input is high.
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

2.8 Common security functions

The "customer key" feature may for instance be used by a customer to be sure that his application communicates only with certified MSX-E modules.

Data Structures

- struct [MXCommon__TestCustomerIDResponse](#)

Functions

- int [MXCommon__SetCustomerKey](#) (struct xsd__base64Binary *bKey, struct xsd__base64Binary *bPublicKey, struct [MXCommon__Response](#) *Response)
Set the Customer key.
- int [MXCommon__TestCustomerID](#) (void *_ , struct [MXCommon__TestCustomerIDResponse](#) *Response)
Test the Customer ID (if the module has the right customer Key).

2.8.1 Detailed Description

A "customer key" consists of two strings of data stored on the certified MSX-E module, to be used by the function [MXCommon__TestCustomerID\(\)](#) to encrypt data.

These strings can not be read back. They are supposed to be kept secret by the user of this functionality.

To test if the MSX-E module you use is certified, you can request the MSX-E module to provide a set of randomly generated data and the result of the encryption (through the use of the stored "customer key") of the same data. Then your application must encrypt the delivered random data with its own "customer key" and compare it with the encrypted data delivered by the MSX-E module.

If the results are matching, the MSX-E module is certified for this application.

Detailed presentation of operations:

The user generates and stores on the module two keys (thanks to the software function : [MXCommon__SetCustomerKey\(\)](#)). This needs only to be done once:

- A public Key K1 (16 Bytes)
- A private Key K2 (32 Bytes)

When requested (with the software function : [MXCommon__TestCustomerID\(\)](#)), the module generates a 16 bytes random value and do an encryption of this value using the two saved keys and the AES algorithm (Rijndael).

The user receives then two arrays of 16 bytes :

- one with a random value [A]
- the second with encrypted random value [B]

[B]=AES([A], K1, K2)

The user performs then the same computation from [A],K1,K2 and compares his result with [B]. If it is the same, it means that the module he is using was already configured with the correct identification token.

The security of the method comes from that even knowing [A] and [B] no one can deduce K1 and K2 back in practical times. ADDI-DATA is not aware of a practical way to remotely retrieve the value of the key stored on a module.

It is the responsibility of the developer of the application to ensure that these tokens are suitably protected. The authorisation of the change of the "customer key" on the MSX-E module can be managed with the web interface.

The use of the "customer key" don't have an impact of the other functionalities of the MSX-E module.

2.8.2 Function Documentation

2.8.2.1 int MXCommon__SetCustomerKey (struct xsd__base64Binary * bKey, struct xsd__base64Binary * bPublicKey, struct MXCommon__Response * Response)

Parameters

- [in] **bKey** : Customer key (only writable on the module) [32 bytes containing a AES key]
- [in] **bPublicKey** : IV (Initialisation vector) for the AES cryptography [16 bytes containing a AES key]
- [out] **Response** • sResponse.iReturnValue : Return value

- 0 : success
- -1: system error (see syserrno)
- sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

2.8.2.2 int MXCommon__TestCustomerID (void * ___, struct MXCommon__- TestCustomerIDResponse * Response)

Parameters

- [in] ___ : No Input
- [out] **Response**
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - bValueArray : non encrypted value array [16 bytes of random data]
 - bCryptedValueArray : Encrypted value array [16 bytes of the encrypted random data]

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

2.9 Common time functions

A MSX-E module provides a "system clock" that may be in the simplest case set by the function [MXCommon__SetTime\(\)](#).

Data Structures

- struct [MXCommon__GetTimeResponse](#)
- struct [MXCommon__GetUpTimeResponse](#)

Functions

- int [MXCommon__SetTime](#) (xsd__unsignedLong ulLowTime, xsd__unsignedLong ulHighTime, struct [MXCommon__Response](#) *Response)

Set the time on the module.

- int [MXCommon__SysToHardwareClock](#) (void * ___, struct [MXCommon__Response](#) *Response)

Set the hardware clock (if present) to the current system time.

- int [MXCommon__HardwareClockToSys](#) (void *_, struct [MXCommon__Response](#) *Response)
Set the system time from the hardware clock (if present).
- int [MXCommon__GetTime](#) (void *_, struct [MXCommon__GetTimeResponse](#) *Response)
Get the time on the module.
- int [MXCommon__GetUpTime](#) (void *_, struct [MXCommon__GetUpTimeResponse](#) *Response)
Ask the MSX-E module uptime (number of seconds since the last boot).

2.9.1 Detailed Description

If the module is configured to use NTP, the time received by the NTP server will have a greater priority. If the module is linked to another through a "synchronization bus" and is slave, then the time received from the master is the one taken into account.

Recent models also provide a "hardware clock", a component whose role is to track the time between reboots.

2.9.2 Function Documentation

2.9.2.1 int [MXCommon__SetTime](#) (xsd__unsignedLong *ulLowTime*, xsd__unsignedLong *ulHighTime*, struct [MXCommon__Response](#) * *Response*)

Parameters

- [in] *ulLowTime* : Number of microseconds since the begin of the second
- [in] *ulHighTime* : Number of seconds since the Epoch (1st January,1970)
- [out] *Response*
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

2.9.2.2 int [MXCommon__SysToHardwareClock](#) (void *_, struct [MXCommon__Response](#) * *Response*)

Parameters

- [in] _ No input parameter
- [out] *Response*
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

- SOAP_OK*** SOAP call success
- otherwise*** SOAP protocol error

If this function fails, it means the module does not have a hardware RTC, or the hardware is not functional. Check the "hwclock" subsystem status.

2.9.2.3 **int MXCommon__HardwareClockToSys (void * __, struct MXCommon__Response * Response)**

When the hardware clock is present, the system time is automatically set to it when the module becomes master on the inter-module synchronisation bus.

Parameters

- [in] __ No input parameter
- [out] ***Response***
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

- SOAP_OK*** SOAP call success
- otherwise*** SOAP protocol error

If this function fails, it means the module does not have a hardware RTC, or the hardware is not functional. Check the "hwclock" subsystem status.

2.9.2.4 **int MXCommon__GetTime (void * __, struct MXCommon__GetTimeResponse * Response)**

Parameters

- [in] __ : No input parameter
- [out] ***Response***
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - ulLowTime : Number of microseconds since the begin of the second
 - ulHighTime : Number of seconds since the Epoch (1st January,1970)

Return values

- SOAP_OK*** SOAP call success
- otherwise*** SOAP protocol error

2.9.2.5 int MXCommon__GetUpTime (void * _, struct MXCommon__GetUpTimeResponse * Response)

Parameters

- [in] _ : no input parameter
- [out] **Response**
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - ulUpTime : Number of seconds since the last boot of the system.

Return values

- SOAP_OK** SOAP call success
- otherwise** SOAP protocol error

2.10 Common I/O auto configuration functions

On the web site of some MSX-E module, there is the possibility to define an auto-configuration and auto start of the I/O.

Data Structures

- struct [MXCommon__GetAutoConfigurationFileResponse](#)

Functions

- int [MXCommon__GetAutoConfigurationFile](#) (void *_, struct [MXCommon__GetAutoConfigurationFileResponse](#) *Response)

Get the auto configuration file of the module.
- int [MXCommon__SetAutoConfigurationFile](#) (struct [xsd__base64Binary](#) *ByteArrayInput, [xsd__unsignedLong](#) ulEOF, struct [MXCommon__Response](#) *Response)

Set the auto configuration file of the module.
- int [MXCommon__StartAutoConfiguration](#) (void *_, struct [MXCommon__ByteArrayResponse](#) *Response)

start/Restart the auto configuration

2.10.1 Detailed Description

- Auto-configuration means the system configures the I/O automatically at boot time.
- Auto-start means the system starts an acquisition automatically at boot time (this may not make sense for some systems). It implies auto-configuration.

This set of functions allows to:

- get the auto-configuration/start currently set on module, as a read-only binary file.
- set a auto-configuration/start on the module, using a previously saved file.
- start or restart the auto-configuration/start on the module, using the current configuration saved on the module.

2.10.2 Function Documentation

2.10.2.1 int MXCommon__GetAutoConfigurationFile (void * __, struct MXCommon__GetAutoConfigurationFileResponse * Response)

Parameters

- [in] *_* : No input parameter
- [out] **Response**
- sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - -100 : Error of the read of the auto configuration file
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - bArray : Array of Bytes of the file
 - ulEOF : End of file flag

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

2.10.2.2 int MXCommon__SetAutoConfigurationFile (struct xsd__base64Binary * ByteArrayInput, xsd__unsignedLong ulEOF, struct MXCommon__Response * Response)

Parameters

- [in] **ByteArrayInput** : Array of Bytes of the file
- [in] **ulEOF** : End of file flag
- [out] **Response**
- sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

2.10.2.3 int MXCommon_StartAutoConfiguration (void * ___, struct MXCommon_ByteArrayResponse * Response)

Parameters

- [in] ___ : No input parameter
- [out] **Response**
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon_Strerror\(\)](#).
 - sArray : message returned by the auto configuration start

Return values

- SOAP_OK** SOAP call success
- otherwise** SOAP protocol error

2.11 Common synchronisation timer functions

When modules are linked through a "synchronisation bus", the master can run a timer that generate a "synchro signal" on the slaves when overrun.

Functions

- int [MXCommon_InitAndStartSynchroTimer](#) (xsd__unsignedLong ulTimeBase, xsd__unsignedLong ulReloadValue, xsd__unsignedLong ulNbrOfCycle, xsd__unsignedLong ulGenerateTriggerMode, xsd__unsignedLong ulOption01, xsd__unsignedLong ulOption02, xsd__unsignedLong ulOption03, xsd__unsignedLong ulOption04, struct [MXCommon_Response](#) *Response)

Initialises and starts the synchronisation timer of the module (not already available on all module).
- int [MXCommon_StopAndReleaseSynchroTimer](#) (xsd__unsignedLong ulOption01, struct [MXCommon_Response](#) *Response)

start/Restart the synchronisation timer (not already available on all module)

2.11.1 Function Documentation

2.11.1.1 int MXCommon_InitAndStartSynchroTimer (xsd__unsignedLong ulTimeBase, xsd__unsignedLong ulReloadValue, xsd__unsignedLong ulNbrOfCycle, xsd__unsignedLong ulGenerateTriggerMode, xsd__unsignedLong ulOption01, xsd__unsignedLong ulOption02, xsd__unsignedLong ulOption03, xsd__unsignedLong ulOption04, struct [MXCommon_Response](#) * Response)

Parameters

- [in] **ulTimeBase** : Time base of the timer (0 for us, 1 for ms, 2 for s)
- [in] **ulReloadValue** : Timer reload value (0 to 0xFFFF), minimum reload time is 5 us
- [in] **ulNbrOfCycle** : Number of timer cycle

- 0: continuous
 - > 0: defined number of cycle
- [in] ***ulGenerateTriggerMode*** :
- 0: Wait the time overflow to set the synchronisation trigger
 - 1: Set the synchronisation trigger by the start of the timer and after each time overflow
- [in] ***ulOption01*** : Define the source of the trigger
- 0 : Trigger disabled
 - 1 : Enable the hardware digital input trigger
- [in] ***ulOption02*** : Define the edge of the hardware trigger who generates a trigger action
- 1 : rising edge (Only if hardware trigger selected)
 - 2 : falling edge (Only if hardware trigger selected)
 - 3 : Both front (Only if hardware trigger selected)
- [in] ***ulOption03*** : Define the number of trigger events before the action occur
- 1 : all trigger event start the action
 - max value : 65535
- [in] ***ulOption04*** : Reserved
- [out] ***Response***
- sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - -2: not available time base
 - -3: timer reload value can not be greater than 65535
 - -4: minimum time reload is 5 us
 - -5: Number of cycle can not be greater than 65535
 - -6: Generate trigger mode error
 - -100: Init timer error
 - -101: Start timer error
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#). May be ENOSYS : Function not implemented.

Return values

- SOAP_OK*** SOAP call success
otherwise SOAP protocol error

2.11.1.2 int MXCommon__StopAndReleaseSynchroTimer (xsd__unsignedLong *ulOption01*, struct MXCommon__Response * *Response*)

Parameters

- [in] ***ulOption01*** : Reserved
- [out] ***Response***
- sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - -100: Start/Stop timer error
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#). May be ENOSYS : Function not implemented.

Return values

- SOAP_OK*** SOAP call success
otherwise SOAP protocol error

2.12 Set/Backup/Restore general system configuration

Distinct of the I/O auto-configuration/auto-start functionality, these functions allows to manipulate the general system configuration.

Functions

- int `MXCommon__GetConfigurationBackupFile` (void *_, struct `MXCommon__FileResponse` *Response)
Download a configuration backup file from the module.
- int `MXCommon__ApplyConfigurationBackupFile` (struct `xsd__base64Binary` *ByteArrayInput,
`xsd__unsignedLong` ulEOF, struct `MXCommon__Response` *Response)
Upload a new configuration on the module.
- int `MXCommon__ChangePassword` (struct `xsd__base64Binary` *PreviousUser, struct `xsd__base64Binary` *PreviousPassword, struct `xsd__base64Binary` *NewUser, struct `xsd__base64Binary` *NewPassword, struct `MXCommon__Response` *Response)
Set a new id/password.

2.12.1 Detailed Description

It includes the network configuration, and generally everything that can be set up through the web interface. These functions have been included to ease the automation of module customisation. They may be disabled using the web interface, in "Security/Remote general system configuration authorisation/remote sysconf changes"

2.12.2 Function Documentation

2.12.2.1 int `MXCommon__GetConfigurationBackupFile` (void * _, struct `MXCommon__FileResponse` * Response)

Parameters

- [in] _ : No input parameter
- [out] ***Response*** • sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno) (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see `MXCommon__Strerror()`.
 - bArray : Array of Bytes of the file
 - ulEOF : End of file flag

Return values

- SOAP_OK*** SOAP call success
otherwise SOAP protocol error

This function is designed to be called repeatedly until no more data is available. At this point the flag ulEOF is set.

Below is an example in pseudo-C.

```
int dummy;
struct MXCommon__FileResponse Response;
while(1)
{
if ( MXCommon__GetConfigurationBackupFile(&dummy, &Response) != SOAP_OK)
{
// handle soap error
}
if (Response.iReturnValue)
{
// handle remote error (Response.syserrno contains more information)
}
// do something with the data, for example save it in a file
write(fd, Response.bArray.__ptr, Response.bArray.__size);
// if this is the end of the file, quit the loop
if(Response.ulEOF)
break;
}
*
```

2.12.2.2 int MXCommon__ApplyConfigurationBackupFile (struct xsd__base64Binary * ByteArrayInput, xsd__unsignedLong ulEOF, struct MXCommon__Response * Response)

Parameters

- [in] **ByteArrayInput** : Array of Bytes of the file
- [in] **ulEOF** : End of file flag
- [out] **Response**
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

This function is designed to be called repeatedly until all data is transferred. At this point the flag ulEOF must be set to 1. The new configuration is then applied.

2.12.2.3 int MXCommon__ChangePassword (struct xsd__base64Binary * PreviousUser, struct xsd__base64Binary * PreviousPassword, struct xsd__base64Binary * NewUser, struct xsd__base64Binary * NewPassword, struct MXCommon__Response * Response)

The changes are immediately active.

Parameters

- [in] _ : No input parameter

- [out] **Response**
- sResponse.iReturnValue : Return value
 - 0 : success
 - -1: string PreviousUser is invalid
 - -2: string PreviousPassword is invalid
 - -3: string NewUser is invalid
 - -4: string NewPassword is invalid
 - -5: authentication failed
 - -100: system error while saving tokens (use syserrno for more information)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - sArray : message returned by the auto configuration start

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

Warning

The parameters transit in clear text. Use this functionality only on trusted networks.
 Given that ADDI-DATA GmbH takes security seriously, there is no way to change the password without knowing it. No "hidden back-door". This function makes it all too easy to lock a module, if you don't remember the password you set on it.

2.13 System state management

Every MSX-E modules are composed of several sub-systems that work together to provide the system functionalities.

Functions

- int [MXCommon__GetSubSystemState](#) (xsd__unsignedLong SubsystemID, struct [MXCommon__UnsignedLongResponse](#) *Response)

Returns the current state of the specified sub-system.
- int [MXCommon__GetSubsystemIDFromName](#) (struct xsd__base64Binary *SubsystemName, struct [MXCommon__UnsignedLongResponse](#) *Response)

Returns the ID of the sub-system of symbolic name "SubsystemName".
- int [MXCommon__GetStateIDFromName](#) (xsd__unsignedLong SubsystemID, struct xsd__base64Binary *StateName, struct [MXCommon__UnsignedLongResponse](#) *Response)

Returns the ID of the state of symbolic name "StateName" of the sub-system of ID "SubsystemID".
- int [MXCommon__GetSubsystemNameFromID](#) (xsd__unsignedLong SubsystemID, struct [MXCommon__ByteArrayResponse](#) *Response)

Returns the symbolic name of the sub-system of numerical ID "SubsystemName".
- int [MXCommon__GetStateNameFromID](#) (xsd__unsignedLong SubsystemID, xsd__unsignedLong StateID, struct [MXCommon__ByteArrayResponse](#) *Response)

Returns the symbolic name of the state of numerical ID "StateID" of the sub-system of ID "SubsystemID".

2.13.1 Detailed Description

These sub-systems have a state that, for example, indicate if it functions nominally.

A sub-system is identified by its ID (a positive integer) and its symbolic name. Each state in the set of possible states for a given sub-system has also an ID and a symbolic name.

Names are less likely to change between releases of the MSX-E operating system. That is why manipulating names should be preferred against indexes in an application. Still, manipulating ID is more efficient.

The functions in this section provide a way to retrieve the association between names and indexes. [MXCommon__GetSubSystemState\(\)](#) requests the state of a given sub-system.

Notice that the event manager is the recommended way to be warned of a change of state.

The list of sub-systems and their ID and associated name can be consulted on the web site of the module.

2.13.2 Function Documentation

2.13.2.1 int MXCommon__GetSubSystemState (xsd__unsignedLong SubsystemID, struct MXCommon__unsignedLongResponse * Response)

Parameters

- [in] *SubsystemID* sub-system numerical ID
- [out] *Response*
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error while executing the request (see syserrno)
 - -2: invalid parameter SubsystemID
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - Value The state of the sub-system "Id" at the moment of the execution of the request.

Return values

- SOAP_OK** SOAP call success
- otherwise** SOAP protocol error

2.13.2.2 int MXCommon__GetSubsystemIDFromName (struct xsd__base64Binary * SubsystemName, struct MXCommon__unsignedLongResponse * Response)

Parameters

- [in] *SubsystemName* sub-system symbolic name.
- [out] *Response*
 - sResponse.iReturnValue :Return value
 - 0 : success
 - -1: system error while executing the request (see syserrno)
 - -2: invalid parameter SubsystemName
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - Value The numerical ID of the sub-system "SubsystemName".

Return values

- SOAP_OK** SOAP call success

otherwise SOAP protocol error

2.13.2.3 int MXCommon__GetStateIDFromName (xsd__unsignedLong *SubsystemID*, struct xsd__base64Binary * *StateName*, struct MXCommon__unsignedLongResponse * *Response*)

Parameters

- [in] *SubsystemID* sub-system numerical ID
- [in] *StateName* state symbolic name.
- [out] *Response*
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error while executing the request (see syserrno)
 - -2: invalid parameters SubsystemID or StateName
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - Value The numerical ID of the state "StateName".

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

2.13.2.4 int MXCommon__GetSubsystemNameFromID (xsd__unsignedLong *SubsystemID*, struct MXCommon__ByteArrayResponse * *Response*)

Parameters

- [in] *SubsystemID* sub-system numerical ID.
- [out] *Response*
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error while executing the request (see syserrno)
 - -2: invalid parameter SubsystemName
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - sArray : The symbolic name associated with the ID.

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

2.13.2.5 int MXCommon__GetStateNameFromID (xsd__unsignedLong *SubsystemID*, xsd__unsignedLong *StateID*, struct MXCommon__ByteArrayResponse * *Response*)

Parameters

- [in] *SubsystemID* sub-system numerical ID.
- [in] *StateID* sub-system numerical ID.

- [out] **Response**
- sResponse.iReturnValue : Return value
 - 0 success
 - -1 system error while executing the request (see syserrno)
 - -2 invalid parameters SubsystemID or StateID
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - sArray The symbolic name associated with the state numerical ID.

Return values

- SOAP_OK** SOAP call success
otherwise SOAP protocol error

2.14 Customer option management

Enable to get informations about the options of the system.

Functions

- int [MXCommon__GetOptionInformation](#) (void *_, xsd__unsignedLong ulOption01, xsd__unsignedLong ulOption02, struct [MXCommon__ByteArrayResponse](#) *Response)
- Enables to get information about the options available on the system.*

2.14.1 Function Documentation

2.14.1.1 int MXCommon__GetOptionInformation (void *_ , xsd__unsignedLong *ulOption01*, xsd__unsignedLong *ulOption02*, struct MXCommon__ByteArrayResponse * *Response*)

Parameters

- [in] *ulOption01*: not used, set it to 0
 [in] *ulOption02*: not used, set it to 0
 [out] **Response**
- sArray : Option information string
 - sResponse Composed of iReturnValue and syserrno

Return values

- SOAP_OK** SOAP call success
otherwise SOAP protocol error

2.15 Synchronisation management

Manage the synchronisation state of the system.

Functions

- int `MXCommon_SetToMaster` (void *`_`, xsd_unsignedLong `ulState`, xsd_unsignedLong `ulOption01`, xsd_unsignedLong `ulOption02`, struct `MXCommon_Response` *`Response`)

Writes if the MSXE has to be always set to master. The master mode (when enabled) make the system always detected as master.

- int `MXCommon_GetSynchronizationStatus` (void *`_`, xsd_unsignedLong `ulOption01`, xsd_unsignedLong `ulOption02`, struct `MXCommon_unsignedLongResponse` *`Response`)

Reads the status of the synchronization for the corresponding MSXE. The master mode (when enabled) make the system always detected as master.

2.15.1 Function Documentation

- 2.15.1.1 int `MXCommon_SetToMaster` (void *`_`, xsd_unsignedLong `ulState`, xsd_unsignedLong `ulOption01`, xsd_unsignedLong `ulOption02`, struct `MXCommon_Response` * `Response`)**

Parameters

[in] `ulState` State of the supermaster mode

- **0** automatic mode (default). The state of the system (master or slave) will be automatically detected by the system
- **1** Set to master mode at all time. The system will always be detected as master

[in] `ulOption01` Reserved. Set to 0

[in] `ulOption02` Reserved. Set to 0

[out] `Response iReturnValue`

- **0** The remote function performed OK
- **-1** System error occurred
- **-2** The PLD is not working
- **-3** The `ulFilterTime` parameter is wrong
- **-100** Internal system error occurred. See value of syserrno `syserrno` system error code (the value of the libc "errno" code)

Return values

0 SOAP_OK

Others See SOAP error

- 2.15.1.2 int `MXCommon_GetSynchronizationStatus` (void *`_`, xsd_unsignedLong `ulOption01`, xsd_unsignedLong `ulOption02`, struct `MXCommon_unsignedLongResponse` * `Response`)**

Parameters

[in] `ulOption01` Reserved. Set to 0

[in] `ulOption02` Reserved. Set to 0

[out] `Response sResponse.iReturnValue`

- **0** The remote function performed OK
- **-1** System error occurred
- **-2** The PLD is not working
- **-100** Internal system error occurred. See value of syserrno

sResponse.syserrno system error code (the value of the libc "errno" code)

ulValue State of the supermaster mode

- **0** Automatic mode (default). The state of the system (master or slave) will be automatically detected by the system
- **1** MSXE is always set as a master. The system will always be detected as master

Return values

0 SOAP_OK

Others See SOAP error

2.16 MSX-E302x functions

Modules

- [MSX-E302x Information functions](#)
- [MSX-E302x Autorefresh functions](#)

In the auto refresh mode the measurement value is updated automatically after each acquisition.

- [MSX-E302x Sequence functions](#)

A sequence is a list of channels (max 16) that are acquired.

- [MSX-E302x calibration functions](#)

The calibration functions permit to calibrate the analog input of the module.

2.17 MSX-E302x Information functions

Data Structures

- struct [MSXE302x__AnalogInputGetChannelTypeResponse](#)

Functions

- int [MSXE302x__AnalogInputGetChannelType](#) ([xsd__unsignedLong](#) ulOption1, struct [MSXE302x__AnalogInputGetChannelTypeResponse](#) *Response)
Return the type of the analog input channels.
- int [MSXE302x__AnalogMeasureGetConfiguration](#) ([xsd__unsignedLong](#) ulModule, struct [MSXE302x__AnalogMeasureGetConfigurationResponse](#) *Response)
Return the running configuration.

2.17.1 Function Documentation

2.17.1.1 int MSXE302x__AnalogInputGetChannelType (xsd__unsignedLong *ulOption1*, struct MSXE302x__AnalogInputGetChannelTypeResponse * *Response*)

Parameters

[in] *ulOption1* : Reserved

[out] *Response* :

iReturnValue :

- 0: means the remote function performed OK
- -1: means an system error occurred

syserrno : system-error code (the value of the libc "errno" code) *ulType* : Array that contain the channels type (0 : voltage, 1 : current)

- *ulType* [0] : Channel 0 type
- ...
- *ulType* [15] : Channel 15 type

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

2.17.1.2 int MSXE302x__AnalogMeasureGetConfiguration (xsd__unsignedLong *ulModule*, struct MSXE302x__AnalogMeasureGetConfigurationResponse * *Response*)

Parameters

[in] *ulOption1* : Reserved

[out] *Response* :

iReturnValue :

- 0: means the remote function performed OK
- -1: means an system error occurred

sAcquisition :

- *ulConvertTimeUnit* 0: micro second 1: milli second 2: second
- *pul_ConvertTimeValue* : (10,65535)
- *pul_ChannelInitialisation* (Are channels initialised and how) pointer to unsigned long[16]. bit 31 = initialised : (0,1) bit 30= polarity : (0,1) - 0:bipolar, 1:unipolar bits 29-0 : gain : (1,2) - 0: 10 V , 1: 5V

sAutoRefresh :

- *ulChannelMask* Mask of channels used for the auto refresh mode
- *ulAverageMode* Determine average mode 0: Sequence 1 : Channel
- *ulAverageValue* Determine the number of sequence for a average value calculation
- *ulDataFormat* D0: Time stamp information. 0 without, 1 with. D1 : Data format 0: digital 1: analog (in V)

sSequence :

- *ulSequenceSize* Sequence array size
- *ulSequence* Sequence channel array

- *ulSequenceInterrupt* Determine the number of sequences for the interrupt
- *ulNbrOfSequence* Determine the number total of sequences. 0: Continuous
- *ulDelayFlag* 0 : Disabled 1 : Enabled
- *ulDelayMode* 0 : delay not used 1 : mode 1 2 : mode 2
- *ulDelayTimeUnit* Delay time unit 1: micros 2 : ms 3 : s
- *ulDelayTime* Delay time
- *ulDataFormat* D0: Time stamp information. 0 without, 1 with.
D1 : Sequence counter information. 0 without, 1 with.
D2 : Data format 0: digital 1: analog (in V)

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

2.18 MSX-E302x Autorefresh functions

In the auto refresh mode the measurement value is updated automatically after each acquisition.

Data Structures

- struct [MSXE302x__AnalogInputGetAutoRefreshValuesResponse](#)

Functions

- int [MSXE302x__AnalogInputInitAndStartAutoRefresh](#) (*xsd__unsignedLong* ulChannelMask, struct [MSXE302x__unsignedLong16FixedArrayParam](#) *pulGainArray, struct [MSXE302x__unsignedLong16FixedArrayParam](#) *pulPolarityArray, *xsd__unsignedLong* ulAverageMode, *xsd__unsignedLong* ulAverageValue, *xsd__unsignedLong* ulConversionTime, *xsd__unsignedLong* ulConversionTimeUnit, *xsd__unsignedLong* ulTriggerMask, *xsd__unsignedLong* ulTriggerMode, *xsd__unsignedLong* ulHardwareTriggerEdge, *xsd__unsignedLong* ulHardwareTriggerCount, *xsd__unsignedLong* ulByTriggerNbrOfSeqToAcquire, *xsd__unsignedLong* ulDataFormat, *xsd__unsignedLong* ulOption1, *xsd__unsignedLong* ulOption2, *xsd__unsignedLong* ulOption3, struct [MSXE302x__Response](#) *Response)

Starts an autorefresh acquisition using provided configuration.

- int [MSXE302x__AnalogInputGetAutoRefreshValues](#) (void *_, struct [MSXE302x__AnalogInputGetAutoRefreshValuesResponse](#) *Response)

Returns the values acquired in auto refresh mode.

- int [MSXE302x__AnalogInputStopAndReleaseAutoRefresh](#) (void *_, struct [MSXE302x__Response](#) *Response)

Stops the current autorefresh acquisition.

2.18.1 Detailed Description

The analog acquisition is initialised and the values of each channels are stored in memory on the Ethernet E/A module MSX-E302x.

The PC reads the data asynchronously to the acquisition via the data socket or a SOAP function.

You can define a mask of all channels that should be acquired.

In the auto refresh mode you can activate the channel average value computation on the module:

- Average value calculation per channel : Each channel is acquired x times to compute an average value for the channel.
- Average value calculation per sequence : All sequences are acquired x times to compute a average value per channel.

You can start the acquisition by a hardware trigger or a synchro trigger.

The hardware trigger can react to a rising wave, falling wave or both edges.

You have the following possibility:

- Defining a number of edges before a trigger action is generated

There are two trigger modes:(for the hardware or synchro trigger)

a) One shot

b) Sequence

a) One shot:

After the software start, the module is waiting for a trigger signal to start the acquisition. After this the trigger signal is ignored.

b) Sequence:

After the software start the module is waiting for the trigger signal and acquires x sequences (also adjustable) and then wait again.

2.18.2 Function Documentation

```
2.18.2.1 int MSXE302x__AnalogInputInitAndStartAutoRefresh ( xsd__unsignedLong
    ulChannelMask, struct MSXE302x__unsignedLong16FixedArrayParam
    * pulGainArray, struct MSXE302x__unsignedLong16FixedArrayParam *
    pulPolarityArray, xsd__unsignedLong ulAverageMode, xsd__unsignedLong
    ulAverageValue, xsd__unsignedLong ulConversionTime, xsd__unsignedLong
    ulConversionTimeUnit, xsd__unsignedLong ulTriggerMask, xsd__unsignedLong
    ulTriggerMode, xsd__unsignedLong ulHardwareTriggerEdge, xsd__unsignedLong
    ulHardwareTriggerCount, xsd__unsignedLong ulByTriggerNbrOfSeqToAcquire,
    xsd__unsignedLong ulDataFormat, xsd__unsignedLong ulOption1, xsd__unsignedLong
    ulOption2, xsd__unsignedLong ulOption3, struct MSXE302x__Response * Response )
```

Parameters

[in] **ulChannelMask** Mask of the channel to acquire by the auto refresh (1 bit = 1 Channel)

[in] **pulGainArray** Define the gain (1 or 2) to use for each channel.

Information : by the channel type "current", the gain 2 is recommended.

- 1 : +10 V or max 20mA when Unipolar, +/-10V or +/- max 20mA when Bipolar

- 2 : +5 V or 20mA when Unipolar, +/-5V or +/- 20mA when Bipolar Each index of the array correspond to the channel :

sample :

- [0] : Define the gain for the channel 0
- [1] : Define the gain for the channel 1
- ...

Remark: When using a current version of the MSX-E302x, gain 2 has to be used.

[in] **pulPolarityArray** Define the polarity (0:Unipolar or 1:Bipolar) to use for each channel Each index of the array correspond to the channel :

sample :

- [0] : Define the polarity for the channel 0
- [1] : Define the polarity for the channel 1
- ...

Remark: When using the unipolar mode, the raw value for 0 volt (or 0 ampere) will be 32767.

[in] **ulAverageMode** Set the average mode :

- 0 : not used
- 1 : average per Sequence
- 2 : average per channel

[in] **ulAverageValue** Set the average value (only used, when average is used) :

- 0 : not used
- max value : 255

[in] **ulConversionTime** Conversion Time

- range from min 10 to 65535 when the unit is the microsecond
- range from min 1 to 65535 when the unit is the millisecond
- range from min 1 to 65535 when the unit is the second

[in] **ulConversionTimeUnit** Conversion Time Unit

- 0 : microsecond
- 1 : millisecond
- 2 : second

[in] **ulTriggerMask** Define the source of the trigger

- 0 : trigger disabled
- 1 : Enable Hardware Digital Input Trigger
- 2 : Enable Synchro Trigger

[in] **ulTriggerMode** Define the trigger mode

- 1 : One shot trigger
- 2 : Sequence trigger

[in] **ulHardwareTriggerEdge** Define the edge of the hardware trigger who generates a trigger action

- 1 : rising edge (Only if hardware trigger selected)
- 2 : falling edge (Only if hardware trigger selected)
- 3 : Both front (Only if hardware trigger selected)

[in] **ulHardwareTriggerCount** Define the number of trigger events before the action occur

- 0 or 1 : all trigger event start the action
- max value : 65535

[in] ***ulByTriggerNbrOfSeqToAcquire*** Define the number of sequence to acquire by each trigger event

- 0 : continuous mode
- <> 0 : number of sequence : (1..0xFFFFFFFF)

[in] ***ulDataFormat*** D0 : Time stamp information

- 0: no time stamp information
- 1: time stamp information

D1 : Data format

- 0: Digital value
- 1: Analog value (in V)

[in] ***ulOption1*** Reserved

[in] ***ulOption2*** Reserved

[in] ***ulOption3*** Reserved

[out] ***Response*** :

iReturnValue :

- 0 : means the remote function performed OK
- -1: means an system error occured
- -2: The channel mask cannot be null
- -3: Channel Mask error
- -4: Gain selection error
- -5: Polarity selection error
- -6: not available average mode
- -7: not available average value
- -8: The minimal converting time is 10 us !
- -9: Not available conversion time unit
- -10: Trigger mode : 2 different mode cannot be simultaneously be activated
- -11: Hardware trigger : front definition error
- -12: Hardware trigger count value not available
- -13: Nbr of sequence to acquire by trigger mode not available
- -14: Data format not available
- -100: Channel initialisation kernel function error
- -101: Conversion time initialisation kernel function error
- -102: Average mode initialisation kernel function error
- -103: hardware trigger initialisation/enable kernel function error
- -104: hardware trigger disable kernel function error
- -105: synchro trigger initialisation/enable kernel function error
- -106: synchro trigger disable kernel function error
- -107 Sequence trigger count initialisation error
- -108: Start auto refresh kernel function error

syserrno : system-error code (the value of the libc "errno" code)

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

2.18.2.2 int MSXE302x__AnalogInputGetAutoRefreshValues (void * __, struct MSXE302x__AnalogInputGetAutoRefreshValuesResponse * *Response*)

Parameters

[in] _ Dummy parameter

[out] *Response* :

iReturnValue :

- 0: means the remote function performed OK
- -1: means an system error occurred
- -100: GetAutoRefreshAllValues kernel function error

ulTimeStampLow : number of microseconds since the begin of the second

ulTimeStampHigh : number of seconds since the Epoch

ulCounterValue : Array that contain the counter values

ulValue : Array that contain the channels values

- *ulValues* [0] : Channel 0 value

- ...

- *ulValues* [15] : Channel 15 value

Remark: When using the unipolar mode, the raw value for 0 volt (or 0 ampere) will be 32767.

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

2.18.2.3 int MSXE302x__AnalogInputStopAndReleaseAutoRefresh (void * __, struct MSXE302x__Response * *Response*)

Parameters

[in] _ Dummy parameter

[out] *Response* :

iReturnValue :

- 0: means the remote function performed OK
- -1: means an system error occurred
- -100: StopAutoRefresh kernel function error

syserrno : system-error code (the value of the libc "errno" code)

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

Must be called before any another call to MSXE302x__AnalogInputInitAndStartAutoRefresh.

2.19 MSX-E302x Sequence functions

A sequence is a list of channels (max 16) that are acquired.

Functions

- int **MSXE302x_AnalogInputInitAndStartSequence** (xsd__unsignedLong ulNbrOfChannel, struct MSXE302x__unsignedLong16FixedArrayParam *pulChannelList, struct MSXE302x__unsignedLong16FixedArrayParam *pulGainArray, struct MSXE302x__unsignedLong16FixedArrayParam *pulPolarityArray, xsd__unsignedLong ulConversionTime, xsd__unsignedLong ulConversionTimeUnit, xsd__unsignedLong ulNbrOfSequence, xsd__unsignedLong ulNbrMaxSequenceToTransfer, xsd__unsignedLong ulDelayMode, xsd__unsignedLong ulDelayTimeUnit, xsd__unsignedLong ulDelayValue, xsd__unsignedLong ulTriggerMask, xsd__unsignedLong ulTriggerMode, xsd__unsignedLong ulHardwareTriggerEdge, xsd__unsignedLong ulHardwareTriggerCount, xsd__unsignedLong ulByTriggerNbrOfSeqToAcquire, xsd__unsignedLong ulDateFormat, xsd__unsignedLong ulOption1, xsd__unsignedLong ulOption2, xsd__unsignedLong ulOption3, struct MSXE302x__Response *Response)

Initialise and start the analog input sequence acquisition mode.

- int **MSXE302x_AnalogInputStopAndReleaseSequence** (void *_, struct MSXE302x__Response *Response)

Stop and release the analog input sequence acquisition mode.

2.19.1 Detailed Description

It can be any order of the channels in this list.

There are different sequence modes:

- Certain number of sequences / continuous
- With/Without delay

a) Certain number of sequences:

After the acquisition of the defined number of sequences, the acquisition is stopped automatically.

b) Continuous:

The sequences are acquired continuously until a software-stop-command occurs.

c) Without delay:

There is no waiting time between the acquisitions of 2 sequences.

d) With delay:

A delay between 2 sequences can be configured:

For this there are 2 delay types:

> Mode 1: The delay time defines the time between 2 sequence beginnings.

> Mode 2: The delay time defines the time between the end of a sequence until the beginning of the next sequence.

You can start the acquisition by a hardware or synchro trigger.

The hardware trigger can react to a rising, falling or both edges.

You have the following possibility:

- Defining a number of edges before a trigger action is generated

There are two trigger modes (for the hardware or synchro trigger):

a) One shot

b) Sequence

a) One shot:

After the software start, the module is waiting for a trigger signal to start the acquisition. After this the trigger signal is ignored.

b) Sequence:

After the software start the module is waiting for the trigger signal and acquires x sequences (also adjustable) and then wait again.

2.19.2 Function Documentation

```
2.19.2.1 int MSXE302x_AnalogInputInitAndStartSequence ( xsd__unsignedLong ulNbrOfChannel, struct MSXE302x__unsignedLong16FixedArrayParam * pulChannelList, struct MSXE302x__unsignedLong16FixedArrayParam * pulGainArray, struct MSXE302x__unsignedLong16FixedArrayParam * pulPolarityArray, xsd__unsignedLong ulConversionTime, xsd__unsignedLong ulConversionTimeUnit, xsd__unsignedLong ulNbrOfSequence, xsd__unsignedLong ulNbrMaxSequenceToTransfer, xsd__unsignedLong ulDelayMode, xsd__unsignedLong ulDelayTimeUnit, xsd__unsignedLong ulDelayValue, xsd__unsignedLong ulTriggerMask, xsd__unsignedLong ulTriggerMode, xsd__unsignedLong ulHardwareTriggerEdge, xsd__unsignedLong ulHardwareTriggerCount, xsd__unsignedLong ulByTriggerNbrOfSeqToAcquire, xsd__unsignedLong ulDataFormat, xsd__unsignedLong ulOption1, xsd__unsignedLong ulOption2, xsd__unsignedLong ulOption3, struct MSXE302x__Response * Response )
```

Parameters

[in] **ulNbrOfChannel** : nbr of channel in the sequence

[in] **pulChannelList** : list of the channel who compose the sequence

[in] **pulGainArray** Define the gain (1 or 2) to use for each channel.

Information : by the channel type "current", the gain 2 is recommended.

- 1 : +10 V or max 20mA when Unipolar, +/-10V or max +/-20mA when Bipolar
- 2 : +5 V or 20 mA when Unipolar, +/-5V or +/- 20mA when Bipolar Each index of the array correspond to the channel :

sample :

- [0] : Define the gain for the channel 0
- [1] : Define the gain for the channel 1
- ...

Remark: When using a current version of the MSX-E302x, gain 2 has to be used.

[in] **pulPolarityArray** Define the polarity (0:Unipolar or 1:Bipolar) to use for each channel

Each index of the array correspond to the channel :

sample :

- [0] : Define the polarity for the channel 0
- [1] : Define the polarity for the channel 1
- ...

Remark: When using the unipolar mode, the raw value for 0 volt (or 0 ampere) will be 32767.

[in] ***ulConversionTime*** Conversion Time (min 10 us or 40 us)

[in] ***ulConversionTimeUnit*** Conversion Time Unit

- 0 : us
- 1 : ms

[in] ***ulNbrOfSequence*** : Number of sequence to acquire :

- 0 : continuous mode
- <> 0 : number of sequence

[in] ***ulNbrMaxSequenceToTransfer*** : Max nbr of sequence to acquire before a data transfer : (1,65535)

[in] ***ulDelayMode*** : Delay Mode :

- 0 : delay not used
- 1 : mode 1
- 2 : mode 2

[in] ***ulDelayTimeUnit*** : Selection of the time unit

0: us
1: ms
2: s

[in] ***ulDelayValue*** : Delay Value : (1..0xFFFF)

[in] ***ulTriggerMask*** Define the source of the trigger

- 0 : trigger disabled
- 1 : Enable Hardware Digital Input Trigger
- 2 : Enable Synchro Trigger
- 3 : Enable both Hardware and Synchro Trigger

[in] ***ulTriggerMode*** Define the trigger mode

- 1 : One shot trigger
- 2 : Sequence trigger

[in] ***ulHardwareTriggerEdge*** Define the edge of the hardware trigger who generate a trigger action

- 1 : rising front (Only if hardware trigger selected)
- 2 : falling front (Only if hardware trigger selected)
- 3 : Both front (Only if hardware trigger selected)

[in] ***ulHardwareTriggerCount*** Define the number of trigger events before the action occur

- 0 or 1 : all trigger event start the action
- max value : 65535

[in] ***ulByTriggerNbrOfSeqToAcquire*** : define the number of sequence to acquire by each trigger event

- 0 : continuous mode
- <> 0 : number of sequence : (1..0xFFFFFFFF)

[in] ***ulDataFormat*** : Data format option

D0 : Time stamp information

- 0 : no time stamp information
- 1 : time stamp information

D1 : Sequence counter information

- 0 : No sequence counter information
- 1 : Sequence counter information

D2 : Data format

- 0 : 32/16 bit digital value
- 1 : 32-bit analog value (in V)

D3 : 16-Bit digital value

- 0 : 32-bit digital/analog value
- 1 : 16-bit digital value.

Only a pair number of acquisition channels (ulNbrOfChannel) can be selected.

[in] ***ulOption1*** : Reserved

[in] ***ulOption2*** : Reserved

[in] ***ulOption3*** : Reserved

[out] ***Response*** :

iReturnValue :

- 0: means the remote function performed OK
- -1: means an system error occurred
- -2: The nbr of channel in the sequence cannot be null
- -3: Channel index selection error
- -4: Gain selection error
- -5: Polarity selection error
- -6: The minimal converting time is 10 us !
- -7: Not available conversion time unit
- -8: Delay mode selection not available
- -9: Delay time unit selection not available
- -10: Delay value not available
- -11: Trigger mode : 2 different mode cannot be simultaneously be activated
- -12: Hardware trigger : edge definition error
- -13: Hardware trigger count value not available
- -14: Nbr of sequence to acquire by trigger mode not available
- -15: Data format not available
- -100: Channel initialisation kernel function error
- -101: Conversion time initialisation kernel function error
- -102: Delay initialisation kernel function error
- -103: hardware trigger initialisation/enable kernel function error
- -104: hardware trigger disable kernel function error
- -105: synchro trigger initialisation/enable kernel function error
- -106: synchro trigger disable kernel function error
- -107 Sequence trigger count initialisation error
- -108: Sequence initialisation kernel function error
- -109: Start sequence kernel function error

syserrno : system-error code (the value of the libc "errno" code)

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

2.19.2.2 int MSXE302x__AnalogInputStopAndReleaseSequence (void * ___, struct MSXE302x__Response * Response)

Parameters

[in] ___ : no input parameter

[out] **Response** :

iReturnValue :

- 0: means the remote function performed OK
- -1: means an system error occurred
- -100: Stop sequence kernel function error
- -101: Release sequence kernel function error

syserrno : system-error code (the value of the libc "errno" code)

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

2.20 MSX-E302x calibration functions

The calibration functions permit to calibrate the analog input of the module.

Data Structures

- struct [MSXE302x__CalibrationGetCurrentStatusResponse](#)

Functions

- int [MSXE302x__CalibrationStart](#) (xsd__unsignedLong ulCalibrationMode, xsd__unsignedLong ulGain, xsd__double dCalibrationValue, struct [MSXE302x__Response](#) *Response)

This function start the calibration thread.

- int [MSXE302x__CalibrationGetCurrentStatus](#) (void *___, struct [MSXE302x__CalibrationGetCurrentStatusResponse](#) *Response)

This function return the current calibration status.

- int [MSXE302x__CalibrationNextStep](#) (void *___, struct [MSXE302x__Response](#) *Response)

This function start the next calibration step.

- int [MSXE302x__CalibrationBreak](#) (void *___, struct [MSXE302x__Response](#) *Response)

This function break the current calibration.

2.20.1 Detailed Description

Please use the following algorithm :

```

MSXE302x__CalibrationStart(...)

do
    MSXE302x__CalibrationGetCurrentStatus
    while (Status == 0)

    MSXE302x__CalibrationNextStep(...)

    do
        MSXE302x__CalibrationGetCurrentStatus
        while (Status == 1)

    MSXE302x__CalibrationNextStep(...)

Use MSXE302x__CalibrationBreak(...) to break the calibration sequence

```

2.20.2 Function Documentation

2.20.2.1 int MSXE302x__CalibrationStart (xsd__unsignedLong *ulCalibrationMode*, xsd__unsignedLong *ulGain*, xsd__double *dCalibrationValue*, struct MSXE302x__Response * *Response*)

Parameters

[in] *ulCalibrationMode* : Calibration mode selection:

- 0 Hex : All channels calibration via a external calibration source (voltage/current). Not available for mixing input types.
- 1 Hex : All channels calibration via the internal voltage calibration source. Not available for current or mixing input types.
- 2 Hex : Channel group 0 (Channel 0 to 3) calibration via a external calibration source (voltage/current).
- 102 Hex : Channel group 1 (Channel 4 to 7) calibration via a external calibration source (voltage/current).
- 202 Hex : Channel group 2 (Channel 8 to 11) calibration via a external calibration source (voltage/current).
- 302 Hex : Channel group 3 (Channel 12 to 15) calibration via a external calibration source (voltage/current).
- 3 Hex : Channel group 0 (Channel 0 to 3) calibration via the internal voltage calibration source. Not available for current inputs.
- 103 Hex : Channel group 1 (Channel 4 to 7) calibration via the internal voltage calibration source. Not available for current inputs.
- 203 Hex : Channel group 2 (Channel 8 to 11) calibration via the internal voltage calibration source. Not available for current inputs.
- 303 Hex : Channel group 3 (Channel 12 to 15) calibration via the internal voltage calibration source. Not available for current inputs.

[in] *ulGain* : Gain selection 1 or 2

[in] *dCalibrationValue* : Calibration value

[out] *Response* :

iReturnValue : Error value :

- 0: means the remote function performed OK
- -1: means an system error occurred
- -2: Calibration mode selection error
- -3: Calibration gain selection error

- -4: Calibration value selection error
- -100: Start calibration kernel function error

syserrno : system-error code (the value of the libc "errno" code)

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

2.20.2.2 int MSXE302x_CalibrationGetCurrentStatus (void * ___, struct MSXE302x_CalibrationGetCurrentStatusResponse * Response)

Parameters

[in] ___ : no input parameter

[out] **Response** :

iReturnValue : Error value :

- 0: means the remote function performed OK
- -1: means an system error occurred
- -100: Get status calibration kernel function error
- -101: Save calibration read source error
- -102: Save calibration write destination error

ulStatus : TODO

ulDigitalValue : Last measured digital value

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

2.20.2.3 int MSXE302x_CalibrationNextStep (void * ___, struct MSXE302x_Response * Response)

Parameters

[in] ___ : no input parameter

[out] **Response** :

iReturnValue : Error value :

- 0: means the remote function performed OK
- -1: means an system error occurred
- -100: Calibration next step kernel function error

syserrno : system-error code (the value of the libc "errno" code)

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

2.20.2.4 int MSXE302x__CalibrationBreak (void * ___, struct MSXE302x__Response * *Response*)

Parameters

[in] ___ : no input parameter

[out] ***Response*** :

iReturnValue : Error value :

- 0: means the remote function performed OK
- -1: means an system error occured
- -100: Calibration break kernel function error

syserrno : system-error code (the value of the libc "errno" code)

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

Chapter 3

Data Structure Documentation

3.1 ByteArray Struct Reference

Dynamic Array of byte - encapsulates C-type strings.

Data Fields

- `xsd__unsignedByte * __ptr`
pointer of byte
- `int __size`
size of the byte array in bytes
- `int __offset`
not used

3.1.1 Field Documentation

3.1.1.1 `xsd__unsignedByte* ByteArray::__ptr`

3.1.1.2 `int ByteArray::__size`

3.1.1.3 `int ByteArray::__offset`

3.2 DefaultResponse Struct Reference

Data Fields

- `xsd__int iReturnValue`
return value of the call :
- `xsd__int syserrno`
system-error code (the value of the libc "errno" code)

3.2.1 Field Documentation

3.2.1.1 xsd_int DefaultResponse::iReturnValue

- 0 means the remote function performed OK
- -1 means a system error occurred, the meaning of other values is function dependant and should be defined in the related header

3.2.1.2 xsd_int DefaultResponse::syserrno

3.3 MSXE302x_AnalogInputGetAutoRefreshValuesResponse Struct Reference

Data Fields

- struct [DefaultResponse](#) sResponse

Default return values.

- [xsd_unsignedLong ulTimeStampLow](#)

The meaning of this field is defined in the related header of the function who use this type.

- [xsd_unsignedLong ulTimeStampHigh](#)

The meaning of this field is defined in the related header of the function who use this type.

- [xsd_unsignedLong ulCounterValue](#)

The meaning of this field is defined in the related header of the function who use this type.

- [xsd_unsignedLong ulValue \[16\]](#)

The meaning of this field is defined in the related header of the function who use this type.

3.3.1 Field Documentation

- 3.3.1.1 struct DefaultResponse MSXE302x__-
AnalogInputGetAutoRefreshValuesResponse::sResponse
- 3.3.1.2 xsd__unsignedLong MSXE302x__-
AnalogInputGetAutoRefreshValuesResponse::ulTimeStampLow
- 3.3.1.3 xsd__unsignedLong MSXE302x__-
AnalogInputGetAutoRefreshValuesResponse::ulTimeStampHigh
- 3.3.1.4 xsd__unsignedLong MSXE302x__-
AnalogInputGetAutoRefreshValuesResponse::ulCounterValue
- 3.3.1.5 xsd__unsignedLong MSXE302x__-
AnalogInputGetAutoRefreshValuesResponse::ulValue[16]

3.4 MSXE302x__AnalogInputGetChannelTypeResponse Struct Reference

Data Fields

- struct DefaultResponse sResponse
Default return values.
- xsd__unsignedLong ulType [16]
The meaning of this field is defined in the related header of the function who use this type.

3.4.1 Field Documentation

- 3.4.1.1 struct DefaultResponse MSXE302x__AnalogInputGetChannelTypeResponse::sResponse
- 3.4.1.2 xsd__unsignedLong MSXE302x__AnalogInputGetChannelTypeResponse::ulType[16]

3.5 MSXE302x__AnalogMeasureGetConfigurationResponse Struct Reference

Data Fields

- xsd__int iReturnValue
- xsd__unsignedLong ulRunningMode
- struct {
 - xsd__unsignedLong ulConvertTimeUnit
0: micro second 1: milli second 2: second
 - xsd__unsignedLong ulConvertTime
The conversion time.
 - xsd__unsignedLong ulChannelInitialization
Channel initialization ?

} **sAcquisition**

0: Disabled 1: Auto refresh 2: Sequence 2: Calibtation

- struct {

 xsd__unsignedLong ulChannelMask
Mask of channels used for the auto refresh mode.
 xsd__unsignedLong ulAverageMode
Determine average mode 0: Sequence 1 : Channel.
 xsd__unsignedLong ulAverageValue
Determine the number of sequence for a average value calculation.
 xsd__unsignedLong ulDataFormat
D0: Time stamp information.
 } **sAutoRefresh**

- struct {

 xsd__unsignedLong ulSequenceSize
Sequence array size.
 xsd__unsignedLong ulSequence [64]
Sequence channel array.
 xsd__unsignedLong ulSequenceInterrupt
Determine the number of sequences for the interrupt.
 xsd__unsignedLong ulNbrOfSequence
Determine the number total of sequences.
 xsd__unsignedLong ulDelayFlag
0 : Disabled 1 : Enabled
 xsd__unsignedLong ulDelayMode
Delay mode.
 xsd__unsignedLong ulDelayTimeUnit
Delay time unit 1: micros 2 : ms 3 : s.
 xsd__unsignedLong ulDelayTime
Delay time.
 xsd__unsignedLong ulDataFormat
D0: Time stamp information.
 } **sSequence**

- struct {

 xsd__unsignedLong ulSequenceTriggerCount
Number of sequence to trigger.
 struct {
 xsd__unsignedLong ulFlag
0 : Disabled 1: Enabled
 xsd__unsignedLong ulLevel
0: Low level 1: High level 2 : Low/High level
 xsd__unsignedLong ulAction
0: One shot 1: Sequence trigger
 xsd__unsignedLong ulCount
Number of trigger vor the action.
 } **sHardware**
 struct {
 xsd__unsignedLong ulFlag
0 : Disabled 1: Enabled
 xsd__unsignedLong ulAction

```

    0: One shot 1: Sequence trigger
} sSoftware
struct {
    xsd__unsignedLong ulFlag
    0 : Disabled 1: Enabled
    xsd__unsignedLong ulAction
    0: One shot 1: Sequence trigger
} sSynchro
} sTrigger

```

3.5.1 Field Documentation

3.5.1.1 xsd__int MSXE302x__AnalogMeasureGetConfigurationResponse::iReturnValue

3.5.1.2 xsd__unsignedLong MSXE302x__-
AnalogMeasureGetConfigurationResponse::ulRunningMode

3.5.1.3 xsd__unsignedLong MSXE302x__-
AnalogMeasureGetConfigurationResponse::ulConvertTimeUnit

3.5.1.4 xsd__unsignedLong MSXE302x__-
AnalogMeasureGetConfigurationResponse::ulConvertTime

3.5.1.5 xsd__unsignedLong MSXE302x__-
AnalogMeasureGetConfigurationResponse::ulChannelInitialization

3.5.1.6 struct { ... } MSXE302x__AnalogMeasureGetConfigurationResponse::sAcquisition

3.5.1.7 xsd__unsignedLong MSXE302x__-
AnalogMeasureGetConfigurationResponse::ulChannelMask

3.5.1.8 xsd__unsignedLong MSXE302x__-
AnalogMeasureGetConfigurationResponse::ulAverageMode

3.5.1.9 xsd__unsignedLong MSXE302x__-
AnalogMeasureGetConfigurationResponse::ulAverageValue

3.5.1.10 xsd__unsignedLong MSXE302x__-
AnalogMeasureGetConfigurationResponse::ulDataFormat

0 without, 1 with. D1 : Data format 0: digital 1: analog (in V)

0 without, 1 with. D1 : Sequence counter information. 0 without, 1 with. D2 : Data format 0: digital 1: analog (in V)

3.5.1.11 **struct { ... } MSXE302x__AnalogMeasureGetConfigurationResponse::sAutoRefresh**

3.5.1.12 **xsd__unsignedLong MSXE302x__-**
AnalogMeasureGetConfigurationResponse::ulSequenceSize

3.5.1.13 **xsd__unsignedLong MSXE302x__-**
AnalogMeasureGetConfigurationResponse::ulSequence[64]

3.5.1.14 **xsd__unsignedLong MSXE302x__-**
AnalogMeasureGetConfigurationResponse::ulSequenceInterrupt

3.5.1.15 **xsd__unsignedLong MSXE302x__-**
AnalogMeasureGetConfigurationResponse::ulNbrOfSequence

0: Continuous

- 3.5.1.16 `xsd__unsignedLong MSXE302x__-`
`AnalogMeasureGetConfigurationResponse::ulDelayFlag`
- 3.5.1.17 `xsd__unsignedLong MSXE302x__-`
`AnalogMeasureGetConfigurationResponse::ulDelayMode`
- 3.5.1.18 `xsd__unsignedLong MSXE302x__-`
`AnalogMeasureGetConfigurationResponse::ulDelayTimeUnit`
- 3.5.1.19 `xsd__unsignedLong MSXE302x__-`
`AnalogMeasureGetConfigurationResponse::ulDelayTime`
- 3.5.1.20 `struct { ... } MSXE302x__AnalogMeasureGetConfigurationResponse::sSequence`
- 3.5.1.21 `xsd__unsignedLong MSXE302x__-`
`AnalogMeasureGetConfigurationResponse::ulSequenceTriggerCount`
- 3.5.1.22 `xsd__unsignedLong MSXE302x__AnalogMeasureGetConfigurationResponse::ulFlag`
- 3.5.1.23 `xsd__unsignedLong MSXE302x__AnalogMeasureGetConfigurationResponse::ulLevel`
- 3.5.1.24 `xsd__unsignedLong MSXE302x__AnalogMeasureGetConfigurationResponse::ulAction`
- 3.5.1.25 `xsd__unsignedLong MSXE302x__AnalogMeasureGetConfigurationResponse::ulCount`
- 3.5.1.26 `struct { ... } MSXE302x__AnalogMeasureGetConfigurationResponse::sHardware`
- 3.5.1.27 `struct { ... } MSXE302x__AnalogMeasureGetConfigurationResponse::sSoftware`
- 3.5.1.28 `struct { ... } MSXE302x__AnalogMeasureGetConfigurationResponse::sSynchro`
- 3.5.1.29 `struct { ... } MSXE302x__AnalogMeasureGetConfigurationResponse::sTrigger`

3.6 MSXE302x__CalibrationGetCurrentStatusResponse Struct Reference

Data Fields

- struct [DefaultResponse](#) sResponse
Default return values.
- `xsd__unsignedLong ulStatus`
Calibration status :
- `xsd__double dCurrentValue`
Last measured value.
- `xsd__unsignedLong ulError`
Calibration error :

3.6.1 Field Documentation

3.6.1.1 struct DefaultResponse MSXE302x_CalibrationGetCurrentStatusResponse::sResponse

3.6.1.2 xsd_unsignedLong MSXE302x_CalibrationGetCurrentStatusResponse::ulStatus

- 0 Hex: No calibration in progress
- 1 Hex: Wait that the user inject 0V to channel 0
- 101 Hex: Wait that the user inject 0V to channel 4
- 201 Hex: Wait that the user inject 0V to channel 8
- 301 Hex: Wait that the user inject 0V to channel 12
- 2 Hex: Offset group 0 (channel 0 to 3) calibration in progress
- 102 Hex: Offset group 1 (channel 4 to 7) calibration in progress
- 202 Hex: Offset group 2 (channel 8 to 11) calibration in progress
- 302 Hex: Offset group 3 (channel 12 to 15) calibration in progress
- 3 Hex: Wait that the user inject the selected calibration value to channel 0
- 103 Hex: Wait that the user inject the selected calibration value to channel 4
- 203 Hex: Wait that the user inject the selected calibration value to channel 8
- 303 Hex: Wait that the user inject the selected calibration value to channel 12
- 4 Hex: Selected group 0 (channel 0 to 3) calibration value in progress
- 104 Hex: Selected group 1 (channel 4 to 7) calibration value in progress
- 204 Hex: Selected group 2 (channel 7 to 11) calibration value in progress
- 304 Hex: Selected group 3 (channel 12 to 15) calibration value in progress
- 6 Hex: Wait that the user inject the selected inverted calibration value to channel 0
- 106 Hex: Wait that the user inject the selected inverted calibration value to channel 4
- 206 Hex: Wait that the user inject the selected inverted calibration value to channel 8
- 306 Hex: Wait that the user inject the selected inverted calibration value to channel 12
- 5 Hex: Calibration finished

3.6.1.3 xsd_double MSXE302x_CalibrationGetCurrentStatusResponse::dCurrentValue

3.6.1.4 xsd_unsignedLong MSXE302x_CalibrationGetCurrentStatusResponse::ulError

- 0 : No error
- 1 : User break occur
- 2 : Min set 0 offset potentiometer value reached
- 3 : Max set 0 offset potentiometer value reached

- 4 : Min set 1 offset potentiometer value reached
- 5 : Max set 1 offset potentiometer value reached
- 6 : Min set 2 offset potentiometer value reached
- 7 : Max set 2 offset potentiometer value reached
- 8 : Min set 3 offset potentiometer value reached
- 9 : Max set 3 offset potentiometer value reached
- 10 : Min set 0 gain potentiometer value reached
- 11 : Max set 0 gain potentiometer value reached
- 12 : Min set 1 gain potentiometer value reached
- 13 : Max set 1 gain potentiometer value reached
- 14 : Min set 2 gain potentiometer value reached
- 15 : Max set 2 gain potentiometer value reached
- 16 : Min set 3 gain potentiometer value reached
- 17 : Max set 3 gain potentiometer value reached

3.7 MSXE302x__Response Struct Reference

Data Fields

- [xsd_int iReturnValue](#)
return value of the call :
- [xsd_int syserrno](#)
System-error code (the value of the libc "errno" code).

3.7.1 Field Documentation

3.7.1.1 xsd_int MSXE302x__Response::iReturnValue

- 0 means the remote function performed OK
- -1 means a system error occurred, the meaning of other values is function dependant and should be defined in the related header

3.7.1.2 `xsd_int MSXE302x_Response::syserrno`

3.8 `MSXE302x_unsignedLong16FixedArrayParam` Struct Reference

Data Fields

- `xsd_unsignedLong ulValue [16]`

The meaning of this field is defined in the related header of the function who use this type.

3.8.1 Field Documentation

3.8.1.1 `xsd_unsignedLong MSXE302x_unsignedLong16FixedArrayParam::ulValue[16]`

3.9 `MSXE302x_unsignedLongResponse` Struct Reference

Data Fields

- struct `DefaultResponse sResponse`

Default return values.

- `xsd_unsignedLong ulValue`

The meaning of this value is defined in the related header of the function who use this type.

3.9.1 Field Documentation

3.9.1.1 struct `DefaultResponse MSXE302x_unsignedLongResponse::sResponse`

3.9.1.2 `xsd_unsignedLong MSXE302x_unsignedLongResponse::ulValue`

3.10 `MXCommon_ByteArrayResponse` Struct Reference

Response containing a C-type string.

Data Fields

- struct `DefaultResponse sResponse`

Default return values.

- struct `ByteArray sArray`

Dynamic Array of byte - encapsulates C-type strings.

3.10.1 Field Documentation

3.10.1.1 struct DefaultResponse MXCommon__ByteArrayResponse::sResponse

3.10.1.2 struct ByteArray MXCommon__ByteArrayResponse::sArray

3.11 MXCommon__FileResponse Struct Reference

Response containing a chunk of a file.

Data Fields

- struct [DefaultResponse](#) sResponse

return values.

- struct [ByteArray](#) sArray

Dynamic Array of byte.

- [xsd__unsignedLong](#) ulEOF

flag indicating end of file.

3.11.1 Field Documentation

3.11.1.1 struct DefaultResponse MXCommon__FileResponse::sResponse

3.11.1.2 struct ByteArray MXCommon__FileResponse::sArray

3.11.1.3 [xsd__unsignedLong](#) MXCommon__FileResponse::ulEOF

3.12 MXCommon__GetAutoConfigurationFileResponse Struct Reference

Data Fields

- struct [DefaultResponse](#) sResponse

Default return values.

- struct [ByteArray](#) bArray

Array of byte of the file.

- [xsd__unsignedLong](#) ulEOF

End of file flag.

3.12.1 Field Documentation

3.12.1.1 struct DefaultResponse MXCommon__GetAutoConfigurationFileResponse::sResponse

3.12.1.2 struct ByteArray MXCommon__GetAutoConfigurationFileResponse::bArray

3.12.1.3 xsd__unsignedLong MXCommon__GetAutoConfigurationFileResponse::ulEOF

3.13 MXCommon__GetEthernetLinksStatesResponse Struct Reference

Data Fields

- struct [DefaultResponse](#) sResponse
Default return values.
- struct [sGetEthernetLinksStatesPort](#) sPort0
- struct [sGetEthernetLinksStatesPort](#) sPort1

3.13.1 Field Documentation

3.13.1.1 struct DefaultResponse MXCommon__GetEthernetLinksStatesResponse::sResponse

3.13.1.2 struct [sGetEthernetLinksStatesPort](#) MXCommon__-
 GetEthernetLinksStatesResponse::sPort0

3.13.1.3 struct [sGetEthernetLinksStatesPort](#) MXCommon__-
 GetEthernetLinksStatesResponse::sPort1

3.14 MXCommon__GetHardwareTriggerFilterTimeResponse Struct Reference

Data Fields

- struct [DefaultResponse](#) sResponse
Default return values.
- xsd__unsignedLong ulFilterTime
0 : Filter disabled >1 : Filter enabled (Filter time)
- xsd__unsignedLong ullInfo01
Reserved.
- xsd__unsignedLong ullInfo02
Reserved.

3.14.1 Field Documentation

- 3.14.1.1 struct DefaultResponse MXCommon__-
GetHardwareTriggerFilterTimeResponse::sResponse
- 3.14.1.2 xsd__unsignedLong MXCommon__-
GetHardwareTriggerFilterTimeResponse::ulFilterTime
- 3.14.1.3 xsd__unsignedLong MXCommon__GetHardwareTriggerFilterTimeResponse::ulInfo01
- 3.14.1.4 xsd__unsignedLong MXCommon__GetHardwareTriggerFilterTimeResponse::ulInfo02

3.15 MXCommon__GetHardwareTriggerStateResponse Struct Reference

Data Fields

- struct DefaultResponse sResponse
Default return values.
- xsd__unsignedLong ulState
0 : Trigger input is low / 1 : Trihgger input is high
- xsd__unsignedLong ulInfo01
Reserved.
- xsd__unsignedLong ulInfo02
Reserved.

3.15.1 Field Documentation

- 3.15.1.1 struct DefaultResponse MXCommon__GetHardwareTriggerStateResponse::sResponse
- 3.15.1.2 xsd__unsignedLong MXCommon__GetHardwareTriggerStateResponse::ulState
- 3.15.1.3 xsd__unsignedLong MXCommon__GetHardwareTriggerStateResponse::ulInfo01
- 3.15.1.4 xsd__unsignedLong MXCommon__GetHardwareTriggerStateResponse::ulInfo02

3.16 MXCommon__GetModuleTemperatureValueAndStatusResponse Struct Reference

Data Fields

- struct DefaultResponse sResponse
Default return value.
- xsd__double dTemperatureValue

Temperature value.

- `xsd__unsignedLong ulTemperatureStatus`

Temperature status.

- `xsd__unsignedLong ullInfo`

Reserved.

3.16.1 Field Documentation

**3.16.1.1 struct DefaultResponse MXCommon__-
GetModuleTemperatureValueAndStatusResponse::sResponse**

**3.16.1.2 xsd__double MXCommon__-
GetModuleTemperatureValueAndStatusResponse::dTemperatureValue**

**3.16.1.3 xsd__unsignedLong MXCommon__-
GetModuleTemperatureValueAndStatusResponse::ulTemperatureStatus**

**3.16.1.4 xsd__unsignedLong MXCommon__-
GetModuleTemperatureValueAndStatusResponse::ullInfo**

3.17 MXCommon__GetTimeResponse Struct Reference

Data Fields

- `struct DefaultResponse sResponse`

Default return values.

- `xsd__unsignedLong ulLowTime`

Number of microseconds since the begin of the second.

- `xsd__unsignedLong ulHighTime`

Number of seconds since the Epoch (1st January, 1970).

3.17.1 Field Documentation

3.17.1.1 struct DefaultResponse MXCommon__GetTimeResponse::sResponse

3.17.1.2 xsd__unsignedLong MXCommon__GetTimeResponse::ulLowTime

3.17.1.3 xsd__unsignedLong MXCommon__GetTimeResponse::ulHighTime

3.18 MXCommon__GetUpTimeResponse Struct Reference

Data Fields

- `struct DefaultResponse sResponse`

Default return value.

- [xsd__unsignedLong ulUpTime](#)

Reserved.

3.18.1 Field Documentation

3.18.1.1 struct DefaultResponse MXCommon__GetUpTimeResponse::sResponse

3.18.1.2 xsd__unsignedLong MXCommon__GetUpTimeResponse::ulUpTime

3.19 MXCommon__Response Struct Reference

contains return values

Data Fields

- [xsd__int iReturnValue](#)

return value of the call :

- 0 *success*
- -1 *a system error occurred, the meaning of other values is function dependent and should be defined in the related header.*

- [xsd__int syserrno](#)

system-error code (the value of the libc "errno" code, see [MXCommon__Strerror\(\)](#)).

3.19.1 Field Documentation

3.19.1.1 xsd__int MXCommon__Response::iReturnValue

3.19.1.2 xsd__int MXCommon__Response::syserrno

3.20 MXCommon__TestCustomerIDResponse Struct Reference

Data Fields

- struct [DefaultResponse sResponse](#)

Default return values.

- struct [ByteArray bValueArray](#)

non encrypted value

- struct [ByteArray bCryptedListValue](#)

encrypted value

3.20.1 Field Documentation

3.20.1.1 struct DefaultResponse MXCommon__TestCustomerIDResponse::sResponse

3.20.1.2 struct ByteArray MXCommon__TestCustomerIDResponse::bValueArray

3.20.1.3 struct ByteArray MXCommon__TestCustomerIDResponse::bCryptedListValueArray

3.21 MXCommon__unsignedLongResponse Struct Reference

Response containing a numerical value (ex: return code).

Data Fields

- struct DefaultResponse sResponse

Default return values.

- xsd__unsignedLong ulValue

The meaning of this value is defined in the related header of the function who use this type.

3.21.1 Field Documentation

3.21.1.1 struct DefaultResponse MXCommon__unsignedLongResponse::sResponse

3.21.1.2 xsd__unsignedLong MXCommon__unsignedLongResponse::ulValue

3.22 sGetEthernetLinksStatesPort Struct Reference

Data Fields

- xsd__unsignedLong ulState
- xsd__unsignedLong ulSpeed
- xsd__unsignedLong ulDuplex
- xsd__unsignedLong ullInfo1
- xsd__unsignedLong ullInfo2

3.22.1 Field Documentation

- 3.22.1.1 `xsd__unsignedLong sGetEthernetLinksStatesPort::ulState`
- 3.22.1.2 `xsd__unsignedLong sGetEthernetLinksStatesPort::ulSpeed`
- 3.22.1.3 `xsd__unsignedLong sGetEthernetLinksStatesPort::ulDuplex`
- 3.22.1.4 `xsd__unsignedLong sGetEthernetLinksStatesPort::ulInfo1`
- 3.22.1.5 `xsd__unsignedLong sGetEthernetLinksStatesPort::ulInfo2`

3.23 UnsignedLongArray Struct Reference

Dynamic Array of unsigned long.

Data Fields

- `xsd__unsignedLong * __ptr`
pointer of unsigned Long
- `int __size`
size of the unsigned Long array in Bytes
- `int __offset`
not used

3.23.1 Field Documentation

- 3.23.1.1 `xsd__unsignedLong* UnsignedLongArray::__ptr`
- 3.23.1.2 `int UnsignedLongArray::__size`
- 3.23.1.3 `int UnsignedLongArray::__offset`

3.24 UnsignedShortArray Struct Reference

Dynamic Array of unsigned short.

Data Fields

- `xsd__unsignedShort * __ptr`
pointer of unsigned short
- `int __size`
size of the unsigned short array in Bytes

- int __offset
not used

3.24.1 Field Documentation

3.24.1.1 xsd__unsignedShort* UnsignedShortArray::__ptr

3.24.1.2 int UnsignedShortArray::__size

3.24.1.3 int UnsignedShortArray::__offset

3.25 xsd__base64Binary Struct Reference

Dynamic Array of byte for input use.

Data Fields

- unsigned char * __ptr
pointer of byte
- int __size
size of the byte array

3.25.1 Field Documentation

3.25.1.1 unsigned char* xsd__base64Binary::__ptr

3.25.1.2 int xsd__base64Binary::__size

Chapter 4

File Documentation

4.1 MSXE302x_public_doc.h File Reference

Data Structures

- struct [xsd__base64Binary](#)
Dynamic Array of byte for input use.
- struct [UnsignedShortArray](#)
Dynamic Array of unsigned short.
- struct [UnsignedLongArray](#)
Dynamic Array of unsigned long.
- struct [ByteArray](#)
Dynamic Array of byte - encapsulates C-type strings.
- struct [DefaultResponse](#)
- struct [MXCommon__Response](#)
contains return values
- struct [MXCommon__ByteArrayResponse](#)
Response containing a C-type string.
- struct [MXCommon__FileResponse](#)
Response containing a chunk of a file.
- struct [MXCommon__unsignedLongResponse](#)
Response containing a numerical value (ex: return code).
- struct [sGetEthernetLinksStatesPort](#)
- struct [MXCommon__GetEthernetLinksStatesResponse](#)
- struct [MXCommon__GetModuleTemperatureValueAndStatusResponse](#)
- struct [MXCommon__GetHardwareTriggerFilterTimeResponse](#)
- struct [MXCommon__GetHardwareTriggerStateResponse](#)

- struct [MXCommon__TestCustomerIDResponse](#)
- struct [MXCommon__GetTimeResponse](#)
- struct [MXCommon__GetUpTimeResponse](#)
- struct [MXCommon__GetAutoConfigurationFileResponse](#)
- struct [MSXE302x__Response](#)
- struct [MSXE302x__unsignedLongResponse](#)
- struct [MSXE302x__unsignedLong16FixedArrayParam](#)
- struct [MSXE302x__AnalogMeasureGetConfigurationResponse](#)
- struct [MSXE302x__AnalogInputGetChannelTypeResponse](#)
- struct [MSXE302x__AnalogInputGetAutoRefreshValuesResponse](#)
- struct [MSXE302x__CalibrationGetCurrentStatusResponse](#)

Typedefs

- **typedef char * xsd__string**
encode xsd__string value as the xsd:string schema type
- **typedef char xsd__char**
encode xsd__string value as the xsd:char schema type
- **typedef float xsd__float**
encode xsd__float value as the xsd:float schema type
- **typedef double xsd__double**
encode xsd__double value as the xsd:double schema type
- **typedef int xsd__int**
encode xsd__int value as the xsd:int schema type
- **typedef long xsd__long**
encode xsd__long value as the xsd:long schema type
- **typedef unsigned char xsd__unsignedByte**
encode xsd__unsignedByte value as the xsd:unsignedByte schema type
- **typedef unsigned int xsd__unsignedInt**
encode xsd__unsignedInt value as the xsd:unsignedInt schema type
- **typedef unsigned short int xsd__unsignedShort**
encode xsd__unsignedShort value as the xsd:unsignedShort schema type
- **typedef unsigned long xsd__unsignedLong**
encode xsd__unsignedLong value as the xsd:unsignedLong schema type

Functions

- int `MXCommon__GetModuleType` (void *, struct `MXCommon__ByteArrayResponse` *Response)

This function return the type of the MSX-E Module.
- int `MXCommon__GetHostname` (void *, struct `MXCommon__ByteArrayResponse` *Response)

This function return the hostname of the MSX-E Module.
- int `MXCommon__SetHostname` (struct `xsd__base64Binary` *bHostname, struct `MXCommon__Response` *Response)

This function allows to set the hostname of the MSX-E Module.
- int `MXCommon__GetClientConnections` (void *, struct `MXCommon__ByteArrayResponse` *Response)

This function return the client connection list.
- int `MXCommon__Strerror` (xsd_int errnum, struct `MXCommon__ByteArrayResponse` *Response)

Call the libc strerror() on the remote device (actually this is a call to strerror_r()).
- int `MXCommon__Reboot` (void *, struct `MXCommon__Response` *Response)

Ask the MSX-E module to reboot.
- int `MXCommon__ResetAllIOPFunctionalities` (xsd_unsignedLong ulOption, struct `MXCommon__Response` *Response)

Reset the I/O functionalities of the MSX-E system.
- int `MXCommon__DataserverRestart` (xsd_unsignedLong ulAction, xsd_unsignedLong ulOption, struct `MXCommon__Response` *Response)

Restart the data-server service.
- int `MXCommon__GetEthernetLinksStates` (void *, struct `MXCommon__GetEthernetLinksStatesResponse` *Response)

Get MSX-E Ethernet links states.
- int `MXCommon__GetModuleTemperatureValueAndStatus` (xsd_unsignedLong ulOption, struct `MXCommon__GetModuleTemperatureValueAndStatusResponse` *Response)

Read the temperature on the module.
- int `MXCommon__SetModuleTemperatureWarningLevels` (xsd_double dMinimalWarningLevel, xsd_double dMaximalWarningLevel, xsd_unsignedLong ulOption, struct `MXCommon__Response` *Response)

Set the temperature warning level on the module.
- int `MXCommon__SetHardwareTriggerFilterTime` (xsd_unsignedLong ulFilterTime, xsd_unsignedLong ulOption, struct `MXCommon__Response` *Response)

Set the filter time for the hardware trigger input in 250 ns step (max value : 65535).
- int `MXCommon__GetHardwareTriggerFilterTime` (xsd_unsignedLong ulOption, struct `MXCommon__GetHardwareTriggerFilterTimeResponse` *Response)

Get the filter time for the hardware trigger input in 250 ns step (max value : 65535).

- int **MXCommon__GetHardwareTriggerState** (xsd__unsignedLong ulOption, struct **MXCommon__GetHardwareTriggerStateResponse** *Response)

Get the hardware trigger state after the filter.
- int **MXCommon__SetCustomerKey** (struct xsd__base64Binary *bKey, struct xsd__base64Binary *bPublicKey, struct **MXCommon__Response** *Response)

Set the Customer key.
- int **MXCommon__TestCustomerID** (void *_, struct **MXCommon__TestCustomerIDResponse** *Response)

Test the Customer ID (if the module has the right customer Key).
- int **MXCommon__SetTime** (xsd__unsignedLong ulLowTime, xsd__unsignedLong ulHighTime, struct **MXCommon__Response** *Response)

Set the time on the module.
- int **MXCommon__SysToHardwareClock** (void *_, struct **MXCommon__Response** *Response)

Set the hardware clock (if present) to the current system time.
- int **MXCommon__HardwareClockToSys** (void *_, struct **MXCommon__Response** *Response)

Set the system time from the hardware clock (if present).
- int **MXCommon__GetTime** (void *_, struct **MXCommon__GetTimeResponse** *Response)

Get the time on the module.
- int **MXCommon__GetUpTime** (void *_, struct **MXCommon__GetUpTimeResponse** *Response)

Ask the MSX-E module uptime (number of seconds since the last boot).
- int **MXCommon__GetAutoConfigurationFile** (void *_, struct **MXCommon__GetAutoConfigurationFileResponse** *Response)

Get the auto configuration file of the module.
- int **MXCommon__SetAutoConfigurationFile** (struct xsd__base64Binary *ByteArrayInput, xsd__unsignedLong ulEOF, struct **MXCommon__Response** *Response)

Set the auto configuration file of the module.
- int **MXCommon__StartAutoConfiguration** (void *_, struct **MXCommon__ByteArrayResponse** *Response)

start/Restart the auto configuration
- int **MXCommon__InitAndStartSynchroTimer** (xsd__unsignedLong ulTimeBase, xsd__unsignedLong ulReloadValue, xsd__unsignedLong ulNbrOfCycle, xsd__unsignedLong ulGenerateTriggerMode, xsd__unsignedLong ulOption01, xsd__unsignedLong ulOption02, xsd__unsignedLong ulOption03, xsd__unsignedLong ulOption04, struct **MXCommon__Response** *Response)

Initialises and starts the synchronisation timer of the module (not already available on all module).
- int **MXCommon__StopAndReleaseSynchroTimer** (xsd__unsignedLong ulOption01, struct **MXCommon__Response** *Response)

start/Restart the synchronisation timer (not already available on all module)

- int `MXCommon__GetConfigurationBackupFile` (void *_, struct `MXCommon__FileResponse` *Response)

Download a configuration backup file from the module.
- int `MXCommon__ApplyConfigurationBackupFile` (struct `xsd__base64Binary` *ByteArrayInput, `xsd__unsignedLong` ulEOF, struct `MXCommon__Response` *Response)

Upload a new configuration on the module.
- int `MXCommon__ChangePassword` (struct `xsd__base64Binary` *PreviousUser, struct `xsd__base64Binary` *PreviousPassword, struct `xsd__base64Binary` *NewUser, struct `xsd__base64Binary` *NewPassword, struct `MXCommon__Response` *Response)

Set a new id/password.
- int `MXCommon__GetSubSystemState` (`xsd__unsignedLong` SubsystemID, struct `MXCommon__unsignedLongResponse` *Response)

Returns the current state of the specified sub-system.
- int `MXCommon__GetSubsystemIDFromName` (struct `xsd__base64Binary` *SubsystemName, struct `MXCommon__unsignedLongResponse` *Response)

Returns the ID of the sub-system of symbolic name "SubsystemName".
- int `MXCommon__GetStateIDFromName` (`xsd__unsignedLong` SubsystemID, struct `xsd__base64Binary` *StateName, struct `MXCommon__unsignedLongResponse` *Response)

Returns the ID of the state of symbolic name "StateName" of the sub-system of ID "SubsystemID".
- int `MXCommon__GetSubsystemNameFromID` (`xsd__unsignedLong` SubsystemID, struct `MXCommon__ByteArrayResponse` *Response)

Returns the symbolic name of the sub-system of numerical ID "SubsystemName".
- int `MXCommon__GetStateNameFromID` (`xsd__unsignedLong` SubsystemID, `xsd__unsignedLong` StateID, struct `MXCommon__ByteArrayResponse` *Response)

Returns the symbolic name of the state of numerical ID "StateID" of the sub-system of ID "SubsystemID".
- int `MXCommon__GetOptionInformation` (void *_, `xsd__unsignedLong` ulOption01, `xsd__unsignedLong` ulOption02, struct `MXCommon__ByteArrayResponse` *Response)

Enables to get information about the options available on the system.
- int `MXCommon__SetToMaster` (void *_, `xsd__unsignedLong` ulState, `xsd__unsignedLong` ulOption01, `xsd__unsignedLong` ulOption02, struct `MXCommon__Response` *Response)

Writes if the MSXE has to be always set to master The master mode (when enabled) make the system always detected as master.
- int `MXCommon__GetSynchronizationStatus` (void *_, `xsd__unsignedLong` ulOption01, `xsd__unsignedLong` ulOption02, struct `MXCommon__unsignedLongResponse` *Response)

Reads the status of the synchronization for the corresponding MSXE The master mode (when enabled) make the system always detected as master.
- int `MSXE302x__AnalogInputGetChannelType` (`xsd__unsignedLong` ulOption1, struct `MSXE302x__AnalogInputGetChannelTypeResponse` *Response)

Return the type of the analog input channels.

- int **MSXE302x__AnalogMeasureGetConfiguration** (xsd__unsignedLong ulModule, struct **MSXE302x__AnalogMeasureGetConfigurationResponse** *Response)

Return the running configuration.

- int **MSXE302x__AnalogInputInitAndStartAutoRefresh** (xsd__unsignedLong ulChannelMask, struct **MSXE302x__unsignedLong16FixedArrayParam** *pulGainArray, struct **MSXE302x__unsignedLong16FixedArrayParam** *pulPolarityArray, xsd__unsignedLong ulAverageMode, xsd__unsignedLong ulAverageValue, xsd__unsignedLong ulConversionTime, xsd__unsignedLong ulConversionTimeUnit, xsd__unsignedLong ulTriggerMask, xsd__unsignedLong ulTriggerMode, xsd__unsignedLong ulHardwareTriggerEdge, xsd__unsignedLong ulHardwareTriggerCount, xsd__unsignedLong ulByTriggerNbrOfSeqToAcquire, xsd__unsignedLong ulDataFormat, xsd__unsignedLong ulOption1, xsd__unsignedLong ulOption2, xsd__unsignedLong ulOption3, struct **MSXE302x__Response** *Response)

Starts an autorefresh acquisition using provided configuration.

- int **MSXE302x__AnalogInputGetAutoRefreshValues** (void *_, struct **MSXE302x__AnalogInputGetAutoRefreshValuesResponse** *Response)

Returns the values acquired in auto refresh mode.

- int **MSXE302x__AnalogInputStopAndReleaseAutoRefresh** (void *_, struct **MSXE302x__Response** *Response)

Stops the current autorefresh acquisition.

- int **MSXE302x__AnalogInputInitAndStartSequence** (xsd__unsignedLong ulNbrOfChannel, struct **MSXE302x__unsignedLong16FixedArrayParam** *pulChannelList, struct **MSXE302x__unsignedLong16FixedArrayParam** *pulGainArray, struct **MSXE302x__unsignedLong16FixedArrayParam** *pulPolarityArray, xsd__unsignedLong ulConversionTime, xsd__unsignedLong ulConversionTimeUnit, xsd__unsignedLong ulNbrOfSequence, xsd__unsignedLong ulNbrMaxSequenceToTransfer, xsd__unsignedLong ulDelayMode, xsd__unsignedLong ulDelayTimeUnit, xsd__unsignedLong ulDelayValue, xsd__unsignedLong ulTriggerMask, xsd__unsignedLong ulTriggerMode, xsd__unsignedLong ulHardwareTriggerEdge, xsd__unsignedLong ulHardwareTriggerCount, xsd__unsignedLong ulByTriggerNbrOfSeqToAcquire, xsd__unsignedLong ulDataFormat, xsd__unsignedLong ulOption1, xsd__unsignedLong ulOption2, xsd__unsignedLong ulOption3, struct **MSXE302x__Response** *Response)

Initialise and start the analog input sequence acquisition mode.

- int **MSXE302x__AnalogInputStopAndReleaseSequence** (void *_, struct **MSXE302x__Response** *Response)

Stop and release the analog input sequence acquisition mode.

- int **MSXE302x__CalibrationStart** (xsd__unsignedLong ulCalibrationMode, xsd__unsignedLong ulGain, xsd__double dCalibrationValue, struct **MSXE302x__Response** *Response)

This function start the calibration thread.

- int **MSXE302x__CalibrationGetCurrentStatus** (void *_, struct **MSXE302x__CalibrationGetCurrentStatusResponse** *Response)

This function return the current calibration status.

- int **MSXE302x__CalibrationNextStep** (void *_, struct **MSXE302x__Response** *Response)

This function start the next calibration step.

- int **MSXE302x__CalibrationBreak** (void *_, struct **MSXE302x__Response** *Response)
This function break the current calibration.

4.1.1 Typedef Documentation

4.1.1.1 typedef char* xsd__string

4.1.1.2 typedef char xsd__char

4.1.1.3 typedef float xsd__float

4.1.1.4 typedef double xsd__double

4.1.1.5 typedef int xsd__int

4.1.1.6 typedef long xsd__long

4.1.1.7 typedef unsigned char xsd__unsignedByte

4.1.1.8 typedef unsigned int xsd__unsignedInt

4.1.1.9 typedef unsigned short int xsd__unsignedShort

4.1.1.10 typedef unsigned long xsd__unsignedLong

4.1.2 Function Documentation

4.1.2.1 int MXCommon__GetModuleType (void * ___, struct MXCommon__ByteArrayResponse * Response)

Parameters

[in] ___ : no input parameter

[out] **Response** • sArray : Module type string
 • sResponse Composed of iReturnValue and syserrno

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

4.1.2.2 int MXCommon__GetHostname (void * ___, struct MXCommon__ByteArrayResponse * Response)

Parameters

[in] ___ : no input parameter

[out] **Response** • sArray : Hostname of the module
 • iReturnValue : Return value

- 0 : success
- -1: system error (see syserrno)
- syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__-Strerror\(\)](#).

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

4.1.2.3 int MXCommon__SetHostname (struct xsd__base64Binary * *bHostname*, struct MXCommon__Response * *Response*)

Parameters

- [in] *bHostname* : Hostname
- [out] *Response* • iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__-Strerror\(\)](#).

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

4.1.2.4 int MXCommon__GetClientConnections (void * *_*, struct MXCommon__ByteArrayResponse * *Response*)

Parameters

- [in] *_* : no input parameter
- [out] *Response* • sArray : string containing the list of connected clients.
 • sResponse Composed of iReturnValue and syserrno

The sArray string is of the form IP-Address:first connection-second connection---- IP-Address:first connection-second connection----

Sample: 172.16.3.43:8989-5555 172.16.3.200:8989

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

4.1.2.5 int MXCommon__Strrror (xsd_int errnum, struct MXCommon__ByteArrayResponse * Response)

Usually SOAP functions return this value in a variable named syserror, which is meaningful only when the function return value, usually called iReturnValue, indicate an error (that is, have a value of -1 or -100, depending of the case).

Parameters

- [in] ***errnum*** : Error number
- [out] ***Response***
 - sArray : See the description below.
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno).
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strrror\(\)](#).

```
STRERROR(3)                                              Linux Programmer's Manual
STRERROR(3)

NAME
strerror, strerror_r - return string describing error code

SYNOPSIS
#include <string.h>

char *strerror(int errnum);

#define _XOPEN_SOURCE 600
#include <string.h>

int strerror_r(int errnum, char *buf, size_t n);

DESCRIPTION
The strerror() function returns a string describing the error code passed
in the argument errnum, possibly using the LC_MESSAGES part of the current
locale to select the appropriate language.
This string must not be modified by the application, but may be modified
by a subsequent call to perror() or strerror(). No library function will
modify this string.

The strerror_r() function is similar to strerror(), but is thread safe.
It returns the string in the user-supplied buffer buf of length n.

RETURN VALUE
The strerror() function returns the appropriate error description string,
or an unknown error message if the error code is unknown.
The value of errno is not changed for a successful call, and is set to a non-zero
value upon error.
The strerror_r() function returns 0 on success and -1 on failure, setting errno.

ERRORS
EINVAL The value of errnum is not a valid error number.

ERANGE Insufficient storage was supplied to contain the error description string.

CONFORMING TO
SVID 3, POSIX, 4.3BSD, ISO/IEC 9899:1990 (C89).
strerror_r() with prototype as given above is specified by SUSv3,
and was in use under Digital Unix and HP Unix. An incompatible function,
with prototype

char *strerror_r(int errnum, char *buf, size_t n);
```

is a GNU extension used by glibc (since 2.0), and must be regarded as obsolete in view of SUSv3.
The GNU version may, but need not, use the user-supplied buffer.
If it does, the result may be truncated in case the supplied buffer is too small.
The result is always NUL-terminated.

SEE ALSO
`errno(3)`, `perror(3)`, `strsignal(3)`

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

4.1.2.6 int MXCommon__Reboot (void * *_*, struct MXCommon__Response * *Response*)

Parameters

[in] *_* : no input parameter
[out] **Response** • *iReturnValue* : Return value

- 0 : success
- -1: system error (see syserrno)

- *syserrno* : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

4.1.2.7 int MXCommon__ResetAllIIOFunctionalities (xsd__unsignedLong *ulOption*, struct MXCommon__Response * *Response*)

The behavior of the function depends on the MSX-E system that is used.

On MSX-E3511: Stop the watchdogs and stop the generators
On MSX-E3601: Stop the sequence acquisition and stop the calibration
On MSX-E3701: Stop the acquisition

Parameters

[in] **ulOption** Reserved. Set to 0
[out] **Response** *iReturnValue*

- **0** The remote function performed OK
- **-1** Internal system error occurred. See value of syserrno
- **-100** Function not supported by the system

syserrno system error code (the value of the libc "errno" code)

Return values

0 SOAP_OK
Others See SOAP error

4.1.2.8 int MXCommon__DataserverRestart (xsd__unsignedLong *ulAction*, xsd__unsignedLong *ulOption*, struct MXCommon__Response * *Response*)

Parameters

[in] *ulAction* : action

- 0: normal restart
- 1: with cache file reset
- 2: with cache file deletion

[in] *ulOption* : Reserved

[out] *Response* • *iReturnValue* : Return value

- 0 : success
- -1: system error (see syserrno)
- syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

Note

(revision>6386) Depending on the system type, can be used to restart the data-recv service as well. In this case, parameter action is ignored.

4.1.2.9 int MXCommon__GetEthernetLinksStates (void * ___, struct MXCommon__GetEthernetLinksStatesResponse * *Response*)

Parameters

[in] ___ : no input parameter

[out] *Response* Structure that contains the MSX-E Ethernet links states and errors:

sResponse.iReturnValue

- **0** The remote function performed OK
- **-1** System error occurred
- **-2** Fail to get Ethernet links states
- **-100** Internal system error occurred. See value of syserrno

sResponse.syserrno system error code (the value of the libc "errno" code)

sPort0: First port informations

- **ulState**
 - **0** Link down
 - **1** Link up
- **ulSpeed**
 - **10** 10 Mb/s
 - **100** 100 Mb/s
- **ulDuplex**
 - **0** Half duplex
 - **1** Full duplex

- **ulInfo1** Reserverd
- **ulInfo2** Reserverd

sPort1: Second port informations

- **ulState**
 - **0** Link down
 - **1** Link up
- **ulSpeed**
 - **10** 10 Mb/s
 - **100** 100 Mb/s
- **ulDuplex**
 - **0** Half duplex
 - **1** Full duplex
- **ulInfo1** Reserverd
- **ulInfo2** Reserverd

Return values

0 SOAP_OK

Others See SOAP error

4.1.2.10 int MXCommon__GetModuleTemperatureValueAndStatus (xsd__unsignedLong *ulOption*, struct MXCommon__GetModuleTemperatureValueAndStatusResponse * *Response*)

Parameters

- [in] ***ulOption*** : Reserved
- [out] ***Response***
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - dValue : Temperature value in Degree Celsius
 - ulTemperatureStatus : Temperature Status :
 - TEMPERATURE_INITIAL = 0 : Temperature not ready
 - TEMPERATURE_TOOWLOW = 1 : Temperature too low !
 - TEMPERATURE_LOW = 2 : Temperature under the min warning value
 - TEMPERATURE_NOMINAL = 3 : Temperature in the nominal range
 - TEMPERATURE_HIGH = 4 : Temperature over the max warning value
 - TEMPERATURE_TOOHIGH = 5 : Temperature too high !
 - ullInfo : Reserved

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

4.1.2.11 int MXCommon__SetModuleTemperatureWarningLevels (xsd__double *dMinimalWarningLevel*, xsd__double *dMaximalWarningLevel*, xsd__unsignedLong *ulOption*, struct MXCommon__Response * *Response*)

Parameters

- [in] *dMinimalWarningLevel* : Minimal temperature warning level in Degree : 5 to 60 Degree Celsius
- [in] *dMaximalWarningLevel* : Maximal temperature warning level in Degree : 5 to 60 Degree Celsius
- [in] *ulOption* : Reserved
- [out] ***Response***
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

- SOAP_OK*** SOAP call success
- otherwise*** SOAP protocol error

4.1.2.12 int MXCommon__SetHardwareTriggerFilterTime (xsd__unsignedLong *ulFilterTime*, xsd__unsignedLong *ulOption*, struct MXCommon__Response * *Response*)

Parameters

- [in] *ulFilterTime* : filter time for the hardware trigger input = multiplier from 250 ns step (max value : 65535).
- 0 : disable the filter
- >1: enable the filter and set the filter time
- [out] ***Response***
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
- [in] *ulOption* Reserved

Return values

- SOAP_OK*** SOAP call success
- otherwise*** SOAP protocol error

4.1.2.13 int MXCommon__GetHardwareTriggerFilterTime (xsd__unsignedLong *ulOption*, struct MXCommon__GetHardwareTriggerFilterTimeResponse * *Response*)

Parameters

- [in] *ulOption* : Reserved

[out] **Response**

- ulFilterTime : filter time for the hardware trigger input = multiplier from 250 ns step (max value : 65535).
 - 0 : filter disabled
 - >1: Filter enabled.
- sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
- sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

4.1.2.14 int MXCommon__GetHardwareTriggerState (xsd__unsignedLong *ulOption*, struct MXCommon__GetHardwareTriggerStateResponse * *Response*)

Parameters

[in] *ulOption* : Reserved

[out] **Response**

- ulState : Hardware trigger input state.
 - 0: Hardware trigger input is low
 - 1: Hardware trigger input is high.
- sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
- sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

4.1.2.15 int MXCommon__SetCustomerKey (struct xsd__base64Binary * *bKey*, struct xsd__base64Binary * *bPublicKey*, struct MXCommon__Response * *Response*)

Parameters

[in] *bKey* : Customer key (only writable on the module) [32 bytes containing a AES key]

[in] *bPublicKey* : IV (Initialisation vector) for the AES cryptography [16 bytes containing a AES key]

[out] **Response**

- sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
- sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

4.1.2.16 int MXCommon__TestCustomerID (void * ___, struct MXCommon__- TestCustomerIDResponse * Response)

Parameters

[in] ___ : No Input

[out] ***Response*** • sResponse.iReturnValue : Return value

– 0 : success

– -1: system error (see syserrno)

- sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

- bValueArray : non encrypted value array [16 bytes of random data]

- bCryptedValueArray : Encrypted value array [16 bytes of the encrypted random data]

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

4.1.2.17 int MXCommon__SetTime (xsd__unsignedLong ulLowTime, xsd__unsignedLong ulHighTime, struct MXCommon__Response * Response)

Parameters

[in] ***ulLowTime*** : Number of microseconds since the begin of the second

[in] ***ulHighTime*** : Number of seconds since the Epoch (1st January,1970)

[out] ***Response*** • sResponse.iReturnValue : Return value

– 0 : success

– -1: system error (see syserrno)

- sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

4.1.2.18 int MXCommon__SysToHardwareClock (void * ___, struct MXCommon__Response * Response)

Parameters

[in] ___ No input parameter

[out] ***Response*** • sResponse.iReturnValue : Return value

- 0 : success
- -1: system error (see syserrno)
- sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

If this function fails, it means the module does not have a hardware RTC, or the hardware is not functional. Check the "hwclock" subsystem status.

4.1.2.19 int MXCommon__HardwareClockToSys (void * ___, struct MXCommon__Response * Response)

When the hardware clock is present, the system time is automatically set to it when the module becomes master on the inter-module synchronisation bus.

Parameters

- [in] ___ No input parameter
- [out] **Response** • sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
- sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

If this function fails, it means the module does not have a hardware RTC, or the hardware is not functional. Check the "hwclock" subsystem status.

4.1.2.20 int MXCommon__GetTime (void * ___, struct MXCommon__GetTimeResponse * Response)

Parameters

- [in] ___ : No input parameter
- [out] **Response** • sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
- sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
- ulLowTime : Number of microseconds since the begin of the second
- ulHighTime : Number of seconds since the Epoch (1st January,1970)

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

4.1.2.21 int MXCommon__GetUpTime (void * *_*, struct MXCommon__GetUpTimeResponse * *Response*)

Parameters

- [in] *_* : no input parameter
- [out] ***Response*** • *sResponse.iReturnValue* : Return value
 - 0 : success
 - -1: system error (see syserrno)
- *sResponse.syserrno* : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
- *ulUpTime* : Number of seconds since the last boot of the system.

Return values

- SOAP_OK*** SOAP call success
otherwise SOAP protocol error

4.1.2.22 int MXCommon__GetAutoConfigurationFile (void * *_*, struct MXCommon__GetAutoConfigurationFileResponse * *Response*)

Parameters

- [in] *_* : No input parameter
- [out] ***Response*** • *sResponse.iReturnValue* : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - -100 : Error of the read of the auto configuration file
- *sResponse.syserrno* : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
- *bArray* : Array of Bytes of the file
- *ulEOF* : End of file flag

Return values

- SOAP_OK*** SOAP call success
otherwise SOAP protocol error

4.1.2.23 int MXCommon__SetAutoConfigurationFile (struct xsd__base64Binary * *ByteArrayInput*, xsd__unsignedLong *ulEOF*, struct MXCommon__Response * *Response*)

Parameters

- [in] ***ByteArrayInput*** : Array of Bytes of the file
- [in] ***ulEOF*** : End of file flag
- [out] ***Response*** • *sResponse.iReturnValue* : Return value
 - 0 : success
 - -1: system error (see syserrno)

- sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

4.1.2.24 int MXCommon__StartAutoConfiguration (void * ___, struct MXCommon__ByteArrayResponse * Response)

Parameters

[in] ___ : No input parameter

[out] **Response** • sResponse.iReturnValue : Return value

– 0 : success

– -1: system error (see syserrno)

- sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

– sArray : message returned by the auto configuration start

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

4.1.2.25 int MXCommon__InitAndStartSynchroTimer (xsd__unsignedLong ulTimeBase, xsd__unsignedLong ulReloadValue, xsd__unsignedLong ulNbrOfCycle, xsd__unsignedLong ulGenerateTriggerMode, xsd__unsignedLong ulOption01, xsd__unsignedLong ulOption02, xsd__unsignedLong ulOption03, xsd__unsignedLong ulOption04, struct MXCommon__Response * Response)

Parameters

[in] **ulTimeBase** : Time base of the timer (0 for us, 1 for ms, 2 for s)

[in] **ulReloadValue** : Timer reload value (0 to 0xFFFF), minimum reload time is 5 us

[in] **ulNbrOfCycle** : Number of timer cycle

• 0: continuous

• > 0: defined number of cycle

[in] **ulGenerateTriggerMode** :

• 0: Wait the time overflow to set the synchronisation trigger

• 1: Set the synchronisation trigger by the start of the timer and after each time overflow

[in] **ulOption01** : Define the source of the trigger

• 0 : Trigger disabled

• 1 : Enable the hardware digital input trigger

[in] **ulOption02** : Define the edge of the hardware trigger who generates a trigger action

• 1 : rising edge (Only if hardware trigger selected)

• 2 : falling edge (Only if hardware trigger selected)

- 3 : Both front (Only if hardware trigger selected)

[in] ***ulOption03*** : Define the number of trigger events before the action occur

- 1 : all trigger event start the action
- max value : 65535

[in] ***ulOption04*** : Reserved

[out] ***Response*** • **sResponse.iReturnValue** : Return value

- 0 : success
- -1: system error (see syserrno)
- -2: not available time base
- -3: timer reload value can not be greater than 65535
- -4: minimum time reload is 5 us
- -5: Number of cycle can not be greater than 65535
- -6: Generate trigger mode error
- -100: Init timer error
- -101: Start timer error

- **sResponse.syserrno** : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#). May be ENOSYS : Function not implemented.

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

4.1.2.26 int MXCommon__StopAndReleaseSynchroTimer (xsd__unsignedLong *ulOption01*, struct MXCommon__Response * *Response*)

Parameters

[in] ***ulOption01*** : Reserved

[out] ***Response*** • **sResponse.iReturnValue** : Return value

- 0 : success
- -1: system error (see syserrno)
- -100: Start/Stop timer error

- **sResponse.syserrno** : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#). May be ENOSYS : Function not implemented.

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

4.1.2.27 int MXCommon__GetConfigurationBackupFile (void * *_*, struct MXCommon__FileResponse * *Response*)

Parameters

[in] *_* : No input parameter

[out] ***Response*** • **sResponse.iReturnValue** : Return value

- 0 : success
- -1: system error (see syserrno) (see syserrno)
- sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
- bArray : Array of Bytes of the file
- ulEOF : End of file flag

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

This function is designed to be called repeatedly until no more data is available. At this point the flag ulEOF is set.

Below is an example in pseudo-C.

```
int dummy;
struct MXCommon__FileResponse Response;
while(1)
{
if ( MXCommon__GetConfigurationBackupFile(&dummy, &Response) != SOAP_OK)
{
// handle soap error
}
if (Response.iReturnValue)
{
// handle remote error (Response.syserrno contains more information)
}
// do something with the data, for example save it in a file
write(fd, Response.bArray.__ptr, Response.bArray.__size);
// if this is the end of the file, quit the loop
if(Response.ulEOF)
break;
}
*
```

4.1.2.28 int MXCommon__ApplyConfigurationBackupFile (struct xsd__base64Binary * *ByteArrayInput*, xsd__unsignedLong *ulEOF*, struct MXCommon__Response * *Response*)

Parameters

- [in] **ByteArrayInput** : Array of Bytes of the file
- [in] **ulEOF** : End of file flag
- [out] **Response**
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

This function is designed to be called repeatedly until all data is transferred. At this point the flag ulEOF must be set to 1. The new configuration is then applied.

4.1.2.29 int MXCommon__ChangePassword (struct xsd__base64Binary * PreviousUser, struct xsd__base64Binary * PreviousPassword, struct xsd__base64Binary * NewUser, struct xsd__base64Binary * NewPassword, struct MXCommon__Response * Response)

The changes are immediately active.

Parameters

- [in] _ : No input parameter
- [out] **Response**
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: string PreviousUser is invalid
 - -2: string PreviousPassword is invalid
 - -3: string NewUser is invalid
 - -4: string NewPassword is invalid
 - -5: authentication failed
 - -100: system error while saving tokens (use syserrno for more information)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - sArray : message returned by the auto configuration start

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

Warning

The parameters transit in clear text. Use this functionality only on trusted networks.

Given that ADDI-DATA GmbH takes security seriously, there is no way to change the password without knowing it. No "hidden back-door". This function makes it all too easy to lock a module, if you don't remember the password you set on it.

4.1.2.30 int MXCommon__GetSubSystemState (xsd__unsignedLong SubsystemID, struct MXCommon__unsignedLongResponse * Response)

Parameters

- [in] **SubsystemID** sub-system numerical ID
- [out] **Response**
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error while executing the request (see syserrno)
 - -2: invalid parameter SubsystemID
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - Value The state of the sub-system "Id" at the moment of the execution of the request.

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

4.1.2.31 int MXCommon__GetSubsystemIDFromName (struct xsd__base64Binary * SubsystemName, struct MXCommon__unsignedLongResponse * Response)

Parameters

[in] **SubsystemName** sub-system symbolic name.

[out] **Response** • sResponse.iReturnValue :Return value

- 0 : success
- -1: system error while executing the request (see syserrno)
- -2: invalid parameter SubsystemName
- sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
- Value The numerical ID of the sub-system "SubsystemName".

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

4.1.2.32 int MXCommon__GetStateIDFromName (xsd__unsignedLong SubsystemID, struct xsd__base64Binary * StateName, struct MXCommon__unsignedLongResponse * Response)

Parameters

[in] **SubsystemID** sub-system numerical ID

[in] **StateName** state symbolic name.

[out] **Response** • sResponse.iReturnValue : Return value

- 0 : success
- -1: system error while executing the request (see syserrno)
- -2: invalid parameters SubsystemID or StateName
- sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
- Value The numerical ID of the state "StateName".

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

4.1.2.33 int MXCommon__GetSubsystemNameFromID (xsd__unsignedLong SubsystemID, struct MXCommon__ByteArrayResponse * Response)

Parameters

- [in] **SubsystemID** sub-system numerical ID.
- [out] **Response**
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error while executing the request (see syserrno)
 - -2: invalid parameter SubsystemName
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - sArray : The symbolic name associated with the ID.

Return values

- SOAP_OK** SOAP call success
otherwise SOAP protocol error

4.1.2.34 int MXCommon__GetStateNameFromID (xsd__unsignedLong SubsystemID, xsd__unsignedLong StateID, struct MXCommon__ByteArrayResponse * Response)

Parameters

- [in] **SubsystemID** sub-system numerical ID.
- [in] **StateID** sub-system numerical ID.
- [out] **Response**
 - sResponse.iReturnValue : Return value
 - 0 success
 - -1 system error while executing the request (see syserrno)
 - -2 invalid parameters SubsystemID or StateID
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - sArray The symbolic name associated with the state numerical ID.

Return values

- SOAP_OK** SOAP call success
otherwise SOAP protocol error

4.1.2.35 int MXCommon__GetOptionInformation (void * _, xsd__unsignedLong ulOption01, xsd__unsignedLong ulOption02, struct MXCommon__ByteArrayResponse * Response)

Parameters

- [in] **ulOption01:** not used, set it to 0
- [in] **ulOption02:** not used, set it to 0
- [out] **Response**
 - sArray : Option information string
 - sResponse Composed of iReturnValue and syserrno

Return values

- SOAP_OK** SOAP call success
otherwise SOAP protocol error

4.1.2.36 int MXCommon_SetToMaster (void * ___, xsd__unsignedLong *ulState*, xsd__unsignedLong *ulOption01*, xsd__unsignedLong *ulOption02*, struct MXCommon_Response * *Response*)

Parameters

[in] *ulState* State of the supermaster mode

- **0** automatic mode (default). The state of the system (master or slave) will be automatically detected by the system
- **1** Set to master mode at all time. The system will always be detected as master

[in] *ulOption01* Reserved. Set to 0

[in] *ulOption02* Reserved. Set to 0

[out] *Response iReturnValue*

- **0** The remote function performed OK
- **-1** System error occurred
- **-2** The PLD is not working
- **-3** The ulFilterTime parameter is wrong
- **-100** Internal system error occurred. See value of syserrno *syserrno* system error code (the value of the libc "errno" code)

Return values

0 SOAP_OK

Others See SOAP error

4.1.2.37 int MXCommon_GetSynchronizationStatus (void * ___, xsd__unsignedLong *ulOption01*, xsd__unsignedLong *ulOption02*, struct MXCommon_unsignedLongResponse * *Response*)

Parameters

[in] *ulOption01* Reserved. Set to 0

[in] *ulOption02* Reserved. Set to 0

[out] *Response sResponse.iReturnValue*

- **0** The remote function performed OK
- **-1** System error occurred
- **-2** The PLD is not working
- **-100** Internal system error occurred. See value of syserrno

sResponse.syserrno system error code (the value of the libc "errno" code)

ulValue State of the supermaster mode

- **0** Automatic mode (default). The state of the system (master or slave) will be automatically detected by the system
- **1** MSXE is always set as a master. The system will always be detected as master

Return values

0 SOAP_OK

Others See SOAP error

4.1.2.38 int MSXE302x__AnalogInputGetChannelType (xsd__unsignedLong *ulOption1*, struct MSXE302x__AnalogInputGetChannelTypeResponse * *Response*)

Parameters

[in] *ulOption1* : Reserved

[out] *Response* :

iReturnValue :

- 0: means the remote function performed OK
- -1: means an system error occured

syserrno : system-error code (the value of the libc "errno" code) *ulType* : Array that contain the channels type (0 : voltage, 1 : current)

- *ulType* [0] : Channel 0 type
- ...
- *ulType* [15] : Channel 15 type

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

4.1.2.39 int MSXE302x__AnalogMeasureGetConfiguration (xsd__unsignedLong *ulModule*, struct MSXE302x__AnalogMeasureGetConfigurationResponse * *Response*)

Parameters

[in] *ulOption1* : Reserved

[out] *Response* :

iReturnValue :

- 0: means the remote function performed OK
- -1: means an system error occured

sAcquisition :

- *ulConvertTimeUnit* 0: micro second 1: milli second 2: second
- *pul_ConvertTimeValue* : (10,65535)
- *pul_ChannelInitialisation* (Are channels initialised and how) pointer to unsigned long[16]. bit 31 = initialised : (0,1) bit 30= polarity : (0,1) - 0:bipolar, 1:unipolar bits 29-0 : gain : (1,2) - 0: 10 V , 1: 5V

sAutoRefresh :

- *ulChannelMask* Mask of channels used for the auto refresh mode
- *ulAverageMode* Determine average mode 0: Sequence 1 : Channel
- *ulAverageValue* Determine the number of sequence for a average value calculation
- *ulDataFormat* D0: Time stamp information. 0 without, 1 with. D1 : Data format 0: digital 1: analog (in V)

sSequence :

- *ulSequenceSize* Sequence array size
- *ulSequence* Sequence channel array
- *ulSequenceInterrupt* Determine the number of sequences for the interrupt
- *ulNbrOfSequence* Determine the number total of sequences. 0: Continuous

- *ulDelayFlag* 0 : Disabled 1 : Enabled
- *ulDelayMode* 0 : delay not used 1 : mode 1 2 : mode 2
- *ulDelayTimeUnit* Delay time unit 1: micros 2 : ms 3 : s
- *ulDelayTime* Delay time
- *ulDataFormat* D0: Time stamp information. 0 without, 1 with.
D1 : Sequence counter information. 0 without, 1 with.
D2 : Data format 0: digital 1: analog (in V)

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

4.1.2.40 int MSXE302x__AnalogInputInitAndStartAutoRefresh (xsd__unsignedLong *ulChannelMask*, struct MSXE302x__unsignedLong16FixedArrayParam * *pulGainArray*, struct MSXE302x__unsignedLong16FixedArrayParam * *pulPolarityArray*, xsd__unsignedLong *ulAverageMode*, xsd__unsignedLong *ulAverageValue*, xsd__unsignedLong *ulConversionTime*, xsd__unsignedLong *ulConversionTimeUnit*, xsd__unsignedLong *ulTriggerMask*, xsd__unsignedLong *ulTriggerMode*, xsd__unsignedLong *ulHardwareTriggerEdge*, xsd__unsignedLong *ulHardwareTriggerCount*, xsd__unsignedLong *ulByTriggerNbrOfSeqToAcquire*, xsd__unsignedLong *ulDataFormat*, xsd__unsignedLong *ulOption1*, xsd__unsignedLong *ulOption2*, xsd__unsignedLong *ulOption3*, struct MSXE302x__Response * *Response*)

Parameters

[in] *ulChannelMask* Mask of the channel to acquire by the auto refresh (1 bit = 1 Channel)

[in] *pulGainArray* Define the gain (1 or 2) to use for each channel.

Information : by the channel type "current", the gain 2 is recommended.

- 1 : +10 V or max 20mA when Unipolar, +/-10V or +/- max 20mA when Bipolar
- 2 : +5 V or 20mA when Unipolar, +/-5V or +/- 20mA when Bipolar Each index of the array correspond to the channel :
sample :
 - [0] : Define the gain for the channel 0
 - [1] : Define the gain for the channel 1
 - ...Remark: When using a current version of the MSX-E302x, gain 2 has to be used.

[in] *pulPolarityArray* Define the polarity (0:Unipolar or 1:Bipolar) to use for each channel Each index of the array correspond to the channel :

sample :

- [0] : Define the polarity for the channel 0
- [1] : Define the polarity for the channel 1
- ...

Remark: When using the unipolar mode, the raw value for 0 volt (or 0 ampere) will be 32767.

[in] *ulAverageMode* Set the average mode :

- 0 : not used
- 1 : average per Sequence

- 2 : average per channel

[in] ***ulAverageValue*** Set the average value (only used, when average is used) :

- 0 : not used
- max value : 255

[in] ***ulConversionTime*** Conversion Time

- range from min 10 to 65535 when the unit is the microsecond
- range from min 1 to 65535 when the unit is the millisecond
- range from min 1 to 65535 when the unit is the second

[in] ***ulConversionTimeUnit*** Conversion Time Unit

- 0 : microsecond
- 1 : millisecond
- 2 : second

[in] ***ulTriggerMask*** Define the source of the trigger

- 0 : trigger disabled
- 1 : Enable Hardware Digital Input Trigger
- 2 : Enable Synchro Trigger

[in] ***ulTriggerMode*** Define the trigger mode

- 1 : One shot trigger
- 2 : Sequence trigger

[in] ***ulHardwareTriggerEdge*** Define the edge of the hardware trigger who generates a trigger action

- 1 : rising edge (Only if hardware trigger selected)
- 2 : falling edge (Only if hardware trigger selected)
- 3 : Both front (Only if hardware trigger selected)

[in] ***ulHardwareTriggerCount*** Define the number of trigger events before the action occur

- 0 or 1 : all trigger event start the action
- max value : 65535

[in] ***ulByTriggerNbrOfSeqToAcquire*** Define the number of sequence to acquire by each trigger event

- 0 : continuous mode
- <> 0 : number of sequence : (1..0xFFFFFFFF)

[in] ***ulDataFormat*** D0 : Time stamp information

- 0: no time stamp information
- 1: time stamp information

D1 : Data format

- 0: Digital value
- 1: Analog value (in V)

[in] ***ulOption1*** Reserved

[in] ***ulOption2*** Reserved

[in] ***ulOption3*** Reserved

[out] ***Response*** :

iReturnValue :

- 0 : means the remote function performed OK

- -1: means an system error occured
- -2: The channel mask cannot be null
- -3: Channel Mask error
- -4: Gain selection error
- -5: Polarity selection error
- -6: not available average mode
- -7: not available average value
- -8: The minimal converting time is 10 us !
- -9: Not available conversion time unit
- -10: Trigger mode : 2 different mode cannot be simultaneously be activated
- -11: Hardware trigger : front definition error
- -12: Hardware trigger count value not available
- -13: Nbr of sequence to acquire by trigger mode not available
- -14: Data format not available
- -100: Channel initialisation kernel function error
- -101: Conversion time initialisation kernel function error
- -102: Average mode initialisation kernel function error
- -103: hardware trigger initialisation/enable kernel function error
- -104: hardware trigger disable kernel function error
- -105: synchro trigger initialisation/enable kernel function error
- -106: synchro trigger disable kernel function error
- -107 Sequence trigger count initialisation error
- -108: Start auto refresh kernel function error

syserrno : system-error code (the value of the libc "errno" code)

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

4.1.2.41 int MSXE302x__AnalogInputGetAutoRefreshValues (void * ___, struct MSXE302x__AnalogInputGetAutoRefreshValuesResponse * *Response*)

Parameters

[in] ___ Dummy parameter

[out] **Response** :

iReturnValue :

- 0: means the remote function performed OK
- -1: means an system error occured
- -100: GetAutoRefreshAllValues kernel function error

ulTimeStampLow : number of microseconds since the begin of the second

ulTimeStampHigh : number of seconds since the Epoch

ulCounterValue : Array that contain the counter values

ulValue : Array that contain the channels values

- `ulValues [0]` : Channel 0 value

- ...

- `ulValues [15]` : Channel 15 value

Remark: When using the unipolar mode, the raw value for 0 volt (or 0 ampere) will be 32767.

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

4.1.2.42 int MSXE302x_AnalogInputStopAndReleaseAutoRefresh (void * `_`, struct MSXE302x_Response * `Response`)

Parameters

[in] `_` Dummy parameter

[out] `Response` :

iReturnValue :

- 0: means the remote function performed OK
- -1: means an system error occurred
- -100: StopAutoRefresh kernel function error

`syserrno` : system-error code (the value of the libc "errno" code)

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

Must be called before any another call to `MSXE302x_AnalogInputInitAndStartAutoRefresh`.

4.1.2.43 int MSXE302x_AnalogInputInitAndStartSequence (xsd_unsignedLong `ulNbrOfChannel`, struct MSXE302x_unsignedLong16FixedArrayParam * `pulChannelList`, struct MSXE302x_unsignedLong16FixedArrayParam * `pulGainArray`, struct MSXE302x_unsignedLong16FixedArrayParam * `pulPolarityArray`, xsd_unsignedLong `ulConversionTime`, xsd_unsignedLong `ulConversionTimeUnit`, xsd_unsignedLong `ulNbrOfSequence`, xsd_unsignedLong `ulNbrMaxSequenceToTransfer`, xsd_unsignedLong `ulDelayMode`, xsd_unsignedLong `ulDelayTimeUnit`, xsd_unsignedLong `ulDelayValue`, xsd_unsignedLong `ulTriggerMask`, xsd_unsignedLong `ulTriggerMode`, xsd_unsignedLong `ulHardwareTriggerEdge`, xsd_unsignedLong `ulHardwareTriggerCount`, xsd_unsignedLong `ulByTriggerNbrOfSeqToAcquire`, xsd_unsignedLong `ulDataFormat`, xsd_unsignedLong `ulOption1`, xsd_unsignedLong `ulOption2`, xsd_unsignedLong `ulOption3`, struct MSXE302x_Response * `Response`)

Parameters

[in] `ulNbrOfChannel` : nbr of channel in the sequence

[in] `pulChannelList` : list of the channel who compose the sequence

[in] `pulGainArray` Define the gain (1 or 2) to use for each channel.

Information : by the channel type "current", the gain 2 is recommended.

- 1 : +10 V or max 20mA when Unipolar, +/-10V or max +/-20mA when Bipolar
 - 2 : +5 V or 20 mA when Unipolar, +/-5V or +/- 20mA when Bipolar Each index of the array correspond to the channel :
- sample :
- [0] : Define the gain for the channel 0
 - [1] : Define the gain for the channel 1
 - ...

Remark: When using a current version of the MSX-E302x, gain 2 has to be used.

[in] **pulPolarityArray** Define the polarity (0:Unipolar or 1:Bipolar) to use for each channel

Each index of the array correspond to the channel :

sample :

- [0] : Define the polarity for the channel 0
- [1] : Define the polarity for the channel 1
- ...

Remark: When using the unipolar mode, the raw value for 0 volt (or 0 ampere) will be 32767.

[in] **ulConversionTime** Conversion Time (min 10 us or 40 us)

[in] **ulConversionTimeUnit** Conversion Time Unit

- 0 : us
- 1 : ms

[in] **ulNbrOfSequence** : Number of sequence to acquire :

- 0 : continuous mode
- <> 0 : number of sequence

[in] **ulNbrMaxSequenceToTransfer** : Max nbr of sequence to acquire before a data transfer :
(1,65535)

[in] **ulDelayMode** : Delay Mode :

- 0 : delay not used
- 1 : mode 1
- 2 : mode 2

[in] **ulDelayTimeUnit** : Selection of the time unit

- 0: us
- 1: ms
- 2: s

[in] **ulDelayValue** : Delay Value : (1..0xFFFF)

[in] **ulTriggerMask** Define the source of the trigger

- 0 : trigger disabled
- 1 : Enable Hardware Digital Input Trigger
- 2 : Enable Synchro Trigger
- 3 : Enable both Hardware and Synchro Trigger

[in] **ulTriggerMode** Define the trigger mode

- 1 : One shot trigger
- 2 : Sequence trigger

[in] **ulHardwareTriggerEdge** Define the edge of the hardware trigger who generate a trigger action

- 1 : rising front (Only if hardware trigger selected)

- 2 : falling front (Only if hardware trigger selected)
- 3 : Both front (Only if hardware trigger selected)

[in] ***ulHardwareTriggerCount*** Define the number of trigger events before the action occur

- 0 or 1 : all trigger event start the action
- max value : 65535

[in] ***ulByTriggerNbrOfSeqToAcquire*** : define the number of sequence to acquire by each trigger event

- 0 : continuous mode
- <> 0 : number of sequence : (1..0xFFFFFFFF)

[in] ***ulDataFormat*** : Data format option

D0 : Time stamp information

- 0 : no time stamp information
- 1 : time stamp information

D1 : Sequence counter information

- 0 : No sequence counter information
- 1 : Sequence counter information

D2 : Data format

- 0 : 32/16 bit digital value
- 1 : 32-bit analog value (in V)

D3 : 16-Bit digital value

- 0 : 32-bit digital/analog value
- 1 : 16-bit digital value.

Only a pair number of acquisition channels (ulNbrOfChannel) can be selected.

[in] ***ulOption1*** : Reserved

[in] ***ulOption2*** : Reserved

[in] ***ulOption3*** : Reserved

[out] ***Response*** :

iReturnValue :

- 0: means the remote function performed OK
- -1: means an system error occurred
- -2: The nbr of channel in the sequence cannot be null
- -3: Channel index selection error
- -4: Gain selection error
- -5: Polarity selection error
- -6: The minimal converting time is 10 us !
- -7: Not available conversion time unit
- -8: Delay mode selection not available
- -9: Delay time unit selection not available
- -10: Delay value not available
- -11: Trigger mode : 2 different mode cannot be simultaneously be activated
- -12: Hardware trigger : edge definition error
- -13: Hardware trigger count value not available
- -14: Nbr of sequence to acquire by trigger mode not available
- -15: Data format not available

- -100: Channel initialisation kernel function error
- -101: Conversion time initialisation kernel function error
- -102: Delay initialisation kernel function error
- -103: hardware trigger initialisation/enable kernel function error
- -104: hardware trigger disable kernel function error
- -105: synchro trigger initialisation/enable kernel function error
- -106: synchro trigger disable kernel function error
- -107 Sequence trigger count initialisation error
- -108: Sequence initialisation kernel function error
- -109: Start sequence kernel function error

syserrno : system-error code (the value of the libc "errno" code)

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

4.1.2.44 int MSXE302x__AnalogInputStopAndReleaseSequence (void * __, struct MSXE302x__Response * Response)

Parameters

[in] __ : no input parameter

[out] **Response** :

iReturnValue :

- 0: means the remote function performed OK
- -1: means an system error occured
- -100: Stop sequence kernel function error
- -101: Release sequence kernel function error

syserrno : system-error code (the value of the libc "errno" code)

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

4.1.2.45 int MSXE302x__CalibrationStart (xsd__unsignedLong ulCalibrationMode, xsd__unsignedLong ulGain, xsd__double dCalibrationValue, struct MSXE302x__Response * Response)

Parameters

[in] **ulCalibrationMode** : Calibration mode selection:

- 0 Hex : All channels calibration via a external calibration source (voltage/current). Not available for mixing input types.
- 1 Hex : All channels calibration via the internal voltage calibration source. Not available for current or mixing input types.
- 2 Hex : Channel group 0 (Channel 0 to 3) calibration via a external calibration source (voltage/current).

- 102 Hex : Channel group 1 (Channel 4 to 7) calibration via a external calibration source (voltage/current).
- 202 Hex : Channel group 2 (Channel 8 to 11) calibration via a external calibration source (voltage/current).
- 302 Hex : Channel group 3 (Channel 12 to 15) calibration via a external calibration source (voltage/current).
- 3 Hex : Channel group 0 (Channel 0 to 3) calibration via the internal voltage calibration source. Not available for current inputs.
- 103 Hex : Channel group 1 (Channel 4 to 7) calibration via the internal voltage calibration source. Not available for current inputs.
- 203 Hex : Channel group 2 (Channel 8 to 11) calibration via the internal voltage calibration source. Not available for current inputs.
- 303 Hex : Channel group 3 (Channel 12 to 15) calibration via the internal voltage calibration source. Not available for current inputs.

[in] ***ulGain*** : Gain selection 1 or 2

[in] ***dCalibrationValue*** : Calibration value

[out] ***Response*** :

iReturnValue : Error value :

- 0: means the remote function performed OK
- -1: means an system error occured
- -2: Calibration mode selection error
- -3: Calibration gain selection error
- -4: Calibration value selection error
- -100: Start calibration kernel function error

syserrno : system-error code (the value of the libc "errno" code)

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

4.1.2.46 int MSXE302x_CalibrationGetCurrentStatus (void * ___, struct MSXE302x_CalibrationGetCurrentStatusResponse * ***Response***)

Parameters

[in] ___ : no input parameter

[out] ***Response*** :

iReturnValue : Error value :

- 0: means the remote function performed OK
- -1: means an system error occured
- -100: Get status calibration kernel function error
- -101: Save calibration read source error
- -102: Save calibration write destination error

ulStatus : TODO

ulDigitalValue : Last measured digital value

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

4.1.2.47 int MSXE302x__CalibrationNextStep (void * ___, struct MSXE302x__Response * Response)

Parameters

[in] ___ : no input parameter

[out] **Response** :

iReturnValue : Error value :

- 0: means the remote function performed OK
- -1: means an system error occured
- -100: Calibration next step kernel function error

syserrno : system-error code (the value of the libc "errno" code)

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

4.1.2.48 int MSXE302x__CalibrationBreak (void * ___, struct MSXE302x__Response * Response)

Parameters

[in] ___ : no input parameter

[out] **Response** :

iReturnValue : Error value :

- 0: means the remote function performed OK
- -1: means an system error occured
- -100: Calibration break kernel function error

syserrno : system-error code (the value of the libc "errno" code)

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

Index

__offset
 ByteArray, 51
 UnsignedLongArray, 67
 UnsignedShortArray, 68

__ptr
 ByteArray, 51
 UnsignedLongArray, 67
 UnsignedShortArray, 68
 xsd_base64Binary, 68

__size
 ByteArray, 51
 UnsignedLongArray, 67
 UnsignedShortArray, 68
 xsd_base64Binary, 68

bArray
 MXCommon_-
 GetAutoConfigurationFileResponse, 62

bCryptedValueArray
 MXCommon_TestCustomerIDResponse, 66

bValueArray
 MXCommon_TestCustomerIDResponse, 66

ByteArray, 51
 __offset, 51
 __ptr, 51
 __size, 51

Common functions, 10
Common general functions, 11
Common hardware trigger functions, 18
Common I/O auto configuration functions, 25
Common security functions, 20
Common synchronisation timer functions, 27
Common temperature functions, 17
Common time functions, 22
Common_autoconf
 MXCommon_GetAutoConfigurationFile, 26
 MXCommon_SetAutoConfigurationFile, 26
 MXCommon_StartAutoConfiguration, 26

Common_configuration
 MXCommon_-
 ApplyConfigurationBackupFile, 30
 MXCommon_ChangePassword, 30

MXCommon__GetConfigurationBackupFile, 29

Common_general
 MXCommon_DataserverRestart, 15
 MXCommon_GetClientConnections, 13
 MXCommon_GetEthernetLinksStates, 16
 MXCommon_GetHostname, 12
 MXCommon_GetModuleType, 12
 MXCommon_Reboot, 14
 MXCommon_ResetAllIIOFunctionalities, 15
 MXCommon_SetHostname, 12
 MXCommon_Strerror, 13

Common_hardware_trigger
 MXCommon_-
 GetHardwareTriggerFilterTime, 19
 MXCommon_GetHardwareTriggerState, 20
 MXCommon_-
 SetHardwareTriggerFilterTime, 19

Common_security
 MXCommon_SetCustomerKey, 21
 MXCommon_TestCustomerID, 22

Common_synchrotimer
 MXCommon_InitAndStartSynchroTimer, 27
 MXCommon_-
 StopAndReleaseSynchroTimer, 28

Common_temperature
 MXCommon_-
 GetModuleTemperatureValueAndStatus, 17
 MXCommon_-
 SetModuleTemperatureWarningLevels, 18

Common_time
 MXCommon__GetTime, 24
 MXCommon__GetUpTime, 24
 MXCommon__HardwareClockToSys, 24
 MXCommon_SetTime, 23
 MXCommon_SysToHardwareClock, 23

Customer option management, 34
CustomerOption
 MXCommon_GetOptionInformation, 34

dCurrentValue
 MSXE302x_-
 CalibrationGetCurrentStatusResponse,

58
 DefaultResponse, 51
 iReturnValue, 52
 syserrno, 52
 dTemperatureValue
 MXCommon_-
 GetModuleTemperatureValueAndStatusResponse, 57
 64
 iReturnValue
 DefaultResponse, 52
 MSXE302x_-
 AnalogMeasureGetConfigurationResponse, 55
 MSXE302x_Response, 59
 MXCommon_Response, 65
 MSX-E systems servers, 10
 MSX-E302x Autorefresh functions, 38
 MSX-E302x calibration functions, 47
 MSX-E302x functions, 36
 MSX-E302x Information functions, 36
 MSX-E302x Sequence functions, 43
 MSXE302x_AnalogInputGetAutoRefreshValues
 MSXE302x_Autorefresh, 41
 MSXE302x_public_doc.h, 96
 MSXE302x_AnalogInputGetAutoRefreshValuesResponse, 52
 sResponse, 53
 ulCounterValue, 53
 ulTimeStampHigh, 53
 ulTimeStampLow, 53
 ulValue, 53
 MSXE302x_AnalogInputGetChannelType
 MSXE302x_Information, 37
 MSXE302x_public_doc.h, 92
 MSXE302x_AnalogInputGetChannelTypeResponse, 53
 sResponse, 53
 ulType, 53
 MSXE302x_AnalogInputInitAndStartAutoRefresh
 MSXE302x_Autorefresh, 39
 MSXE302x_public_doc.h, 94
 MSXE302x_AnalogInputInitAndStartSequence
 MSXE302x_public_doc.h, 97
 MSXE302x_Sequence, 44
 MSXE302x_AnalogInputStopAndReleaseAutoRefresh
 MSXE302x_Autorefresh, 42
 MSXE302x_public_doc.h, 97
 MSXE302x_AnalogInputStopAndReleaseSequence
 MSXE302x_public_doc.h, 100
 MSXE302x_Sequence, 46
 MSXE302x_AnalogMeasureGetConfiguration
 MSXE302x_Information, 37
 MSXE302x_public_doc.h, 93
 MSXE302x__AnalogMeasureGetConfigurationResponse, 53
 iReturnValue, 55
 sAcquisition, 55
 sAutoRefresh, 55
 sSequence, 57
 sSoftware, 57
 sSynchro, 57
 sTrigger, 57
 ulAction, 57
 ulAverageMode, 55
 ulAverageValue, 55
 ulChannelInitialization, 55
 ulChannelMask, 55
 ulConvertTime, 55
 ulConvertTimeUnit, 55
 ulCount, 57
 ulDateFormat, 55
 ulDelayFlag, 56
 ulDelayMode, 57
 ulDelayTime, 57
 ulDelayTimeUnit, 57
 ulFlag, 57
 ulLevel, 57
 ulNbrOfSequence, 56
 ulRunningMode, 55
 ulSequence, 56
 ulSequenceInterrupt, 56
 ulSequenceSize, 56
 ulSequenceTriggerCount, 57
 MSXE302x_CalibrationBreak
 MSXE302x_Calib, 49
 MSXE302x_public_doc.h, 102
 MSXE302x_CalibrationGetCurrentStatus
 MSXE302x_Calib, 49
 MSXE302x_public_doc.h, 101
 MSXE302x_CalibrationGetCurrentStatusResponse, 57
 dCurrentValue, 58
 sResponse, 58
 ulError, 58
 ulStatus, 58
 MSXE302x_CalibrationNextStep
 MSXE302x_Calib, 49
 MSXE302x_public_doc.h, 102
 MSXE302x_CalibrationStart
 MSXE302x_Calib, 48
 MSXE302x_public_doc.h, 100
 MSXE302x_Response, 59
 iReturnValue, 59
 syserrno, 59

MSXE302x__unsignedLong16FixedArrayParam,
 60
 ulValue, 60
MSXE302x__unsignedLongResponse, 60
 sResponse, 60
 ulValue, 60
MSXE302x_Autorefresh
 MSXE302x__-
 AnalogInputGetAutoRefreshValues,
 41
 MSXE302x__-
 AnalogInputInitAndStartAutoRefresh,
 39
 MSXE302x__-
 AnalogInputStopAndReleaseAutoRefresh,
 42
MSXE302x_Calib
 MSXE302x_CalibrationBreak, 49
 MSXE302x_CalibrationGetCurrentStatus, 49
 MSXE302x_CalibrationNextStep, 49
 MSXE302x_CalibrationStart, 48
MSXE302x_Information
 MSXE302x_AnalogInputGetChannelType,
 37
 MSXE302x__-
 AnalogMeasureGetConfiguration, 37
MSXE302x_public_doc.h, 69
 MSXE302x__-
 AnalogInputGetAutoRefreshValues,
 96
 MSXE302x_AnalogInputGetChannelType,
 92
 MSXE302x__-
 AnalogInputInitAndStartAutoRefresh,
 94
 MSXE302x__-
 AnalogInputInitAndStartSequence,
 97
 MSXE302x__-
 AnalogInputStopAndReleaseAutoRefresh,
 97
 MSXE302x__-
 AnalogInputStopAndReleaseSequence,
 100
 MSXE302x__-
 AnalogMeasureGetConfiguration, 93
MSXE302x_CalibrationBreak, 102
MSXE302x_CalibrationGetCurrentStatus,
 101
MSXE302x_CalibrationNextStep, 102
MSXE302x_CalibrationStart, 100
MXCommon__-
 ApplyConfigurationBackupFile, 88
MXCommon_ChangePassword, 89
MXCommon_DataserverRestart, 78
MXCommon_GetAutoConfigurationFile, 85
MXCommon_GetClientConnections, 76
MXCommon_GetConfigurationBackupFile,
 87
MXCommon_GetEthernetLinksStates, 79
MXCommon__-
 GetHardwareTriggerFilterTime, 81
MXCommon_GetHardwareTriggerState, 82
MXCommon_GetHostname, 75
MXCommon__-
 GetModuleTemperatureValueAndStatus,
 80
MXCommon_GetModuleType, 75
MXCommon_GetOptionInformation, 91
MXCommon_GetStateIDFromName, 90
MXCommon_GetStateNameFromID, 91
MXCommon_GetSubsystemIDFromName,
 90
MXCommon_GetSubsystemNameFromID,
 90
MXCommon_GetSubSystemState, 89
MXCommon_GetSynchronizationStatus, 92
MXCommon_GetTime, 84
MXCommon_GetUpTime, 84
MXCommon_HardwareClockToSys, 84
MXCommon_InitAndStartSynchroTimer, 86
MXCommon_Reboot, 78
MXCommon_ResetAllIIOFunctionalties, 78
MXCommon_SetAutoConfigurationFile, 85
MXCommon_SetCustomerKey, 82
MXCommon__-
 SetHardwareTriggerFilterTime, 81
MXCommon_SetHostname, 76
MXCommon__-
 SetModuleTemperatureWarningLevels,
 80
MXCommon_SetTime, 83
MXCommon_SetToMaster, 91
MXCommon_StartAutoConfiguration, 86
MXCommon__-
 StopAndReleaseSynchroTimer, 87
MXCommon_Strerror, 76
MXCommon_SysToHardwareClock, 83
MXCommon_TestCustomerID, 83
xsd_char, 75
xsd_double, 75
xsd_float, 75
xsd_int, 75
xsd_long, 75
xsd_string, 75
xsd_unsignedByte, 75
xsd_unsignedInt, 75
xsd_unsignedLong, 75

xsd__unsignedShort, 75
MSXE302x_Sequence
 MSXE302x__-
 AnalogInputInitAndStartSequence,
 44
 MSXE302x__-
 AnalogInputStopAndReleaseSequence,
 46
MXCommon__ApplyConfigurationBackupFile
 Common_configuration, 30
 MSXE302x_public_doc.h, 88
MXCommon__ByteArrayResponse, 60
 sArray, 61
 sResponse, 61
MXCommon__ChangePassword
 Common_configuration, 30
 MSXE302x_public_doc.h, 89
MXCommon__DataserverRestart
 Common_general, 15
 MSXE302x_public_doc.h, 78
MXCommon__FileResponse, 61
 sArray, 61
 sResponse, 61
 ulEOF, 61
MXCommon__GetAutoConfigurationFile
 Common_autoconf, 26
 MSXE302x_public_doc.h, 85
MXCommon__GetAutoConfigurationFileResponse,
 61
 bArray, 62
 sResponse, 62
 ulEOF, 62
MXCommon__GetClientConnections
 Common_general, 13
 MSXE302x_public_doc.h, 76
MXCommon__GetConfigurationBackupFile
 Common_configuration, 29
 MSXE302x_public_doc.h, 87
MXCommon__GetEthernetLinksStates
 Common_general, 16
 MSXE302x_public_doc.h, 79
MXCommon__GetEthernetLinksStatesResponse,
 62
 sPort0, 62
 sPort1, 62
 sResponse, 62
MXCommon__GetHardwareTriggerFilterTime
 Common_hardware_trigger, 19
 MSXE302x_public_doc.h, 81
MXCommon__GetHardwareTriggerFilterTimeResponse,
 62
 sResponse, 63
 ulFilterTime, 63
 ulInfo01, 63
 ulInfo02, 63
MXCommon__GetHardwareTriggerState
 Common_hardware_trigger, 20
 MSXE302x_public_doc.h, 82
MXCommon__GetHardwareTriggerStateResponse,
 63
 sResponse, 63
 ulInfo01, 63
 ulInfo02, 63
 ulState, 63
MXCommon__GetHostname
 Common_general, 12
 MSXE302x_public_doc.h, 75
MXCommon__GetModuleTemperatureValueAndStatus
 Common_temperature, 17
 MSXE302x_public_doc.h, 80
MXCommon__GetModuleTemperatureValueAndStatusResponse,
 63
 dTemperatureValue, 64
 sResponse, 64
 ulInfo, 64
 ulTemperatureStatus, 64
MXCommon__GetModuleType
 Common_general, 12
 MSXE302x_public_doc.h, 75
MXCommon__GetOptionInformation
 CustomerOption, 34
 MSXE302x_public_doc.h, 91
MXCommon__GetStateIDFromName
 MSXE302x_public_doc.h, 90
 SystemStatemanagement, 33
MXCommon__GetStateNameFromID
 MSXE302x_public_doc.h, 91
 SystemStatemanagement, 33
MXCommon__GetSubsystemIDFromName
 MSXE302x_public_doc.h, 90
 SystemStatemanagement, 32
MXCommon__GetSubsystemNameFromID
 MSXE302x_public_doc.h, 90
 SystemStatemanagement, 33
MXCommon__GetSubSystemState
 MSXE302x_public_doc.h, 89
 SystemStatemanagement, 32
MXCommon__GetSynchronizationStatus
 MSXE302x_public_doc.h, 92
 Synchronisation, 35
MXCommon__GetTime
 Common_time, 24
 MSXE302x_public_doc.h, 84
MXCommon__GetTimeResponse, 64
 sResponse, 64
 ulHighTime, 64
 ulLowTime, 64
MXCommon__GetUpTime

Common_time, 24
 MSXE302x_public_doc.h, 84
MXCommon_GetUpTimeResponse, 64
 sResponse, 65
 ulUpTime, 65
MXCommon_HardwareClockToSys
 Common_time, 24
 MSXE302x_public_doc.h, 84
MXCommon_InitAndStartSynchroTimer
 Common_synchrotimer, 27
 MSXE302x_public_doc.h, 86
MXCommon_Reboot
 Common_general, 14
 MSXE302x_public_doc.h, 78
MXCommon_ResetAllIIOFunctionalities
 Common_general, 15
 MSXE302x_public_doc.h, 78
MXCommon_Response, 65
 iReturnValue, 65
 syserrno, 65
MXCommon_SetAutoConfigurationFile
 Common_autoconf, 26
 MSXE302x_public_doc.h, 85
MXCommon_SetCustomerKey
 Common_security, 21
 MSXE302x_public_doc.h, 82
MXCommon_SetHardwareTriggerFilterTime
 Common_hardware_trigger, 19
 MSXE302x_public_doc.h, 81
MXCommon_SetHostname
 Common_general, 12
 MSXE302x_public_doc.h, 76
MXCommon_SetModuleTemperatureWarningLevels
 Common_temperature, 18
 MSXE302x_public_doc.h, 80
MXCommon_SetTime
 Common_time, 23
 MSXE302x_public_doc.h, 83
MXCommon_SetToMaster
 MSXE302x_public_doc.h, 91
 Synchronisation, 35
MXCommon_StartAutoConfiguration
 Common_autoconf, 26
 MSXE302x_public_doc.h, 86
MXCommon_StopAndReleaseSynchroTimer
 Common_synchrotimer, 28
 MSXE302x_public_doc.h, 87
MXCommon_Strrorr
 Common_general, 13
 MSXE302x_public_doc.h, 76
MXCommon_SysToHardwareClock
 Common_time, 23
 MSXE302x_public_doc.h, 83
MXCommon_TestCustomerID
 Common_security, 22
 MSXE302x_public_doc.h, 83
MXCommon_TestCustomerIDResponse, 65
 bCryptedValueArray, 66
 bValueArray, 66
 sResponse, 66
MXCommon_unsignedLongResponse, 66
 sResponse, 66
 ulValue, 66
sAcquisition
 MSXE302x_-
 AnalogMeasureGetConfigurationResponse, 55
sArray
 MXCommon_ByteArrayResponse, 61
 MXCommon_FileResponse, 61
sAutoRefresh
 MSXE302x_-
 AnalogMeasureGetConfigurationResponse, 55
 Set/Backup/Restore general system configuration, 29
sGetEthernetLinksStatesPort, 66
 ulDuplex, 67
 ulInfo1, 67
 ulInfo2, 67
 ulSpeed, 67
 ulState, 67
sHardware
 MSXE302x_-
 AnalogMeasureGetConfigurationResponse, 57
 SOAP function calls in C/C++ language, 3
 Software hints, 3
sPort0
 MXCommon_-
 GetEthernetLinksStatesResponse, 62
sPort1
 MXCommon_-
 GetEthernetLinksStatesResponse, 62
sResponse
 MSXE302x_-
 AnalogInputGetAutoRefreshValuesResponse, 53
 MSXE302x_-
 AnalogInputGetChannelTypeResponse, 53
 MSXE302x_-
 CalibrationGetCurrentStatusResponse, 58
 MSXE302x_unsignedLongResponse, 60
 MXCommon_ByteArrayResponse, 61
 MXCommon_FileResponse, 61

MXCommon_-
 GetAutoConfigurationFileResponse,
 62

MXCommon_-
 GetEthernetLinksStatesResponse, 62

MXCommon_-
 GetHardwareTriggerFilterTimeResponse,
 63

MXCommon_-
 GetHardwareTriggerStateResponse,
 63

MXCommon_-
 GetModuleTemperatureValueAndStatusResponse
 64

MXCommon__GetTimeResponse, 64

MXCommon__GetUpTimeResponse, 65

MXCommon__TestCustomerIDResponse, 66

MXCommon__unsignedLongResponse, 66

sSequence
 MSXE302x_-
 AnalogMeasureGetConfigurationResponse,
 57

sSoftware
 MSXE302x_-
 AnalogMeasureGetConfigurationResponse,
 57

sSynchro
 MSXE302x_-
 AnalogMeasureGetConfigurationResponse,
 57

sTrigger
 MSXE302x_-
 AnalogMeasureGetConfigurationResponse,
 57

Synchronisation
 MXCommon__GetSynchronizationStatus, 35

MXCommon__SetToMaster, 35

Synchronisation management, 34

syserrno
 DefaultResponse, 52

MSXE302x__Response, 59

MXCommon__Response, 65

System state management, 31

SystemStatemanagement
 MXCommon__GetStateIDFromName, 33

MXCommon__GetStateNameFromID, 33

MXCommon__GetSubsystemIDFromName,
 32

MXCommon__GetSubsystemNameFromID,
 33

MXCommon__GetSubSystemState, 32

ulAction

MSXE302x_-
 AnalogMeasureGetConfigurationResponse,
 57

ulAverageMode
 MSXE302x_-
 AnalogMeasureGetConfigurationResponse,
 55

ulAverageValue
 MSXE302x_-
 AnalogMeasureGetConfigurationResponse,
 55

ulChannelInitialization
 MSXE302x_-
 AnalogMeasureGetConfigurationResponse,
 55

ulChannelMask
 MSXE302x_-
 AnalogMeasureGetConfigurationResponse,
 55

ulConvertTime
 MSXE302x_-
 AnalogMeasureGetConfigurationResponse,
 55

ulConvertTimeUnit
 MSXE302x_-
 AnalogMeasureGetConfigurationResponse,
 55

ulCount
 MSXE302x_-
 AnalogMeasureGetConfigurationResponse,
 57

ulCounterValue
 MSXE302x_-
 AnalogInputGetAutoRefreshValuesResponse,
 53

ulDateFormat
 MSXE302x_-
 AnalogMeasureGetConfigurationResponse,
 55

ulDelayFlag
 MSXE302x_-
 AnalogMeasureGetConfigurationResponse,
 56

ulDelayMode
 MSXE302x_-
 AnalogMeasureGetConfigurationResponse,
 57

ulDelayTime
 MSXE302x_-
 AnalogMeasureGetConfigurationResponse,
 57

ulDelayTimeUnit
 MSXE302x_-
 AnalogMeasureGetConfigurationResponse,

57
ulDuplex
 sGetEthernetLinksStatesPort, 67
ulEOF
 MXCommon__FileResponse, 61
 MXCommon__-
 GetAutoConfigurationFileResponse,
 62
ulError
 MSXE302x__-
 CalibrationGetCurrentStatusResponse,
 58
ulFilterTime
 MXCommon__-
 GetHardwareTriggerFilterTimeResponse,
 63
ulFlag
 MSXE302x__-
 AnalogMeasureGetConfigurationResponse,
 57
ulHighTime
 MXCommon__GetTimeResponse, 64
ulInfo
 MXCommon__-
 GetModuleTemperatureValueAndStatusResponse,
 64
ulInfo01
 MXCommon__-
 GetHardwareTriggerFilterTimeResponse,
 63
 MXCommon__-
 GetHardwareTriggerStateResponse,
 63
ulInfo02
 MXCommon__-
 GetHardwareTriggerFilterTimeResponse,
 63
 MXCommon__-
 GetHardwareTriggerStateResponse,
 63
ulInfo1
 sGetEthernetLinksStatesPort, 67
ulInfo2
 sGetEthernetLinksStatesPort, 67
ulLevel
 MSXE302x__-
 AnalogMeasureGetConfigurationResponse,
 57
ulLowTime
 MXCommon__GetTimeResponse, 64
ulNbrOfSequence
 MSXE302x__-
 AnalogMeasureGetConfigurationResponse,
 56
ulRunningMode
 MSXE302x__-
 AnalogMeasureGetConfigurationResponse,
 55
ulSequence
 MSXE302x__-
 AnalogMeasureGetConfigurationResponse,
 56
ulSequenceInterrupt
 MSXE302x__-
 AnalogMeasureGetConfigurationResponse,
 56
ulSequenceSize
 MSXE302x__-
 AnalogMeasureGetConfigurationResponse,
 56
ulSequenceTriggerCount
 MSXE302x__-
 AnalogMeasureGetConfigurationResponse,
 57
ulSpeed
 sGetEthernetLinksStatesPort, 67
ulState
 MXCommon__-
 GetHardwareTriggerStateResponse,
 63
 sGetEthernetLinksStatesPort, 67
ulStatus
 MSXE302x__-
 CalibrationGetCurrentStatusResponse,
 58
ulTemperatureStatus
 MXCommon__-
 GetModuleTemperatureValueAndStatusResponse,
 64
ulTimeStampHigh
 MSXE302x__-
 AnalogInputGetAutoRefreshValuesResponse,
 53
ulTimeStampLow
 MSXE302x__-
 AnalogInputGetAutoRefreshValuesResponse,
 53
ulType
 MSXE302x__-
 AnalogInputGetChannelTypeResponse,
 53
ulUpTime
 MXCommon__GetUpTimeResponse, 65
ulValue
 MSXE302x__-
 AnalogInputGetAutoRefreshValuesResponse,
 53

MSXE302x_-
 unsignedLong16FixedArrayParam,
 60
 MSXE302x_unsignedLongResponse, 60
 MXCommon_unsignedLongResponse, 66
UnsignedLongArray, 67
 __offset, 67
 __ptr, 67
 __size, 67
UnsignedShortArray, 67
 __offset, 68
 __ptr, 68
 __size, 68
xsd_base64Binary, 68
 __ptr, 68
 __size, 68
xsd_char
 MSXE302x_public_doc.h, 75
xsd_double
 MSXE302x_public_doc.h, 75
xsd_float
 MSXE302x_public_doc.h, 75
xsd_int
 MSXE302x_public_doc.h, 75
xsd_long
 MSXE302x_public_doc.h, 75
xsd_string
 MSXE302x_public_doc.h, 75
xsd_unsignedByte
 MSXE302x_public_doc.h, 75
xsd_unsignedInt
 MSXE302x_public_doc.h, 75
xsd_unsignedLong
 MSXE302x_public_doc.h, 75
xsd_unsignedShort
 MSXE302x_public_doc.h, 75