

MSXE321x soap api functions

Generated by Doxygen 1.7.1

Tue Nov 12 2013 14:51:52

Contents

1	Introduction	1
1.1	Introduction	1
1.2	Remark: SOAP functions prototypes	1
2	Module Documentation	3
2.1	MSX-E321x functions	3
2.2	Software hints	3
2.3	SOAP function calls in C/C++ language	3
2.3.1	C/C++ language SOAP function prototypes	4
2.3.2	Rules and use of gSOAP calls in C/C++	4
2.3.3	SOAP calls sample	6
2.4	MSX-E systems servers	10
2.4.1	SOAP server	10
2.4.2	Event server	10
2.4.3	Modbus server	10
2.4.4	Data server	11
2.5	Temperature diagnostic	11
2.6	Common functions	11
2.7	Common general functions	12
2.7.1	Function Documentation	13
2.7.1.1	MXCommon__GetModuleType	13
2.7.1.2	MXCommon__GetHostname	13
2.7.1.3	MXCommon__SetHostname	13
2.7.1.4	MXCommon__GetClientConnections	14
2.7.1.5	MXCommon__Sterror	14
2.7.1.6	MXCommon__Reboot	15
2.7.1.7	MXCommon__ResetAllIIOFunctionalities	16
2.7.1.8	MXCommon__DataserverRestart	16

2.7.1.9	MXCommon__GetEthernetLinksStates	17
2.8	Common temperature functions	17
2.8.1	Detailed Description	18
2.8.2	Function Documentation	18
2.8.2.1	MXCommon__GetModuleTemperatureValueAndStatus	18
2.8.2.2	MXCommon__SetModuleTemperatureWarningLevels	19
2.9	Common hardware trigger functions	19
2.9.1	Function Documentation	20
2.9.1.1	MXCommon__SetHardwareTriggerFilterTime	20
2.9.1.2	MXCommon__GetHardwareTriggerFilterTime	20
2.9.1.3	MXCommon__GetHardwareTriggerState	21
2.10	Common security functions	21
2.10.1	Detailed Description	22
2.10.2	Function Documentation	22
2.10.2.1	MXCommon__SetCustomerKey	22
2.10.2.2	MXCommon__TestCustomerID	23
2.11	Common time functions	23
2.11.1	Detailed Description	24
2.11.2	Function Documentation	24
2.11.2.1	MXCommon__SetTime	24
2.11.2.2	MXCommon__SysToHardwareClock	24
2.11.2.3	MXCommon__HardwareClockToSys	25
2.11.2.4	MXCommon__GetTime	25
2.11.2.5	MXCommon__GetUpTime	26
2.12	Common I/O auto configuration functions	26
2.12.1	Detailed Description	26
2.12.2	Function Documentation	27
2.12.2.1	MXCommon__GetAutoConfigurationFile	27
2.12.2.2	MXCommon__SetAutoConfigurationFile	27
2.12.2.3	MXCommon__StartAutoConfiguration	28
2.13	Common synchronisation timer functions	28
2.13.1	Function Documentation	28
2.13.1.1	MXCommon__InitAndStartSynchroTimer	28
2.13.1.2	MXCommon__StopAndReleaseSynchroTimer	29
2.14	Set/Backup/Restore general system configuration	30
2.14.1	Detailed Description	30

2.14.2	Function Documentation	30
2.14.2.1	MXCommon__GetConfigurationBackupFile	30
2.14.2.2	MXCommon__ApplyConfigurationBackupFile	31
2.14.2.3	MXCommon__ChangePassword	31
2.15	System state management	32
2.15.1	Detailed Description	33
2.15.2	Function Documentation	33
2.15.2.1	MXCommon__GetSubSystemState	33
2.15.2.2	MXCommon__GetSubsystemIDFromName	33
2.15.2.3	MXCommon__GetStateIDFromName	34
2.15.2.4	MXCommon__GetSubsystemNameFromID	34
2.15.2.5	MXCommon__GetStateNameFromID	34
2.16	Customer option management	35
2.16.1	Function Documentation	35
2.16.1.1	MXCommon__GetOptionInformation	35
2.17	Synchronisation management	35
2.17.1	Function Documentation	36
2.17.1.1	MXCommon__SetToMaster	36
2.17.1.2	MXCommon__GetSynchronizationStatus	36
2.18	MSX-E321x Acquisition functions	37
2.19	MSX-E321x Acquisition information functions	37
2.19.1	Function Documentation	38
2.19.1.1	MSXExxxx__AcquisitionGetNumberOfChannels	38
2.19.1.2	MSXExxxx__AcquisitionGetChannelInfo	38
2.20	MSX-E321x Autorefresh functions	39
2.20.1	Detailed Description	39
2.20.2	Function Documentation	40
2.20.2.1	MSXExxxx__AcquisitionAutoRefreshInitAndStart	40
2.20.2.2	MSXExxxx__AcquisitionAutoRefreshGetValues	42
2.20.2.3	MSXExxxx__AcquisitionAutoRefreshStopAndRelease	43
2.21	MSX-E321x Sequence functions	43
2.21.1	Detailed Description	44
2.21.2	Function Documentation	44
2.21.2.1	MSXExxxx__AcquisitionSequenceInitAndStart	44
2.21.2.2	MSXExxxx__AcquisitionSequenceStopAndRelease	47
2.22	MSX-E321x Temperature functions	47

2.23	MSX-E321x Temperature initialisation/information functions	47
2.23.1	Function Documentation	48
2.23.1.1	MSXExxxx__TemperatureGetNumberOfChannels	48
2.23.1.2	MSXExxxx__TemperatureGetChannelSensorClass	48
2.23.1.3	MSXExxxx__TemperatureSetChannelType	49
2.23.1.4	MSXExxxx__TemperatureSetSamplingRate	50
2.23.1.5	MSXExxxx__TemperatureGetConfiguration	51
2.24	MSX-E321x Temperature diagnostic functions	52
2.24.1	Function Documentation	52
2.24.1.1	MSXExxxx__TemperatureDiagnostic	52
3	Data Structure Documentation	55
3.1	ByteArray Struct Reference	55
3.1.1	Field Documentation	55
3.1.1.1	__ptr	55
3.1.1.2	__size	55
3.1.1.3	__offset	55
3.2	DefaultResponse Struct Reference	55
3.2.1	Field Documentation	56
3.2.1.1	iReturnValue	56
3.2.1.2	syserrno	56
3.3	MSXExxxx__AcquisitionAutoRefreshGetValuesResponse Struct Reference	56
3.3.1	Field Documentation	57
3.3.1.1	sResponse	57
3.3.1.2	ulTimeStampLow	57
3.3.1.3	ulTimeStampHigh	57
3.3.1.4	ulCounterValue	57
3.3.1.5	dValue	57
3.4	MSXExxxx__AcquisitionGetChannelInfoResponse Struct Reference	57
3.4.1	Field Documentation	57
3.4.1.1	sResponse	57
3.4.1.2	ulType	57
3.4.1.3	ulHwPosition	58
3.4.1.4	ulChannelIndex	58
3.5	MSXExxxx__AcquisitionSequenceInitAndStartChannelListParam Struct Reference	58
3.5.1	Field Documentation	58
3.5.1.1	ulChannelList	58

3.6	MSXExxxx__FileResponse Struct Reference	58
3.6.1	Field Documentation	59
3.6.1.1	sResponse	59
3.6.1.2	sArray	59
3.6.1.3	ulEOF	59
3.7	MSXExxxx__Response Struct Reference	59
3.7.1	Field Documentation	59
3.7.1.1	iReturnValue	59
3.7.1.2	syserrno	59
3.8	MSXExxxx__TemperatureGetChannelSensorClassResponse Struct Reference	59
3.8.1	Field Documentation	60
3.8.1.1	sResponse	60
3.8.1.2	ulType	60
3.9	MSXExxxx__TemperatureGetConfigurationResponse Struct Reference	60
3.9.1	Field Documentation	60
3.9.1.1	sResponse	60
3.9.1.2	ulClass	60
3.9.1.3	ulType	60
3.9.1.4	ulBaseSamplingRate	60
3.10	MSXExxxx__unsignedLongResponse Struct Reference	60
3.10.1	Field Documentation	61
3.10.1.1	sResponse	61
3.10.1.2	ulValue	61
3.11	MSXExxxx__unsignedLongTimeStampResponse Struct Reference	61
3.11.1	Field Documentation	61
3.11.1.1	sResponse	61
3.11.1.2	ulValue	61
3.11.1.3	ulTimeStampLow	61
3.11.1.4	ulTimeStampHigh	61
3.12	MXCommon__ByteArrayResponse Struct Reference	61
3.12.1	Field Documentation	62
3.12.1.1	sResponse	62
3.12.1.2	sArray	62
3.13	MXCommon__FileResponse Struct Reference	62
3.13.1	Field Documentation	62
3.13.1.1	sResponse	62

3.13.1.2	sArray	62
3.13.1.3	ulEOF	62
3.14	MXCommon__GetAutoConfigurationFileResponse Struct Reference	62
3.14.1	Field Documentation	63
3.14.1.1	sResponse	63
3.14.1.2	bArray	63
3.14.1.3	ulEOF	63
3.15	MXCommon__GetEthernetLinksStatesResponse Struct Reference	63
3.15.1	Field Documentation	63
3.15.1.1	sResponse	63
3.15.1.2	sPort0	63
3.15.1.3	sPort1	63
3.16	MXCommon__GetHardwareTriggerFilterTimeResponse Struct Reference	63
3.16.1	Field Documentation	64
3.16.1.1	sResponse	64
3.16.1.2	ulFilterTime	64
3.16.1.3	ulInfo01	64
3.16.1.4	ulInfo02	64
3.17	MXCommon__GetHardwareTriggerStateResponse Struct Reference	64
3.17.1	Field Documentation	64
3.17.1.1	sResponse	64
3.17.1.2	ulState	64
3.17.1.3	ulInfo01	64
3.17.1.4	ulInfo02	64
3.18	MXCommon__GetModuleTemperatureValueAndStatusResponse Struct Reference	64
3.18.1	Field Documentation	65
3.18.1.1	sResponse	65
3.18.1.2	dTemperatureValue	65
3.18.1.3	ulTemperatureStatus	65
3.18.1.4	ulInfo	65
3.19	MXCommon__GetTimeResponse Struct Reference	65
3.19.1	Field Documentation	65
3.19.1.1	sResponse	65
3.19.1.2	ulLowTime	65
3.19.1.3	ulHighTime	65
3.20	MXCommon__GetUpTimeResponse Struct Reference	65

3.20.1	Field Documentation	66
3.20.1.1	sResponse	66
3.20.1.2	ulUpTime	66
3.21	MXCommon__Response Struct Reference	66
3.21.1	Field Documentation	66
3.21.1.1	iReturnValue	66
3.21.1.2	syserrno	66
3.22	MXCommon__TestCustomerIDResponse Struct Reference	66
3.22.1	Field Documentation	67
3.22.1.1	sResponse	67
3.22.1.2	bValueArray	67
3.22.1.3	bCryptedValueArray	67
3.23	MXCommon__unsignedLongResponse Struct Reference	67
3.23.1	Field Documentation	67
3.23.1.1	sResponse	67
3.23.1.2	ulValue	67
3.24	sGetEthernetLinksStatesPort Struct Reference	67
3.24.1	Field Documentation	68
3.24.1.1	ulState	68
3.24.1.2	ulSpeed	68
3.24.1.3	ulDuplex	68
3.24.1.4	ulInfo1	68
3.24.1.5	ulInfo2	68
3.25	UnsignedLongArray Struct Reference	68
3.25.1	Field Documentation	68
3.25.1.1	__ptr	68
3.25.1.2	__size	68
3.25.1.3	__offset	68
3.26	UnsignedShortArray Struct Reference	68
3.26.1	Field Documentation	69
3.26.1.1	__ptr	69
3.26.1.2	__size	69
3.26.1.3	__offset	69
3.27	xsd__base64Binary Struct Reference	69
3.27.1	Field Documentation	69
3.27.1.1	__ptr	69

3.27.1.2	<code>__size</code>	69
4	File Documentation	71
4.1	MSXE321x_public_doc.h File Reference	71
4.1.1	Typedef Documentation	77
4.1.1.1	<code>xsd_string</code>	77
4.1.1.2	<code>xsd_char</code>	77
4.1.1.3	<code>xsd_float</code>	77
4.1.1.4	<code>xsd_double</code>	77
4.1.1.5	<code>xsd_int</code>	77
4.1.1.6	<code>xsd_long</code>	77
4.1.1.7	<code>xsd_unsignedByte</code>	77
4.1.1.8	<code>xsd_unsignedInt</code>	77
4.1.1.9	<code>xsd_unsignedShort</code>	77
4.1.1.10	<code>xsd_unsignedLong</code>	77
4.1.2	Function Documentation	77
4.1.2.1	<code>MXCommon__GetModuleType</code>	77
4.1.2.2	<code>MXCommon__GetHostname</code>	78
4.1.2.3	<code>MXCommon__SetHostname</code>	78
4.1.2.4	<code>MXCommon__GetClientConnections</code>	78
4.1.2.5	<code>MXCommon__Strerror</code>	79
4.1.2.6	<code>MXCommon__Reboot</code>	80
4.1.2.7	<code>MXCommon__ResetAllIOFunctionalities</code>	80
4.1.2.8	<code>MXCommon__DataseverRestart</code>	81
4.1.2.9	<code>MXCommon__GetEthernetLinksStates</code>	81
4.1.2.10	<code>MXCommon__GetModuleTemperatureValueAndStatus</code>	82
4.1.2.11	<code>MXCommon__SetModuleTemperatureWarningLevels</code>	83
4.1.2.12	<code>MXCommon__SetHardwareTriggerFilterTime</code>	83
4.1.2.13	<code>MXCommon__GetHardwareTriggerFilterTime</code>	84
4.1.2.14	<code>MXCommon__GetHardwareTriggerState</code>	84
4.1.2.15	<code>MXCommon__SetCustomerKey</code>	85
4.1.2.16	<code>MXCommon__TestCustomerID</code>	85
4.1.2.17	<code>MXCommon__SetTime</code>	85
4.1.2.18	<code>MXCommon__SysToHardwareClock</code>	86
4.1.2.19	<code>MXCommon__HardwareClockToSys</code>	86
4.1.2.20	<code>MXCommon__GetTime</code>	87
4.1.2.21	<code>MXCommon__GetUpTime</code>	87

4.1.2.22	MXCommon__GetAutoConfigurationFile	87
4.1.2.23	MXCommon__SetAutoConfigurationFile	88
4.1.2.24	MXCommon__StartAutoConfiguration	88
4.1.2.25	MXCommon__InitAndStartSynchroTimer	88
4.1.2.26	MXCommon__StopAndReleaseSynchroTimer	89
4.1.2.27	MXCommon__GetConfigurationBackupFile	90
4.1.2.28	MXCommon__ApplyConfigurationBackupFile	91
4.1.2.29	MXCommon__ChangePassword	91
4.1.2.30	MXCommon__GetSubSystemState	92
4.1.2.31	MXCommon__GetSubsystemIDFromName	92
4.1.2.32	MXCommon__GetStateIDFromName	92
4.1.2.33	MXCommon__GetSubsystemNameFromID	93
4.1.2.34	MXCommon__GetStateNameFromID	93
4.1.2.35	MXCommon__GetOptionInformation	94
4.1.2.36	MXCommon__SetToMaster	94
4.1.2.37	MXCommon__GetSynchronizationStatus	94
4.1.2.38	MSXExxxx__AcquisitionGetNumberOfChannels	95
4.1.2.39	MSXExxxx__AcquisitionGetChannelInfo	95
4.1.2.40	MSXExxxx__AcquisitionAutoRefreshInitAndStart	96
4.1.2.41	MSXExxxx__AcquisitionAutoRefreshGetValues	98
4.1.2.42	MSXExxxx__AcquisitionAutoRefreshStopAndRelease	99
4.1.2.43	MSXExxxx__AcquisitionSequenceInitAndStart	99
4.1.2.44	MSXExxxx__AcquisitionSequenceStopAndRelease	102
4.1.2.45	MSXExxxx__TemperatureGetNumberOfChannels	102
4.1.2.46	MSXExxxx__TemperatureGetChannelSensorClass	102
4.1.2.47	MSXExxxx__TemperatureSetChannelType	103
4.1.2.48	MSXExxxx__TemperatureSetSamplingRate	104
4.1.2.49	MSXExxxx__TemperatureGetConfiguration	105
4.1.2.50	MSXExxxx__TemperatureDiagnostic	106

Chapter 1

Introduction

MainRevision:

1.1 Introduction

This documentation describes the SOAP functions and gives software hints to work with the MSX-E systems. Following documentations can be found under **Modules**.

SOAP means Simple Object Access Protocol. This protocol enables to use the MSX-E software functions over Ethernet. It is providing **Web Services** that can easily be consumed in many programming languages like C, C++, C#, VB.Net... With the SOAP functions, all functionalities of the MSX-E system can be managed / configured / monitored.

1.2 Remark: SOAP functions prototypes

In some programming languages, SOAP functions names and parameters could be different as those described in this documentation. Please see to [Software hints](#)

Chapter 2

Module Documentation

2.1 MSX-E321x functions

Modules

- [MSX-E321x Acquisition functions](#)
Contain the acquisition information and initialisation functions.
- [MSX-E321x Temperature functions](#)
Contain the temperature initialisation and diagnostic functions.

2.2 Software hints

Modules

- [SOAP function calls in C/C++ language](#)
Some hints on how to use the SOAP functions in a C/C++ program.
- [MSX-E systems servers](#)
The MSX-E embeds servers to provide configuration, management and monitoring over Ethernet.
- [Temperature diagnostic](#)
The MSX-E is continuously checking, on each channel, the sensor connection state to detect short-circuits and open-lines.

2.3 SOAP function calls in C/C++ language

Some hints on how to use the SOAP functions in a C/C++ program.

2.3.1 C/C++ language SOAP function prototypes

In this documentation, functions are described as follows.

```
int MXCommon__GetModuleType(void * __, struct MXCommon__ByteArrayResponse
* Response);
```

Two main differences can be remarked in the function prototypes:

- The prefix:

```
soap_call__
```

- The first three parameters of the SOAP stub:

```
struct soap *soap
const char *soap_endpoint
const char *soap_action
```

The C function prototype has the following syntax:

```
int soap_call_MXCommon__GetModuleType(struct soap *soap, const char *soap_endpoin
t, const char *soap_action, void __, struct MXCommon__ByteArrayResponse *Response
);
```

Functions to call in C/C++ are called **stubs** and can be found in the **MSXEXXXXStub.h** file.

2.3.2 Rules and use of gSOAP calls in C/C++

When programming with gSOAP in C/C++ language, some rules have to be followed to avoid memory leaks, slow socket disconnections and multi-threading compliancy.

Note: Software code pieces in this chapter comes from [SOAP calls sample](#)

- **Opening and initializing an SOAP connection (using the gSOAP functions)**

```
struct soap *soapContext;

// IP address of the MSX-E and after the ':' is the MSX-E SOAP server port number

char soap_endpoint[] = IP_ADDRESS":5555";

// Allocates and initialize a new runtime context
if ((soapContext = soap_new ()) == NULL)
    return EXIT_FAILURE;

// Initializes the SOAP context with options
soap_init2 (soapContext, SOAP_IO_KEEPAIVE, SOAP_IO_KEEPAIVE);

// Sets timeouts in seconds
soapContext->send_timeout = 1;
soapContext->recv_timeout = 1;
soapContext->accept_timeout = 1;
```

Remark: A new runtime context is required in each new thread!

• Calling the MSX-E SOAP functions

Important

- In C/C++, each MSX-E SOAP function call is allocating memory (to manage deserialized data) and is not deallocating it automatically. The allocated memory has to be deallocated explicitly by calling, in this order, the `soap_destroy` and `soap_end` functions. These functions can be called after each MSX-E SOAP function call or after several calls. It is important to call these functions regularly to prevent memory leaks.
- If the SOAP function is returning pointer, call the `soap_destroy` and `soap_end` functions only after working with the pointers. If `soap_destroy` and `soap_end` are called before working with the pointers, the values pointed by the pointer will not be available. All dynamically allocated values are destroyed by `soap_destroy` and `soap_end`.

See [C/C++ language SOAP function prototypes](#) to call the MSX-E SOAP functions.

```
for ( ; ; )
{
    soap_error = soap_call_MXCommon__GetModuleTemperatureValueAndStatus (soapContext,
    soap_endpoint, NULL, option, &tempResponse);

    ...

    // As gSOAP doesn't released automatically the memory that it allocates t
o
    // deserialize SOAP data we have to released it explicitly.
    // There is no need to call the function in each loop cycle,
    // it depends on the application, and desired performance and
    // available memory.
    soap_destroy (soapContext);
    soap_end (soapContext);

    ...
}
```

• Error management

There are 3 types of errors that can be generated by the MSX-E SOAP functions:

- SOAP errors: It is the SOAP function return value. More details about the error can be obtained by using the `soap_faultstring` function.

```
soap_error = soap_call_MXCommon__GetModuleTemperatureValueAndStatus (soapContext,
    soap_endpoint, NULL, option, &tempResponse);

if (soap_error)
    printf ("message: %s\n", *soap_faultstring (soapContext));
```

Remark: `soap_faultstring` has to be called just after the SOAP function call that generates the SOAP error and before the call of `soap_destroy` and `soap_end`.

- The MSX-E error (`iReturnValue`): Returns errors that are not linux specific. The `iReturnValue` variable is located in the response structure. These errors are described in this documentation.

```
soap_error = soap_call_MXCommon__GetModuleTemperatureValueAndStatus (soapContext,
    soap_endpoint, NULL, option, &tempResponse);

// Check for errors, if there are, stop the loop
if (checkErrors (soapContext, soap_endpoint, NULL, soap_error, tempResponse.sResponse.iReturnValue, tempResponse.sResponse.syserrno))
    break;
```

- The MSX-E system error (syserrno): Returns linux specific errors. This variable has to be checked only if iReturnValue = -1 or iReturnValue <= -100. It returns the linux errno error. More details about the error can be obtained by using the soap_call_MXCommon__Strerror function.

```
struct MXCommon__ByteArrayResponse byteArrayResponse;

memset (&byteArrayResponse, 0, sizeof (struct MXCommon__ByteArrayResponse));

soap_error = soap_call_MXCommon__GetModuleTemperatureValueAndStatus (soapContext,
    soap_endpoint, NULL, option, &tempResponse);

if ((tempResponse.sResponse.iReturnValue == -1) || ((tempResponse.sResponse.iRetu
    rnValue <= -100) && tempResponse.sResponse.syserrno))
{
    soap_call_MXCommon__Strerror (soapContext, soap_endpoint, soap_action, te
    mpResponse.sResponse.syserrno, &byteArrayResponse);

    // Display the system error
    printf ("\nSystem error: %s\n", byteArrayResponse.sArray.__ptr);
}
```

- **Close the SOAP connection**

Before to quit the application or when no MSX-E SOAP function calls are necessary, the SOAP connection has to be closed and the context has to be released. Call following functions in this order: soap_destroy, soap_end, soap_free.

```
// Release SOAP
soap_destroy (soapContext);
soap_end (soapContext);

// Close the socket an release the SOAP context
soap_free (soapContext);
```

2.3.3 SOAP calls sample

Here a sample code, and it's makefile, to read the MSX-E internal temperature.

To compile it, use *make IP_ADDRESS=YOUR_MSX-E_IP_ADDRESS* don't forget to set the **INTERFACE_COMMON_LIBRARY_DIR** to point on the MSX-E Common Interface_Library directory.

Remark: Don't use blank spaces in the directories and file names.

temperature.c file

```
#include <unistd.h>
#include <stdio.h>
#include <stdbool.h>
#include <string.h>
#include <errno.h>
#include <MXCommon.nsmap> // this file must be included only once in the project
#include <assert.h>
#include <sys/stat.h>
#include <termios.h>

//-----
//-----

/** kbhit for linux.
```

```

@retval 0: No key pressed.
@retval <>0: Key pressed.
*/
int kbhit (void)
{
    struct termios oldt, newt;
    struct timeval tv;
    fd_set read_fd;
    int status;

    tcgetattr (STDIN_FILENO, &oldt);
    memcpy (&newt, &oldt, sizeof (newt));
    newt.c_lflag &= ~(ICANON | ECHO);
    tcsetattr (STDIN_FILENO, TCSANOW, &newt);

    tv.tv_sec = 0;
    tv.tv_usec = 0;
    FD_ZERO (&read_fd);
    FD_SET (0, &read_fd);

    status = select (1, &read_fd, NULL, NULL, &tv);
    tcsetattr (STDIN_FILENO, TCSANOW, &oldt);

    if (status < 0)
        return 0;
    else
        return (status);
}

//-----

/** getch for linux.

@retval key: Key number.
*/
int getch (void)
{
    struct termios oldt, newt;
    int ch;

    tcgetattr (STDIN_FILENO, &oldt);
    memcpy (&newt, &oldt, sizeof (newt));
    newt.c_lflag &= ~(ICANON | ECHO);
    tcsetattr (STDIN_FILENO, TCSANOW, &newt);
    ch = getchar();
    tcsetattr (STDIN_FILENO, TCSANOW, &oldt);

    return (ch);
}

//-----
//-----

/** Check if the SOAP call returns an error, display it.

@param[in] soapContext : SOAP context structure.
@param[in] soap_endpoint : IP and port number of the system to access.
@param[in] soap_action : SOAP action required by the Web service.
@param[in] soap_error: The SOAP function return value.
@param[in] msxe_error: The MSX-E system return value contained in the response s
    tructure (iReturnValue).
@param[in] msxe_syserro: The MSX-E system errno value contained in the response
    structure (syserro).

```

```

@retval 0: No error.
@retval 1: Error.
*/
int checkErrors (struct soap *soapContext, const char *soap_endpoint, const char
                *soap_action, int soap_error, int msxe_error, int msxe_syserrno)
{
    if ((soap_error != 0) || (msxe_error != 0))
    {
        printf ("MSX-E function response error: %d\n", msxe_error);
        printf ("soap error: %d ", soap_error);

        // In case of an SOAP error, display it
        if (soap_error)
            printf ("message: %s\n", *soap_faultstring (soapContext))
;
        else
        {
            // It's not an SOAP error but a system error
            if ((msxe_error == -1) || ((msxe_error <= -100) && msxe_s
yserrno))
            {
                struct MXCommon__ByteArrayResponse byteArrayRespo
nse;
                memset (&byteArrayResponse, 0, sizeof (struct
MXCommon__ByteArrayResponse));

                // Get the system error
                if (soap_call_MXCommon__Strerror (soapContext, so
ap_endpoint, soap_action, msxe_syserrno, &byteArrayResponse))
                    printf ("\nsoap_call_MXCommon__Strerror e
rror: %s\n", *soap_faultstring (soapContext));
                else // Display the system error
                    printf ("\nSystem error: %s\n", byteArray
Response.sArray.__ptr);
            }
        }

        return 1;
    }

    return 0;
}

//-----
//-----

int main (void)
{
    struct soap *soapContext;
    unsigned long option = 0;
    struct MXCommon__GetModuleTemperatureValueAndStatusResponse tempResponse
;
    int soap_error = 0;
    char *tempStatus[] = {"NOT AVAILABLE", "TOO LOW", "LOW", "NOMINAL", "HIG
H", "TOO HIGH"};
    // IP address of the MSX-E and after the ':' is the MSX-E SOAP server po
rt number
    char soap_endpoint[] = IP_ADDRESS":5555";

    memset (&tempResponse, 0, sizeof (struct
MXCommon__GetModuleTemperatureValueAndStatusResponse));

    // Allocates and initialize a new runtime context
    if ((soapContext = soap_new ()) == NULL)

```

```

        return EXIT_FAILURE;

    // Initializes the SOAP context with options
    soap_init2 (soapContext, SOAP_IO_KEEPAIVE, SOAP_IO_KEEPAIVE);

    // Sets timeouts in seconds
    soapContext->send_timeout = 1;
    soapContext->recv_timeout = 1;
    soapContext->accept_timeout = 1;

    for ( ; ; )
    {
        soap_error = soap_call_MXCommon__GetModuleTemperatureValueAndSta
tus (soapContext, soap_endpoint, NULL, option, &tempResponse);

        // Check for errors, if there are, stop the loop
        if (checkErrors (soapContext, soap_endpoint, NULL, soap_error, t
empResponse.sResponse.iReturnValue, tempResponse.sResponse.syserrno))
            break;

        // There is no error
        printf ("MSX-E Temperature: %.2lf °C status: ", tempResponse.dTem
peratureValue);

        if (tempResponse.ulTemperatureStatus < 6)
            printf ("%s ", tempStatus[tempResponse.ulTemperatureStatu
s]);
        else
            printf ("unknown ");

        printf ("\n");

        // As gSOAP doesn't released automatically the memory that it al
locates to
        // deserialize SOAP data we have to released it explicitly.
        // There is no need to call the function in each loop cycle,
        // it depends on the application, and desired performance and
        // available memory.
        soap_destroy (soapContext);
        soap_end (soapContext);

        // Listen on keyboard actions
        if (kbhit ())
            if (getch () == 27) // Check if ESC key has been used
                break;
    }

    // Release SOAP
    soap_destroy (soapContext);
    soap_end (soapContext);
    // Close the socket an release the SOAP context
    soap_free (soapContext);

    return EXIT_SUCCESS;
}

```

Makefile

```

TOPDIR                                :=$(shell pwd)

CC                                    :=$(CROSS)$(CC)
LD                                    :=$(CROSS)ld
STRIP                                 :=$(CROSS)strip

ifneq ($(INTERFACE_COMMON_LIBRARY_DIR), "")
INTERFACE_COMMON_LIBRARY_DIR         :=$(TOPDIR)/../../Interface_Library
endif

```

```

# The MSX-E IP address
ifneq ($(IP_ADDRESS), "")
IP_ADDRESS                                =192.168.99.99
endif

# File implementing SOAP client
SOAPSOURCES                             := $(INTERFACE_COMMON_LIBRARY_DIR)/MSXEclient.o $
      (INTERFACE_COMMON_LIBRARY_DIR)/MSXEC.o $(INTERFACE_COMMON_LIBRARY_DIR)/stdsoap2.o

CFLAGS                                  += -pipe -Wall -O0 -Winline -I$(INTERFACE_COMMON_
      LIBRARY_DIR) -DIP_ADDRESS="\$(IP_ADDRESS)\\"

TEMPERATURE_SRC                         := temperature.o
BINS                                    := temperature

all: $(BINS)

temperature: $(SOAPSOURCES) $(TEMPERATURE_SRC)
      $(CC) $(CFLAGS) -o $@ $^
      $(STRIP) $@

clean:
      -rm -f $(BINS)
      -rm -f $(INTERFACE_COMMON_LIBRARY_DIR)/*.o
      -rm -f *.o

```

2.4 MSX-E systems servers

The MSX-E embeds servers to provide configuration, management and monitoring over Ethernet.

2.4.1 SOAP server

SOAP means Simple Object Access Protocol. This protocol allows you to use the MSX-E software functions over Ethernet. It is providing **Web Services** that can easily be consumed in many programming languages like C, C++, C#, VB.Net... With the SOAP functions, all functionalities of the MSX-E system can be managed / configured / monitored. This server can be accessed on port 5555. All SOAP functions are described under Modules -> MSX-EXXXX functions.

2.4.2 Event server

MSX-E systems embed an event server that can be used to monitor the current MSX-E state. An MSX-E system is logically divided in subsystem states. A subsystem is uniquely identified by a number, as well as each possible state associated to it. These numerical identifiers can be monitored by using the event server, which signals when the state of a subsystem has changed. The MSX-E will send a new event frame as soon as a subsystem state changes on the MSX-E.

2.4.3 Modbus server

A Modbus server, accessible on port 512 permits, for example, to manage MSX-E systems from a PLC. The port number, endianness (Intel / Motorola) and protocol (TCP/UDP) can be configured through the MSX-E web interface.

2.4.4 Data server

The MSX-E321x embeds a **data server** that can be used to read acquired values. The default port number is set on 8989 and can be changed by using the **Data server** MSX-E Web interface.

2.5 Temperature diagnostic

The MSX-E is continuously checking, on each channel, the sensor connection state to detect short-circuits and open-lines.

In case of short-circuit or open-line, the temperature corresponding to the failing channel is set to -2000.0 °C to indicate an error on the channel. In order to get the cause of the error, call the TemperatureDiagnostics function.

2.6 Common functions

Modules

- [Common general functions](#)

Various utility functions, mainly to identify a remote system.

- [Common temperature functions](#)

These functions deals with the internal temperature sub-system.

- [Common hardware trigger functions](#)

These functions allow to set and request the current value of the hardware trigger.

- [Common security functions](#)

The "customer key" feature may for instance be used by a customer to be sure that his application communicates only with certified MSX-E modules.

- [Common time functions](#)

A MSX-E module provides a "system clock" that may be in the simplest case set by the function [MXCommon_SetTime\(\)](#).

- [Common I/O auto configuration functions](#)

On the web site of some MSX-E module, there is the possibility to define an auto-configuration and auto start of the I/O.

- [Common synchronisation timer functions](#)

When modules are linked through a "synchronisation bus", the master can run a timer that generate a "synchro signal" on the slaves when overrun.

- [Set/Backup/Restore general system configuration](#)

Distinct of the I/O auto-configuration/auto-start functionality, these functions allows to manipulate the general system configuration.

- [System state management](#)

Every MSX-E modules are composed of several sub-systems that work together to provide the system functionalities.

- [Customer option management](#)

Enable to get informations about the options of the system.

- [Synchronisation management](#)

Manage the synchronisation state of the system.

2.7 Common general functions

Various utility functions, mainly to identify a remote system.

Functions

- `int MXCommon__GetModuleType (void *__, struct MXCommon__ByteArrayResponse *Response)`

This function return the type of the MSX-E Module.

- `int MXCommon__GetHostname (void *__, struct MXCommon__ByteArrayResponse *Response)`

This function return the hostname of the MSX-E Module.

- `int MXCommon__SetHostname (struct xsd__base64Binary *bHostname, struct MXCommon__Response *Response)`

This function allows to set the hostname of the MSX-E Module.

- `int MXCommon__GetClientConnections (void *__, struct MXCommon__ByteArrayResponse *Response)`

This function return the client connection list.

- `int MXCommon__Strerror (xsd__int ernum, struct MXCommon__ByteArrayResponse *Response)`

Call the libc strerror() on the remote device (actually this is a call to strerror_r()).

- `int MXCommon__Reboot (void *__, struct MXCommon__Response *Response)`

Ask the MSX-E module to reboot.

- `int MXCommon__ResetAllIOFunctionalities (xsd__unsignedLong ulOption, struct MXCommon__Response *Response)`

Reset the I/O functionalities of the MSX-E system.

- `int MXCommon__DataseverRestart (xsd__unsignedLong ulAction, xsd__unsignedLong ulOption, struct MXCommon__Response *Response)`

Restart the data-server service.

- `int MXCommon__GetEthernetLinksStates (void *__, struct MXCommon__GetEthernetLinksStatesResponse *Response)`

Get MSX-E Ethernet links states.

2.7.1 Function Documentation

2.7.1.1 `int MXCommon__GetModuleType (void * _, struct MXCommon__ByteArrayResponse * Response)`

Parameters

- [in] `_` : no input parameter
- [out] **Response** • `sArray` : Module type string
- `sResponse` Composed of `iReturnValue` and `syserrno`

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

2.7.1.2 `int MXCommon__GetHostname (void * _, struct MXCommon__ByteArrayResponse * Response)`

Parameters

- [in] `_` : no input parameter
- [out] **Response** • `sArray` : Hostname of the module
- `iReturnValue` : Return value
 - 0 : success
 - -1: system error (see `syserrno`)
 - `syserrno` : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

2.7.1.3 `int MXCommon__SetHostname (struct xsd__base64Binary * bHostname, struct MXCommon__Response * Response)`

Parameters

- [in] **bHostname** : Hostname
- [out] **Response** • `iReturnValue` : Return value
- 0 : success
 - -1: system error (see `syserrno`)
 - `syserrno` : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

2.7.1.4 int MXCommon__GetClientConnections (void * _ , struct MXCommon__ByteArrayResponse * Response)

Parameters

- [in] _ : no input parameter
- [out] **Response** • sArray : string containing the list of connected clients.
- sResponse Composed of iReturnValue and syserrno

The sArray string is of the form IP-Address:first connection-second connection---- IP-Address:first connection-second connection----

Sample: 172.16.3.43:8989-5555 172.16.3.200:8989

Return values

- SOAP_OK** SOAP call success
- otherwise** SOAP protocol error

2.7.1.5 int MXCommon__Strerror (xsd__int errnum, struct MXCommon__ByteArrayResponse * Response)

Usually SOAP functions return this value in a variable named syserror, which is meaningful only when the function return value, usually called iReturnValue, indicate an error (that is, have a value of -1 or -100, depending of the case).

Parameters

- [in] **errnum** : Error number
- [out] **Response** • sArray : See the description below.
- sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno).
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

STRERROR(3)
STRERROR(3)

Linux Programmer's Manual

NAME

strerror, strerror_r - return string describing error code

SYNOPSIS

```
#include <string.h>
```

```
char *strerror(int errnum);
```

```
#define _XOPEN_SOURCE 600
#include <string.h>
```

```
int strerror_r(int errnum, char *buf, size_t n);
```

DESCRIPTION

The `strerror()` function returns a string describing the error code passed in the argument `errnum`, possibly using the `LC_MESSAGES` part of the current locale to select the appropriate language.

This string must not be modified by the application, but may be modified by a subsequent call to `perror()` or `strerror()`. No library function will modify this string.

The `strerror_r()` function is similar to `strerror()`, but is thread safe. It returns the string in the user-supplied buffer `buf` of length `n`.

RETURN VALUE

The `strerror()` function returns the appropriate error description string, or an unknown error message if the error code is unknown.

The value of `errno` is not changed for a successful call, and is set to a non-zero value upon error.

The `strerror_r()` function returns 0 on success and -1 on failure, setting `errno`.

ERRORS

`EINVAL` The value of `errnum` is not a valid error number.

`ERANGE` Insufficient storage was supplied to contain the error description string.

CONFORMING TO

SVID 3, POSIX, 4.3BSD, ISO/IEC 9899:1990 (C89).

`strerror_r()` with prototype as given above is specified by SUSv3, and was in use under Digital Unix and HP Unix. An incompatible function, with prototype

```
char *strerror_r(int errnum, char *buf, size_t n);
```

is a GNU extension used by glibc (since 2.0), and must be regarded as obsolete in view of SUSv3.

The GNU version may, but need not, use the user-supplied buffer.

If it does, the result may be truncated in case the supplied buffer is too small. The result is always NUL-terminated.

SEE ALSO

`errno(3)`, `perror(3)`, `strsignal(3)`

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

2.7.1.6 int MXCommon__Reboot (void * __, struct MXCommon__Response * *Response*)

Parameters

[in] `__` : no input parameter

[out] ***Response*** • `iReturnValue` : Return value

– 0 : success

– -1 : system error (see `syserrno`)

• `syserrno` : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

2.7.1.7 `int MXCommon__ResetAllIOFunctionalities (xsd__unsignedLong ulOption, struct MXCommon__Response * Response)`

The behavior of the function depends on the MSX-E system that is used.

On MSX-E3511: Stop the watchdogs and stop the generators
 On MSX-E3601: Stop the sequence acquisition and stop the calibration
 On MSX-E3701: Stop the acquisition

Parameters

- [in] *ulOption* Reserved. Set to 0
- [out] *Response iReturnValue*
- **0** The remote function performed OK
 - **-1** Internal system error occurred. See value of `syserrno`
 - **-100** Function not supported by the system
- syserrno* system error code (the value of the libc "errno" code)

Return values

- 0** SOAP_OK
- Others* See SOAP error

2.7.1.8 `int MXCommon__DataseverRestart (xsd__unsignedLong ulAction, xsd__unsignedLong ulOption, struct MXCommon__Response * Response)`

Parameters

- [in] *ulAction* : action
- 0: normal restart
 - 1: with cache file reset
 - 2: with cache file deletion
- [in] *ulOption* : Reserved
- [out] *Response* • *iReturnValue* : Return value
- 0: success
 - -1: system error (see `syserrno`)
 - `syserrno` : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

- SOAP_OK** SOAP call success
- otherwise* SOAP protocol error

Note

(revision>6386) Depending on the system type, can be used to restart the data-recv service as well. In this case, parameter action is ignored.

2.7.1.9 `int MXCommon__GetEthernetLinksStates (void * _, struct MXCommon__GetEthernetLinksStatesResponse * Response)`

Parameters

[in] `_` : no input parameter

[out] *Response* Structure that contains the MSX-E Ethernet links states and errors:

sResponse.iReturnValue

- **0** The remote function performed OK
- **-1** System error occurred
- **-2** Fail to get Ethernet links states
- **-100** Internal system error occurred. See value of `syserrno`

sResponse.syserrno system error code (the value of the libc "errno" code)

sPort0: Fisrt port informations

- **ulState**
 - **0** Link down
 - **1** Link up
- **ulSpeed**
 - **10** 10 Mb/s
 - **100** 100 Mb/s
- **ulDuplex**
 - **0** Half duplex
 - **1** Full duplex
- **ulInfo1** Reserved
- **ulInfo2** Reserved

sPort1: Second port informations

- **ulState**
 - **0** Link down
 - **1** Link up
- **ulSpeed**
 - **10** 10 Mb/s
 - **100** 100 Mb/s
- **ulDuplex**
 - **0** Half duplex
 - **1** Full duplex
- **ulInfo1** Reserved
- **ulInfo2** Reserved

Return values

0 SOAP_OK

Others See SOAP error

2.8 Common temperature functions

These functions deals with the internal temperature sub-system.

Data Structures

- struct [MXCommon__GetModuleTemperatureValueAndStatusResponse](#)

Functions

- int [MXCommon__GetModuleTemperatureValueAndStatus](#) (xsd__unsignedLong ulOption, struct [MXCommon__GetModuleTemperatureValueAndStatusResponse](#) *Response)

Read the temperature on the module.

- int [MXCommon__SetModuleTemperatureWarningLevels](#) (xsd__double dMinimalWarningLevel, xsd__double dMaximalWarningLevel, xsd__unsignedLong ulOption, struct [MXCommon__Response](#) *Response)

Set the temperature warning level on the module.

2.8.1 Detailed Description

The role of this sub-system is to monitor the internal temperature of a module and issue a warning if it is below or above a threshold. If the internal temperature reaches a domain where the system is endangered, it switches automatically in a degraded working mode.

2.8.2 Function Documentation

2.8.2.1 int [MXCommon__GetModuleTemperatureValueAndStatus](#) (xsd__unsignedLong *ulOption*, struct [MXCommon__GetModuleTemperatureValueAndStatusResponse](#) * *Response*)

Parameters

[in] *ulOption* : Reserved

[out] *Response* • sResponse.iReturnValue : Return value

– 0 : success

– -1: system error (see syserrno)

- sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Sterror\(\)](#).

– dValue : Temperature value in Degree Celsius

- ulTemperatureStatus : Temperature Status :

– TEMPERATURE_INITIAL = 0 : Temperature not ready

– TEMPERATURE_TOLOW = 1 : Temperature too low !

– TEMPERATURE_LOW = 2 : Temperature under the min warning value

– TEMPERATURE_NOMINAL = 3 : Temperature in the nominal range

– TEMPERATURE_HIGH = 4 : Temperature over the max warning value

– TEMPERATURE_TOOHIGH = 5 : Temperature too high !

- ulInfo : Reserved

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

2.8.2.2 `int MXCommon__SetModuleTemperatureWarningLevels (xsd__double dMinimalWarningLevel, xsd__double dMaximalWarningLevel, xsd__unsignedLong ulOption, struct MXCommon__Response * Response)`

Parameters

- [in] *dMinimalWarningLevel* : Minimal temperature warning level in Degree : 5 to 60 Degree Celsius
- [in] *dMaximalWarningLevel* : Maximal temperature warning level in Degree : 5 to 60 Degree Celsius
- [in] *ulOption* : Reserved
- [out] *Response*
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Sterror\(\)](#).

Return values

- SOAP_OK* SOAP call success
- otherwise* SOAP protocol error

2.9 Common hardware trigger functions

These functions allow to set and request the current value of the hardware trigger.

Data Structures

- struct [MXCommon__GetHardwareTriggerFilterTimeResponse](#)
- struct [MXCommon__GetHardwareTriggerStateResponse](#)

Functions

- int [MXCommon__SetHardwareTriggerFilterTime](#) (xsd__unsignedLong ulFilterTime, xsd__unsignedLong ulOption, struct MXCommon__Response *Response)
Sets the filter time for the hardware trigger input in steps of 250 ns (max value: 65535).
- int [MXCommon__GetHardwareTriggerFilterTime](#) (xsd__unsignedLong ulOption, struct MXCommon__GetHardwareTriggerFilterTimeResponse *Response)
Get the filter time for the hardware trigger input.
- int [MXCommon__GetHardwareTriggerState](#) (xsd__unsignedLong ulOption, struct MXCommon__GetHardwareTriggerStateResponse *Response)
Get the hardware trigger state after the filter.

2.9.1 Function Documentation

2.9.1.1 `int MXCommon__SetHardwareTriggerFilterTime (xsd__unsignedLong ulFilterTime, xsd__unsignedLong ulOption, struct MXCommon__Response * Response)`

Sets the filter time for the hardware trigger input in steps of 250 ns (max value: 65535).

On the MSX-E3011 system, the step of the hardware trigger filter is **622ns**.

Parameters

[in] *ulFilterTime* Filter time for the hardware trigger input in steps of 250ns (max value : 65535).

- **0**: Disable the filter
- **1**: Sets the filter time to 250 ns
- **2**: Sets the filter time to 500 ns
- ...
- **65535**: Sets the filter time to 16 ms

[in] *ulOption* Reserved. Set to 0

[out] *Response* Response of the system

- *sResponse.iReturnValue*
 - **0**: The remote function performed OK
 - **-1**: Internal system error occurred. See value of syserrno
- *sResponse.syserrno* system error code (the value of the libc "errno" code)

Return values

0 SOAP_OK

Others See SOAP error

2.9.1.2 `int MXCommon__GetHardwareTriggerFilterTime (xsd__unsignedLong ulOption, struct MXCommon__GetHardwareTriggerFilterTimeResponse * Response)`

Get the filter time for the hardware trigger input in **250ns** step (max value : 65535).

On the MSX-E3011 system, the step of the hardware trigger filter is **622ns**.

Parameters

[in] *ulOption* Reserved. Set to 0

[out] *Response* Response of the system

- *ulFilterTime* filter time for the hardware trigger input
 - **0**: filter disabled
 - **1**: filter of 250ns
 - **2**: filter of 500ns
 - ...
 - **65535**: filter of 16ms
- *sResponse.iReturnValue*
 - **0**: The remote function performed OK
 - **-1**: Internal system error occurred. See value of syserrno
- *sResponse.syserrno* system error code (the value of the libc "errno" code)

Return values*0* SOAP_OK*Others* See SOAP error

2.9.1.3 `int MXCommon__GetHardwareTriggerState (xsd__unsignedLong ulOption, struct MXCommon__GetHardwareTriggerStateResponse * Response)`

Parameters[in] *ulOption* : Reserved[out] *Response* • ulState : Hardware trigger input state.

- 0: Hardware trigger input is low
- 1: Hardware trigger input is high.

• sResponse.iReturnValue : Return value

- 0 : success
- -1: system error (see syserrno)

• sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).**Return values***SOAP_OK* SOAP call success*otherwise* SOAP protocol error

2.10 Common security functions

The "customer key" feature may for instance be used by a customer to be sure that his application communicates only with certified MSX-E modules.

Data Structures

- struct [MXCommon__TestCustomerIDResponse](#)

Functions

- int [MXCommon__SetCustomerKey](#) (struct [xsd__base64Binary](#) *bKey, struct [xsd__base64Binary](#) *bPublicKey, struct [MXCommon__Response](#) *Response)

Set the Customer key.

- int [MXCommon__TestCustomerID](#) (void *_ , struct [MXCommon__TestCustomerIDResponse](#) *Response)

Test the Customer ID (if the module has the right customer Key).

2.10.1 Detailed Description

A "customer key" consists of two strings of data stored on the certified MSX-E module, to be used by the function `MXCommon__TestCustomerID()` to encrypt data.

These strings can not be read back. They are supposed to be kept secret by the user of this functionality.

To test if the MSX-E module you use is certified, you can request the MSX-E module to provide a set of randomly generated data and the result of the encryption (through the use of the stored "customer key") of the same data. Then your application must encrypt the delivered random data with its own "customer key" and compare it with the encrypted data delivered by the MSX-E module.

If the results are matching, the MSX-E module is certified for this application.

Detailed presentation of operations:

The user generates and stores on the module two keys (thanks to the software function : `MXCommon__SetCustomerKey()`). This needs only to be done once:

- A public Key K1 (16 Bytes)
- A private Key K2 (32 Bytes)

When requested (with the software function : `MXCommon__TestCustomerID()`), the module generates a 16 bytes random value and do an encryption of this value using the two saved keys and the AES algorithm (Rijndael).

The user receives then two arrays of 16 bytes :

- one with a random value [A]
- the second with encrypted random value [B]

$[B] = \text{AES}([A], K1, K2)$

The user performs then the same computation from [A],K1,K2 and compares his result with [B]. If it is the same, it means that the module he is using was already configured with the correct identification token.

The security of the method comes from that even knowing [A] and [B] no one can deduce K1 and K2 back in practical times. ADDI-DATA is not aware of a practical way to remotely retrieve the value of the key stored on a module.

It is the responsibility of the developer of the application to ensure that these tokens are suitably protected. The authorisation of the change of the "customer key" on the MSX-E module can be managed with the web interface.

The use of the "customer key" don't have an impact of the other functionalities of the MSX-E module.

2.10.2 Function Documentation

2.10.2.1 `int MXCommon__SetCustomerKey (struct xsd__base64Binary * bKey, struct xsd__base64Binary * bPublicKey, struct MXCommon__Response * Response)`

Parameters

- [in] *bKey* : Customer key (only writable on the module) [32 bytes containing a AES key]
 [in] *bPublicKey* : IV (Initialisation vector) for the AES cryptography [16 bytes containing a AES key]
 [out] *Response* • `sResponse.iReturnValue` : Return value

- 0 : success
- -1: system error (see `syserrno`)
- `sResponse.syserrno` : System-error code. The value of the libc "errno" code, see [MXCommon__Sterror\(\)](#).

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

2.10.2.2 `int MXCommon__TestCustomerID (void * _, struct MXCommon__TestCustomerIDResponse * Response)`

Parameters

- [in] `_` : No Input
- [out] *Response* • `sResponse.iReturnValue` : Return value
- 0 : success
 - -1: system error (see `syserrno`)
 - `sResponse.syserrno` : System-error code. The value of the libc "errno" code, see [MXCommon__Sterror\(\)](#).
 - `bValueArray` : non encrypted value array [16 bytes of random data]
 - `bCryptedValueArray` : Encrypted value array [16 bytes of the encrypted random data]

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

2.11 Common time functions

A MSX-E module provides a "system clock" that may be in the simplest case set by the function [MXCommon__SetTime\(\)](#).

Data Structures

- struct [MXCommon__GetTimeResponse](#)
- struct [MXCommon__GetUpTimeResponse](#)

Functions

- `int MXCommon__SetTime (xsd__unsignedLong ulLowTime, xsd__unsignedLong ulHighTime, struct MXCommon__Response *Response)`
Set the time on the module.
- `int MXCommon__SysToHardwareClock (void *, struct MXCommon__Response *Response)`
Set the hardware clock (if present) to the current system time.

- `int MXCommon__HardwareClockToSys (void *, struct MXCommon__Response *Response)`
Set the system time from the hardware clock (if present).
- `int MXCommon__GetTime (void *, struct MXCommon__GetTimeResponse *Response)`
Get the time on the module.
- `int MXCommon__GetUpTime (void *, struct MXCommon__GetUpTimeResponse *Response)`
Ask the MSX-E module uptime (number of seconds since the last boot).

2.11.1 Detailed Description

If the module is configured to use NTP, the time received by the NTP server will have a greater priority. If the module is linked to another through a "synchronization bus" and is slave, then the time received from the master is the one taken into account.

Recent models also provide a "hardware clock", a component whose role is to track the time between reboots.

2.11.2 Function Documentation

2.11.2.1 `int MXCommon__SetTime (xsd__unsignedLong ulLowTime, xsd__unsignedLong ulHighTime, struct MXCommon__Response * Response)`

Parameters

- [in] *ulLowTime* : Number of microseconds since the begin of the second
- [in] *ulHighTime* : Number of seconds since the Epoch (1st January,1970)
- [out] *Response*
 - `sResponse.iReturnValue` : Return value
 - 0 : success
 - -1: system error (see `syserrno`)
 - `sResponse.syserrno` : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

2.11.2.2 `int MXCommon__SysToHardwareClock (void * _, struct MXCommon__Response * Response)`

Parameters

- [in] *_* No input parameter
- [out] *Response*
 - `sResponse.iReturnValue` : Return value
 - 0 : success
 - -1: system error (see `syserrno`)
 - `sResponse.syserrno` : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

If this function fails, it means the module does not have a hardware RTC, or the hardware is not functional. Check the "hwclock" subsystem status.

2.11.2.3 int MXCommon__HardwareClockToSys (void * __, struct MXCommon__Response * Response)

When the hardware clock is present, the system time is automatically set to it when the module becomes master on the inter-module synchronisation bus.

Parameters

- [in] _ No input parameter
- [out] **Response**
- sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

If this function fails, it means the module does not have a hardware RTC, or the hardware is not functional. Check the "hwclock" subsystem status.

2.11.2.4 int MXCommon__GetTime (void * __, struct MXCommon__GetTimeResponse * Response)**Parameters**

- [in] _ : No input parameter
- [out] **Response**
- sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - ulLowTime : Number of microseconds since the begin of the second
 - ulHighTime : Number of seconds since the Epoch (1st January,1970)

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

2.11.2.5 int MXCommon__GetUpTime (void * __, struct MXCommon__GetUpTimeResponse * Response)

Parameters

- [in] __ : no input parameter
- [out] **Response** • sResponse.iReturnValue : Return value
- 0 : success
 - -1: system error (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Sterror\(\)](#).
 - ulUpTime : Number of seconds since the last boot of the system.

Return values

- SOAP_OK** SOAP call success
- otherwise** SOAP protocol error

2.12 Common I/O auto configuration functions

On the web site of some MSX-E module, there is the possibility to define an auto-configuration and auto start of the I/O.

Data Structures

- struct [MXCommon__GetAutoConfigurationFileResponse](#)

Functions

- int [MXCommon__GetAutoConfigurationFile](#) (void __, struct [MXCommon__GetAutoConfigurationFileResponse](#) *Response)
Get the auto configuration file of the module.
- int [MXCommon__SetAutoConfigurationFile](#) (struct [xsd__base64Binary](#) *ByteArrayInput, [xsd__unsignedLong](#) ulEOF, struct [MXCommon__Response](#) *Response)
Set the auto configuration file of the module.
- int [MXCommon__StartAutoConfiguration](#) (void __, struct [MXCommon__ByteArrayResponse](#) *Response)
start/Restart the auto configuration

2.12.1 Detailed Description

- Auto-configuration means the system configures the I/O automatically at boot time.
- Auto-start means the system starts an acquisition automatically at boot time (this may no make sense for some systems). It implies auto-configuration.

This set of functions allows to:

- get the auto-configuration/start currently set on module, as a read-only binary file.
- set a auto-configuration/start on the module, using a previously saved file.
- start or restart the auto-configuration/start on the module, using the current configuration saved on the module.

2.12.2 Function Documentation

2.12.2.1 int MXCommon__GetAutoConfigurationFile (void * _, struct MXCommon__GetAutoConfigurationFileResponse * Response)

Parameters

- [in] _ : No input parameter
- [out] **Response** • sResponse.iReturnValue : Return value
- 0 : success
 - -1: system error (see syserrno)
 - -100 : Error of the read of the auto configuration file
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - bArray : Array of Bytes of the file
 - ulEOF : End of file flag

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

2.12.2.2 int MXCommon__SetAutoConfigurationFile (struct xsd__base64Binary * ByteArrayInput, xsd__unsignedLong ulEOF, struct MXCommon__Response * Response)

Parameters

- [in] **ByteArrayInput** : Array of Bytes of the file
- [in] **ulEOF** : End of file flag
- [out] **Response** • sResponse.iReturnValue : Return value
- 0 : success
 - -1: system error (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

2.12.2.3 int MXCommon__StartAutoConfiguration (void * _ , struct MXCommon__ByteArrayResponse * Response)

Parameters

- [in] _ : No input parameter
- [out] **Response**
- sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - sArray : message returned by the auto configuration start

Return values

- SOAP_OK** SOAP call success
- otherwise** SOAP protocol error

2.13 Common synchronisation timer functions

When modules are linked through a "synchronisation bus", the master can run a timer that generate a "synchro signal" on the slaves when overrun.

Functions

- int [MXCommon__InitAndStartSynchroTimer](#) (xsd__unsignedLong ulTimeBase, xsd__unsignedLong ulReloadValue, xsd__unsignedLong ulNbrOfCycle, xsd__unsignedLong ulGenerateTriggerMode, xsd__unsignedLong ulOption01, xsd__unsignedLong ulOption02, xsd__unsignedLong ulOption03, xsd__unsignedLong ulOption04, struct MXCommon__Response *Response)
Initialises and starts the synchronisation timer of the module (not already available on all module).
- int [MXCommon__StopAndReleaseSynchroTimer](#) (xsd__unsignedLong ulOption01, struct MXCommon__Response *Response)
start/Restart the synchronisation timer (not already available on all module)

2.13.1 Function Documentation

2.13.1.1 int MXCommon__InitAndStartSynchroTimer (xsd__unsignedLong ulTimeBase, xsd__unsignedLong ulReloadValue, xsd__unsignedLong ulNbrOfCycle, xsd__unsignedLong ulGenerateTriggerMode, xsd__unsignedLong ulOption01, xsd__unsignedLong ulOption02, xsd__unsignedLong ulOption03, xsd__unsignedLong ulOption04, struct MXCommon__Response * Response)

Parameters

- [in] **ulTimeBase** : Time base of the timer (0 for us, 1 for ms, 2 for s)
- [in] **ulReloadValue** : Timer reload value (0 to 0xFFFF), minimum reload time is 5 us
- [in] **ulNbrOfCycle** : Number of timer cycle

- 0: continuous
 - > 0: defined number of cycle
- [in] **ulGenerateTriggerMode** :
- 0: Wait the time overflow to set the synchronisation trigger
 - 1: Set the synchronisation trigger by the start of the timer and after each time overflow
- [in] **ulOption01** : Define the source of the trigger
- 0 : Trigger disabled
 - 1 : Enable the hardware digital input trigger
- [in] **ulOption02** : Define the edge of the hardware trigger who generates a trigger action
- 1 : rising edge (Only if hardware trigger selected)
 - 2 : falling edge (Only if hardware trigger selected)
 - 3 : Both front (Only if hardware trigger selected)
- [in] **ulOption03** : Define the number of trigger events before the action occur
- 1 : all trigger event start the action
 - max value : 65535
- [in] **ulOption04** : Reserved
- [out] **Response** • sResponse.iReturnValue : Return value
- 0 : success
 - -1: system error (see syserrno)
 - -2: not available time base
 - -3: timer reload value can not be greater than 65535
 - -4: minimum time reload is 5 us
 - -5: Number of cycle can not be greater than 65535
 - -6: Generate trigger mode error
 - -100: Init timer error
 - -101: Start timer error
- sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Sterror\(\)](#). May be ENOSYS : Function not implemented.

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

2.13.1.2 int MXCommon__StopAndReleaseSynchroTimer (xsd__unsignedLong ulOption01, struct MXCommon__Response * Response)

Parameters

- [in] **ulOption01** : Reserved
- [out] **Response** • sResponse.iReturnValue : Return value
- 0 : success
 - -1: system error (see syserrno)
 - -100: Start/Stop timer error
- sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Sterror\(\)](#). May be ENOSYS : Function not implemented.

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

2.14 Set/Backup/Restore general system configuration

Distinct of the I/O auto-configuration/auto-start functionality, these functions allows to manipulate the general system configuration.

Functions

- `int MXCommon__GetConfigurationBackupFile (void *_ , struct MXCommon__FileResponse *Response)`
Download a configuration backup file from the module.
- `int MXCommon__ApplyConfigurationBackupFile (struct xsd__base64Binary *ByteArrayInput, xsd__unsignedLong ulEOF, struct MXCommon__Response *Response)`
Upload a new configuration on the module.
- `int MXCommon__ChangePassword (struct xsd__base64Binary *PreviousUser, struct xsd__base64Binary *PreviousPassword, struct xsd__base64Binary *NewUser, struct xsd__base64Binary *NewPassword, struct MXCommon__Response *Response)`
Set a new id/password.

2.14.1 Detailed Description

It includes the network configuration, and generally everything that can be set up through the web interface.

These functions have been included to ease the automation of module customisation. They may be disabled using the web interface, in "Security/Remote general system configuration authorisation/remote sysconf changes"

2.14.2 Function Documentation

2.14.2.1 `int MXCommon__GetConfigurationBackupFile (void * _ , struct MXCommon__FileResponse * Response)`

Parameters

- [in] `_` : No input parameter
- [out] **Response**
 - `sResponse.iReturnValue` : Return value
 - 0 : success
 - -1: system error (see `syserrno`) (see `syserrno`)
 - `sResponse.syserrno` : System-error code. The value of the libc "errno" code, see [MXCommon__Sterror\(\)](#).
 - `bArray` : Array of Bytes of the file
 - `ulEOF` : End of file flag

Return values

- SOAP_OK* SOAP call success
- otherwise* SOAP protocol error

This function is designed to be called repeatedly until no more data is available. At this point the flag `ulEOF` is set.

Below is an example in pseudo-C.

```
int dummy;
struct MXCommon__FileResponse Response;
while(1)
{
    if ( MXCommon__GetConfigurationBackupFile(&dummy, &Response) != SOAP_OK)
    {
        // handle soap error
    }
    if (Response.iReturnValue)
    {
        // handle remote error (Response.syserrno contains more information)
    }
    // do something with the data, for example save it in a file
    write(fd, Response.bArray.__ptr, Response.bArray.__size);
    // if this is the end of the file, quit the loop
    if(Response.ulEOF)
        break;
}
*
```

2.14.2.2 `int MXCommon__ApplyConfigurationBackupFile (struct xsd__base64Binary * ByteArrayInput, xsd__unsignedLong ulEOF, struct MXCommon__Response * Response)`

Parameters

- [in] *ByteArrayInput* : Array of Bytes of the file
- [in] *ulEOF* : End of file flag
- [out] *Response*
 - `sResponse.iReturnValue` : Return value
 - 0: success
 - -1: system error (see `syserrno`)
 - `sResponse.syserrno` : System-error code. The value of the libc "errno" code, see [MXCommon__Sterror\(\)](#).

Return values

- SOAP_OK* SOAP call success
- otherwise* SOAP protocol error

This function is designed to be called repeatedly until all data is transferred. At this point the flag `ulEOF` must be set to 1. The new configuration is then applied.

2.14.2.3 `int MXCommon__ChangePassword (struct xsd__base64Binary * PreviousUser, struct xsd__base64Binary * PreviousPassword, struct xsd__base64Binary * NewUser, struct xsd__base64Binary * NewPassword, struct MXCommon__Response * Response)`

The changes are immediately active.

Parameters

- [in] `_` : No input parameter

- [out] **Response**
- sResponse.iReturnValue : Return value
 - 0 : success
 - -1: string PreviousUser is invalid
 - -2: string PreviousPassword is invalid
 - -3: string NewUser is invalid
 - -4: string NewPassword is invalid
 - -5: authentication failed
 - -100: system error while saving tokens (use syserrno for more information)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Sterror\(\)](#).
 - sArray : message returned by the auto configuration start

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

Warning

The parameters transit in clear text. Use this functionality only on trusted networks.
 Given that ADDI-DATA GmbH takes security seriously, there is no way to change the password without knowing it. No "hidden back-door". This function makes it all too easy to lock a module, if you don't remember the password you set on it.

2.15 System state management

Every MSX-E modules are composed of several sub-systems that work together to provide the system functionalities.

Functions

- int [MXCommon__GetSubSystemState](#) (xsd__unsignedLong SubsystemID, struct [MXCommon__unsignedLongResponse](#) *Response)
Returns the current state of the specified sub-system.
- int [MXCommon__GetSubsystemIDFromName](#) (struct [xsd__base64Binary](#) *SubsystemName, struct [MXCommon__unsignedLongResponse](#) *Response)
Returns the ID of the sub-system of symbolic name "SubsystemName".
- int [MXCommon__GetStateIDFromName](#) (xsd__unsignedLong SubsystemID, struct [xsd__base64Binary](#) *StateName, struct [MXCommon__unsignedLongResponse](#) *Response)
Returns the ID of the state of symbolic name "StateName" of the sub-system of ID "SubsystemID".
- int [MXCommon__GetSubsystemNameFromID](#) (xsd__unsignedLong SubsystemID, struct [MXCommon__ByteArrayResponse](#) *Response)
Returns the symbolic name of the sub-system of numerical ID "SubsystemName".
- int [MXCommon__GetStateNameFromID](#) (xsd__unsignedLong SubsystemID, [xsd__unsignedLong](#) StateID, struct [MXCommon__ByteArrayResponse](#) *Response)
Returns the symbolic name of the state of numerical ID "StateID" of the sub-system of ID "SubsystemID".

2.15.1 Detailed Description

These sub-systems have a state that, for example, indicate if it functions nominally.

A sub-system is identified by its ID (a positive integer) and its symbolic name. Each state in the set of possible states for a given sub-system has also an ID and a symbolic name.

Names are less likely to change between releases of the MSX-E operating system. That is why manipulating names should be preferred against indexes in an application. Still, manipulating ID is more efficient.

The functions in this section provide a way to retrieve the association between names and indexes. [MXCommon__GetSubSystemState\(\)](#) requests the state of a given sub-system.

Notice that the event manager is the recommended way to be warned of a change of state.

The list of sub-systems and their ID and associated name can be consulted on the web site of the module.

2.15.2 Function Documentation

2.15.2.1 `int MXCommon__GetSubSystemState (xsd__unsignedLong SubsystemID, struct MXCommon__unsignedLongResponse * Response)`

Parameters

- [in] *SubsystemID* sub-system numerical ID
- [out] *Response*
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error while executing the request (see syserrno)
 - -2: invalid parameter SubsystemID
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Sterror\(\)](#).
 - Value The state of the sub-system "Id" at the moment of the execution of the request.

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

2.15.2.2 `int MXCommon__GetSubsystemIDFromName (struct xsd__base64Binary * SubsystemName, struct MXCommon__unsignedLongResponse * Response)`

Parameters

- [in] *SubsystemName* sub-system symbolic name.
- [out] *Response*
 - sResponse.iReturnValue :Return value
 - 0 : success
 - -1: system error while executing the request (see syserrno)
 - -2: invalid parameter SubsystemName
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Sterror\(\)](#).
 - Value The numerical ID of the sub-system "SubsystemName".

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

2.15.2.3 `int MXCommon__GetStateIDFromName (xsd__unsignedLong SubsystemID, struct xsd__base64Binary * StateName, struct MXCommon__unsignedLongResponse * Response)`

Parameters

- [in] *SubsystemID* sub-system numerical ID
- [in] *StateName* state symbolic name.
- [out] *Response*
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error while executing the request (see syserrno)
 - -2: invalid parameters SubsystemID or StateName
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - Value The numerical ID of the state "StateName".

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

2.15.2.4 `int MXCommon__GetSubsystemNameFromID (xsd__unsignedLong SubsystemID, struct MXCommon__ByteArrayResponse * Response)`

Parameters

- [in] *SubsystemID* sub-system numerical ID.
- [out] *Response*
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error while executing the request (see syserrno)
 - -2: invalid parameter SubsystemName
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - sArray : The symbolic name associated with the ID.

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

2.15.2.5 `int MXCommon__GetStateNameFromID (xsd__unsignedLong SubsystemID, xsd__unsignedLong StateID, struct MXCommon__ByteArrayResponse * Response)`

Parameters

- [in] *SubsystemID* sub-system numerical ID.
- [in] *StateID* sub-system numerical ID.

- [out] **Response**
- sResponse.iReturnValue : Return value
 - 0 success
 - -1 system error while executing the request (see syserrno)
 - -2 invalid parameters SubsystemID or StateID
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - sArray The symbolic name associated with the state numerical ID.

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

2.16 Customer option management

Enable to get informations about the options of the system.

Functions

- int [MXCommon__GetOptionInformation](#) (void *, [xsd__unsignedLong](#) ulOption01, [xsd__unsignedLong](#) ulOption02, struct [MXCommon__ByteArrayResponse](#) *Response)
- Enables to get information about the options available on the system.*

2.16.1 Function Documentation

2.16.1.1 int [MXCommon__GetOptionInformation](#) (void * _, [xsd__unsignedLong](#) ulOption01, [xsd__unsignedLong](#) ulOption02, struct [MXCommon__ByteArrayResponse](#) * Response)

Parameters

- [in] **ulOption01,:** not used, set it to 0
- [in] **ulOption02,:** not used, set it to 0
- [out] **Response**
- sArray : Option information string
 - sResponse Composed of iReturnValue and syserrno

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

2.17 Synchronisation management

Manage the synchronisation state of the system.

Functions

- `int MXCommon__SetToMaster (void *_ , xsd__unsignedLong ulState, xsd__unsignedLong ulOption01, xsd__unsignedLong ulOption02, struct MXCommon__Response *Response)`

Writes if the MSXE has to be always set to master The master mode (when enabled) make the system always detected as master.

- `int MXCommon__GetSynchronizationStatus (void *_ , xsd__unsignedLong ulOption01, xsd__unsignedLong ulOption02, struct MXCommon__unsignedLongResponse *Response)`

Reads the status of the synchronization for the corresponding MSXE The master mode (when enabled) make the system always detected as master.

2.17.1 Function Documentation

- 2.17.1.1** `int MXCommon__SetToMaster (void * _ , xsd__unsignedLong ulState, xsd__unsignedLong ulOption01, xsd__unsignedLong ulOption02, struct MXCommon__Response * Response)`

Parameters

[in] *ulState* State of the supermaster mode

- **0** automatic mode (default). The state of the system (master or slave) will be automatically detected by the system
- **1** Set to master mode at all time. The system will always be detected as master

[in] *ulOption01* Reserved. Set to 0

[in] *ulOption02* Reserved. Set to 0

[out] *Response iReturnValue*

- **0** The remote function performed OK
- **-1** System error occurred
- **-2** The PLD is not working
- **-3** The ulFilterTime parameter is wrong
- **-100** Internal system error occurred. See value of syserrno *syserrno* system error code (the value of the libc "errno" code)

Return values

0 SOAP_OK

Others See SOAP error

- 2.17.1.2** `int MXCommon__GetSynchronizationStatus (void * _ , xsd__unsignedLong ulOption01, xsd__unsignedLong ulOption02, struct MXCommon__unsignedLongResponse * Response)`

Parameters

[in] *ulOption01* Reserved. Set to 0

[in] *ulOption02* Reserved. Set to 0

[out] *Response sResponse.iReturnValue*

- **0** The remote function performed OK
- **-1** System error occurred
- **-2** The PLD is not working
- **-100** Internal system error occurred. See value of `syserrno`

sResponse.syserrno system error code (the value of the libc "errno" code)

ulValue State of the supermaster mode

- **0** Automatic mode (default). The state of the system (master or slave) will be automatically detected by the system
- **1** MSXE is always set as a master. The system will always be detected as master

Return values

0 SOAP_OK

Others See SOAP error

2.18 MSX-E321x Acquisition functions

Contain the acquisition information and initialisation functions.

Modules

- [MSX-E321x Acquisition information functions](#)

Contain the acquisition information functions.

- [MSX-E321x Autorefresh functions](#)

In the auto refresh mode the measurement value is updated automatically after each acquisition.

- [MSX-E321x Sequence functions](#)

A sequence is a list of channels (max 16) that are acquired.

2.19 MSX-E321x Acquisition information functions

Contain the acquisition information functions.

Data Structures

- struct [MSXExxxx__AcquisitionGetChannelInfoResponse](#)

Functions

- int [MSXExxxx__AcquisitionGetNumberOfChannels](#) (xsd__unsignedLong ulOption1, struct [MSXExxxx__unsignedLongResponse](#) *Response)

Return the number of acquisition channels.

- `int MSXExxxx__AcquisitionGetChannelInfo (xsd__unsignedLong ulChannel, xsd__unsignedLong ulOption1, struct MSXExxxx__AcquisitionGetChannelInfoResponse *Response)`

Return the selected acquisition channel type and hardware position.

2.19.1 Function Documentation

2.19.1.1 `int MSXExxxx__AcquisitionGetNumberOfChannels (xsd__unsignedLong ulOption1, struct MSXExxxx__unsignedLongResponse * Response)`

Parameters

[in] *ulOption1* : Reserved. Set to 0

[out] *Response* :

sResponse.iReturnValue :

- 0: Means the remote function performed OK
- -1: Means an system error occurred
- -100: Internal system error occurred. See value of syserrno

sResponse.syserrno : system-error code (the value of the libc "errno" code)

ulValue : Number of available acquisition channels

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

2.19.1.2 `int MSXExxxx__AcquisitionGetChannelInfo (xsd__unsignedLong ulChannel, xsd__unsignedLong ulOption1, struct MSXExxxx__AcquisitionGetChannelInfoResponse * Response)`

Parameters

[in] *ulChannel* : Selected acquisition channel

[in] *ulOption1* : Reserved. Set to 0

[out] *Response* :

sResponse.iReturnValue :

- 0: Means the remote function performed OK
- -1: Means an system error occurred
- -2: Channel selection wrong
- -100: Internal system error occurred. See value of syserrno

sResponse.syserrno : system-error code (the value of the libc "errno" code)

ulType : Acquisition channel type

- 0 : Not available
- 1 : Temperature channel
- 2 : Pressure channel
- 3 : Transducer channel
- 4 : Analog input channel
- 5 : Analog input ICP channel

- 6 : Digital I/O port
ulHwPosition : Hardware position index (0 to 7) **ulChannelIndex** : Return the functionality channel index

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

2.20 MSX-E321x Autorefresh functions

In the auto refresh mode the measurement value is updated automatically after each acquisition.

Data Structures

- struct [MSXExxxx__AcquisitionAutoRefreshGetValuesResponse](#)

Functions

- int [MSXExxxx__AcquisitionAutoRefreshInitAndStart](#) (xsd__unsignedLong ulChannelMask, xsd__unsignedLong ulAverageValue, xsd__unsignedLong ulRefreshTime, xsd__unsignedLong ulRefreshTimeUnit, xsd__unsignedLong ulTriggerMask, xsd__unsignedLong ulTriggerMode, xsd__unsignedLong ulHardwareTriggerEdge, xsd__unsignedLong ulHardwareTriggerCount, xsd__unsignedLong ulByTriggerNbrOfSeqToAcquire, xsd__unsignedLong ulDataFormat, xsd__unsignedLong ulForceStart, xsd__unsignedLong ulOption1, xsd__unsignedLong ulOption2, xsd__unsignedLong ulOption3, struct [MSXExxxx__Response](#) *Response)
Starts an autorefresh acquisition using provided configuration.
- int [MSXExxxx__AcquisitionAutoRefreshGetValues](#) (xsd__unsignedLong ulBlocking, struct [MSXExxxx__AcquisitionAutoRefreshGetValuesResponse](#) *Response)
Reads the values acquired in auto refresh mode.
- int [MSXExxxx__AcquisitionAutoRefreshStopAndRelease](#) (void *_ , struct [MSXExxxx__Response](#) *Response)
Stops the current auto refresh acquisition.

2.20.1 Detailed Description

The acquisition is initialised and the values of each channels are stored in memory on the Ethernet E/A module MSX-E321x.

The PC reads the data asynchronously to the acquisition via the data socket or a SOAP function.

You can define a mask of all channels that should be acquired.

In the auto refresh mode you can activate the channel average value computation on the module

You can start the acquisition by a hardware trigger or a synchro trigger.

The hardware trigger can react to a rising wave, falling wave or both edges.

You have the following possibility:

- Defining a number of edges before a trigger action is generated

There are two trigger modes:(for the hardware or synchro trigger)

a) One shot

b) Sequence

a) One shot:

After the software start, the module is waiting for a trigger signal to start the acquisition. After this the trigger signal is ignored.

b) Sequence:

After the software start the module is waiting for the trigger signal and acquires x sequences (also adjustable) and then wait again.

2.20.2 Function Documentation

2.20.2.1 `int MSXExxxx__AcquisitionAutoRefreshInitAndStart (xsd__unsignedLong ulChannelMask, xsd__unsignedLong ulAverageValue, xsd__unsignedLong ulRefreshTime, xsd__unsignedLong ulRefreshTimeUnit, xsd__unsignedLong ulTriggerMask, xsd__unsignedLong ulTriggerMode, xsd__unsignedLong ulHardwareTriggerEdge, xsd__unsignedLong ulHardwareTriggerCount, xsd__unsignedLong ulByTriggerNbrOfSeqToAcquire, xsd__unsignedLong ulDataFormat, xsd__unsignedLong ulForceStart, xsd__unsignedLong ulOption1, xsd__unsignedLong ulOption2, xsd__unsignedLong ulOption3, struct MSXExxxx__Response * Response)`

Parameters

- [in] **ulChannelMask** Mask of the channel to acquire by the auto refresh (1 bit = 1 Channel). 0 for all available acquisition channels
- [in] **ulAverageValue** Set the average value :
 - 1 : not used
 - max value : 255
- [in] **ulRefreshTimeUnit** Refresh Time Unit
 - 0 : microsecond
 - 1 : millisecond
 - 2 : second
- [in] **ulRefreshTime** Refresh Time
 - range from min 1000 to 65535 when the unit is the microsecond
 - range from min 1 to 65535 when the unit is the millisecond
 - range from min 1 to 65535 when the unit is the second
- [in] **ulTriggerMask** Define the source of the trigger
 - 0 : trigger disabled
 - 1 : Enable Hardware Digital Input Trigger
 - 2 : Enable Synchro Trigger
 - 4 : Enable Compare Trigger (only useful if your system has incremental counter or Sine/-Cosine input)
 - 8 : Enable Index Trigger (only useful if your system has Sine/Cosine input)

- [in] ***ulTriggerMode*** Define the trigger mode
- 1 : One shot trigger
 - 2 : Sequence trigger
- [in] ***ulHardwareTriggerEdge*** Define the edge of the hardware trigger who generates a trigger action
- 1 : rising edge (Only if hardware trigger selected)
 - 2 : falling edge (Only if hardware trigger selected)
 - 3 : Both front (Only if hardware trigger selected)
- [in] ***ulHardwareTriggerCount*** Define the number of trigger events before the action occur
- 1 : all trigger event start the action
 - max value : 65535
- [in] ***ulByTriggerNbrOfSeqToAcquire*** Define the number of sequence to acquire by each trigger event
- 0 : continuous mode
 - <> 0 : number of sequence : (1..0xFFFFFFFF)
- D0 : Absolute Time stamp information
- [in] ***ulDataFormat*** • 0 : no time stamp information
- 1 : time stamp information
- D1 : Relative Time stamp information
- 0 : no time stamp information
 - 1 : time stamp information
- D2 : Auto refresh counter information
- 0 : No auto refresh counter information
 - 1 : Auto refresh counter information
- D3 : System status information
- 0 : No system status information required
 - 1 : System status information required
- D4 : Data format
- 0: Digital value (see technical description)
 - 1: Analog value (see technical description)
- You can not select both absolute and relative time stamp simultaneously
- [in] ***ulForceStart*** :
- 0 : Function return a error if any acquisition already in progress
 - 1 : If any acquisition in progress then stop this
- [in] ***ulOption1*** Reserved. Set to 0
- [in] ***ulOption2*** Reserved. Set to 0
- [in] ***ulOption3*** Reserved. Set to 0
- [out] ***Response*** :
- iReturnValue*** :
- 0: Means the remote function performed OK
 - -1: Means an system error occurred
 - -2: Any acquisition already in progress
 - -3: Any selected channel not OK, call the diagnostic function for more information
 - -4: Channel Mask error

- -5: Not available average value
- -6: Not available refresh time unit
- -7: The minimal refresh time is 1000 us !
- -8: The maximal refresh time is 65535 !
- -9: Trigger mask not available
- -10: Trigger mask : 2 different trigger source cannot be simultaneously be activated
- -11: Trigger mode not available
- -12: Trigger mask : 2 trigger mode cannot be simultaneously activated
- -13: Hardware trigger : front definition error
- -14: Hardware trigger count value not available
- -15: Nbr of sequence to acquire by trigger mode not available
- -16: Data format not available
- -17: Selected channels combination not available
- -100: Kernel function error

syserrno : system-error code (the value of the libc "errno" code)

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

2.20.2.2 int MSXExxxx__AcquisitionAutoRefreshGetValues (xsd__unsignedLong ulBlocking, struct MSXExxxx__AcquisitionAutoRefreshGetValuesResponse * Response)

Reads the values acquired in auto refresh mode.

Parameters

[in] **ulBlocking** Wait a new value or read the actual value

- **0**: Get the current auto refresh values
- **1**: Wait a new auto refresh value cycle

[out] **Response** Response of the system

- **iReturnValue**
 - **0**: The remote function performed OK
 - **-1**: Means an system error occurred
 - **-2**: No Acquisition in progress
 - **-3**: 2s timeout occurred. This if you have enabled the blocking mode.
 - **-4**: 2s timeout occurred. This if you do not have enabled the blocking mode, and if the first value is not available.
 - **-100**: Internal system error occurred. See value of syserrno
- **syserrno** system error code (the value of the libc "errno" code)
- **ulTimeStampLow** number of microseconds since the Epoch
- **ulTimeStampHigh** number of seconds since the Epoch
- **ulCounterValue** counter value
- **dValue** Array that contains the channels values
 - **dValue[0]** Value of channel 0
 - ...

– *dValue[15]* Value of channel 15

Return values

0 SOAP_OK

Others See SOAP error

2.20.2.3 int MSXExxxx__AcquisitionAutoRefreshStopAndRelease (void * __, struct MSXExxxx__Response * Response)

Parameters

[in] __ Dummy parameter

[out] *Response* :

iReturnValue :

- 0: Means the remote function performed OK
- -1: Means an system error occurred
- -100: Kernel function error

syserrno : system-error code (the value of the libc "errno" code)

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

Must be called before any another call to MSXExxxx__AcquisitionAutoRefreshInitAndStart.

2.21 MSX-E321x Sequence functions

A sequence is a list of channels (max 16) that are acquired.

Data Structures

- struct [MSXExxxx__AcquisitionSequenceInitAndStartChannelListParam](#)

Functions

- int [MSXExxxx__AcquisitionSequenceInitAndStart](#) (xsd_unsignedLong ulNbrOfChannel, struct [MSXExxxx__AcquisitionSequenceInitAndStartChannelListParam](#) *psChannelList, xsd_unsignedLong ulAcquisitionTime, xsd_unsignedLong ulAcquisitionTimeUnit, xsd_unsignedLong ulNbrOfSequence, xsd_unsignedLong ulNbrMaxSequenceToTransfer, xsd_unsignedLong ulTriggerMask, xsd_unsignedLong ulTriggerMode, xsd_unsignedLong ulHardwareTriggerEdge, xsd_unsignedLong ulHardwareTriggerCount, xsd_unsignedLong ulByTriggerNbrOfSeqToAcquire, xsd_unsignedLong ulDataFormat, xsd_unsignedLong ulForceStart, xsd_unsignedLong ulOption1, xsd_unsignedLong ulOption2, xsd_unsignedLong ulOption3, struct [MSXExxxx__Response](#) *Response)

Initialises and starts the sequence acquisition mode.

- int [MSXExxxx__AcquisitionSequenceStopAndRelease](#) (void *__, struct [MSXExxxx__Response](#) *Response)

Stop and release the sequence acquisition mode.

2.21.1 Detailed Description

It can be any order of the channels in this list.

There are different sequence modes:

- Certain number of sequences / continuous

a) Certain number of sequences:

After the acquisition of the defined number of sequences, the acquisition is stopped automatically.

b) Continuous:

The sequences are acquired continuously until a software-stop-command occurs.

You can start the acquisition by a hardware or synchro trigger.

The hardware trigger can react to a rising, falling or both edges.

You have the following possibility:

- Defining a number of edges before a trigger action is generated

There are two trigger modes (for the hardware or synchro trigger):

a) One shot

b) Sequence

a) One shot:

After the software start, the module is waiting for a trigger signal to start the acquisition. After this the trigger signal is ignored.

b) Sequence:

After the software start the module is waiting for the trigger signal and acquires x sequences (also adjustable) and then wait again.

2.21.2 Function Documentation

2.21.2.1 `int MSXExxxx_AcquisitionSequenceInitAndStart (xsd__unsignedLong ulNbrOfChannel, struct MSXExxxx_AcquisitionSequenceInitAndStartChannelListParam * psChannelList, xsd__unsignedLong ulAcquisitionTime, xsd__unsignedLong ulAcquisitionTimeUnit, xsd__unsignedLong ulNbrOfSequence, xsd__unsignedLong ulNbrMaxSequenceToTransfer, xsd__unsignedLong ulTriggerMask, xsd__unsignedLong ulTriggerMode, xsd__unsignedLong ulHardwareTriggerEdge, xsd__unsignedLong ulHardwareTriggerCount, xsd__unsignedLong ulByTriggerNbrOfSeqToAcquire, xsd__unsignedLong ulDataFormat, xsd__unsignedLong ulForceStart, xsd__unsignedLong ulOption1, xsd__unsignedLong ulOption2, xsd__unsignedLong ulOption3, struct MSXExxxx_Response * Response)`

Initialises and starts the sequence acquisition mode.

Parameters

[in] *ulNbrOfChannel* : Nbr of channel in the sequence

- [in] **psChannelList** : List of the channel who compose the sequence.
- [in] **ulAcquisitionTime** : Acquisition Time
- range from min 1000 to 65535 when the unit is the microsecond
 - range from min 1 to 65535 when the unit is the millisecond
 - range from min 1 to 65535 when the unit is the second
- [in] **ulAcquisitionTimeUnit** : Acquisition Time Unit
- 0 : us
 - 1 : ms
 - 2 : s
- [in] **ulNbrOfSequence** : Number of sequence to acquire :
- 0 : continuous mode
 - <> 0 : number of sequence
- [in] **ulNbrMaxSequenceToTransfer** : Max nbr of sequence to acquire before a data transfer : (1,4096)
- [in] **ulTriggerMask** : Define the source of the trigger
- 0 : trigger disabled
 - 1 : Enable Hardware Digital Input Trigger
 - 2 : Enable Synchro Trigger
 - 4 : Enable Compare Trigger (only useful if your system has incremental counter or Sine/-Cosine input)
 - 8 : Enable Index Trigger (only useful if your system has Sine/Cosine input)
- [in] **ulTriggerMode** : Define the trigger mode
- 1 : One shot trigger
 - 2 : Sequence trigger
- [in] **ulHardwareTriggerEdge** : Define the edge of the hardware trigger who generate a trigger action
- 1 : rising front (Only if hardware trigger selected)
 - 2 : falling front (Only if hardware trigger selected)
 - 3 : Both front (Only if hardware trigger selected)
- [in] **ulHardwareTriggerCount** : Define the number of trigger events before the action occur
- 1 : all trigger event start the action
 - max value : 65535
- [in] **ulByTriggerNbrOfSeqToAcquire** : define the number of sequence to acquire by each trigger event
- 0 : continuous mode
 - <> 0 : number of sequence : (1..0xFFFFFFFF)
- [in] **ulDataFormat** : Data format option
- D0 : Absolute Time stamp information
- 0 : no time stamp information
 - 1 : time stamp information
- D1 : Relative Time stamp information
- 0 : no time stamp information
 - 1 : time stamp information

D2 : Sequence counter information

- 0 : No sequence counter information
- 1 : Sequence counter information

D3 : System status information

- 0 : No system status information required
- 1 : System status information required

D4 : Data format

- 0: Digital value (see technical description)
- 1: Analog value (see technical description)

You can not select both absolute and relative time stamp simultaneously

[in] ***ulForceStart*** :

- 0 : Function return a error if any acquisition already in progress
- 1 : If any acquisition in progress then stop this

[in] ***ulOption1*** : Reserved. Set to 0

[in] ***ulOption2*** : Reserved. Set to 0

[in] ***ulOption3*** : Reserved. Set to 0

[out] ***Response*** :

iReturnValue :

- 0: Means the remote function performed OK
- -1: Means an system error occurred
- -2: Any acquisition already in progress
- -3: The nbr of channel in the sequence is null or too high
- -4: Channel index selection error
- -5: Channel already selected
- -6: Any selected channel not OK, call the diagnostic function for more information
- -7: Not available acquisition time unit
- -8: The minimal acquisition time is 1000 us !
- -9: The maximal acquisition time is 65535 !
- -10: Transfer sequence size error (1 to 4096) !
- -11: The total number of sequences is not a multiple from number of sequences to transfer
- -12: Trigger mask not available
- -13: Trigger mask : 2 different trigger source cannot be simultaneously be activated
- -14: Trigger mode not available
- -15: Trigger mask : 2 trigger mode cannot be simultaneously be activated
- -16: Hardware trigger : front definition error
- -17: Hardware trigger count value not available
- -18: Nbr of sequence to acquire by trigger mode not available
- -19: Data format not available
- -20: Selected channels combination not available
- -100: Start sequence kernel function error

syserrno : system-error code (the value of the libc "errno" code)

Return values

0 SOAP_OK

Others See SOAP error

2.21.2.2 int MSXExxxx__AcquisitionSequenceStopAndRelease (void * __, struct MSXExxxx__Response * *Response*)

Parameters

[in] __ : no input parameter

[out] *Response* :

iReturnValue :

- 0: Means the remote function performed OK
- -1: Means an system error occurred
- -2: No sequence acquisition in progress
- -100: Kernel function error

syserrno : system-error code (the value of the libc "errno" code)

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

2.22 MSX-E321x Temperature functions

Contain the temperature initialisation and diagnostic functions.

Modules

- [MSX-E321x Temperature initialisation/information functions](#)

Contain the temperature initialisation/information functions.

- [MSX-E321x Temperature diagnostic functions](#)

Contain the temperature diagnostic functions.

2.23 MSX-E321x Temperature initialisation/information functions

Contain the temperature initialisation/information functions.

Data Structures

- struct [MSXExxxx__TemperatureGetChannelSensorClassResponse](#)
- struct [MSXExxxx__TemperatureGetConfigurationResponse](#)

Functions

- int [MSXExxxx__TemperatureGetNumberOfChannels](#) (xsd__unsignedLong ulOption1, struct [MSXExxxx__unsignedLongResponse](#) *Response)

Return the number of temperature channels.

- `int MSXExxxx__TemperatureGetChannelSensorClass (xsd__unsignedLong ulOption1, struct MSXExxxx__TemperatureGetChannelSensorClassResponse *Response)`
Return the type of the temperature channels.
- `int MSXExxxx__TemperatureSetChannelType (xsd__unsignedLong ulChannel, xsd__unsignedLong ulType, xsd__unsignedLong ulOption1, struct MSXExxxx__Response *Response)`
Temperature sensor type selection for the selected channel.
- `int MSXExxxx__TemperatureSetSamplingRate (xsd__unsignedLong ulChannelGroup, xsd__unsignedLong ulBaseSamplingRate, xsd__unsignedLong ulOption1, struct MSXExxxx__Response *Response)`
Temperature acquisition sampling rate selection.
- `int MSXExxxx__TemperatureGetConfiguration (xsd__unsignedLong ulChannel, xsd__unsignedLong ulOption1, struct MSXExxxx__TemperatureGetConfigurationResponse *Response)`
Get the selected temperature channel current configuration.

2.23.1 Function Documentation

2.23.1.1 `int MSXExxxx__TemperatureGetNumberOfChannels (xsd__unsignedLong ulOption1, struct MSXExxxx__unsignedLongResponse * Response)`

Parameters

- [in] *ulOption1* : Reserved. Set to 0
- [out] *Response* :
- sResponse.iReturnValue* :
- 0: Means the remote function performed OK
 - -1: Means an system error occurred
- sResponse.syserrno* : system-error code (the value of the libc "errno" code)
- ulValue* : Number of available temperature channels

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

2.23.1.2 `int MSXExxxx__TemperatureGetChannelSensorClass (xsd__unsignedLong ulOption1, struct MSXExxxx__TemperatureGetChannelSensorClassResponse * Response)`

Parameters

- [in] *ulOption1* : Reserved. Set to 0
- [out] *Response* :
- iReturnValue* :
- 0: Means the remote function performed OK
 - -1: Means an system error occurred
- syserrno* : system-error code (the value of the libc "errno" code)
- ulType* : Array that contain the channels class (0 : RTD, 1 : TC, 2 : NTC)

- `ulType [0]` : Channel 0 type
- ...
- `ulType [15]` : Channel 15 type

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

2.23.1.3 `int MSXExxxx_TemperatureSetChannelType (xsd__unsignedLong ulChannel, xsd__unsignedLong ulType, xsd__unsignedLong ulOption1, struct MSXExxxx_Response * Response)`

Parameters

[in] *ulChannel* : Channel selection (0 to 15 or 255 for all channels)

[in] *ulType* : Type selection

- For TC
 - 1: Type B
 - 4: Type E
 - 9: Type J
 - 10: Type K
 - 13: Type N
 - 18: Type R
 - 19: Type S
 - 20: Type T
- For RTD type PT
 - 100: PT100
 - 200: PT200
 - 500: PT500
 - 1000: PT1000
 - ...
- For RTD type Ni
 - 101: Ni100
 - 201: Ni200
 - 501: Ni500
 - 1001: Ni1000
 - ...
- For NTC
 - 1: G10K4D453

[in] *ulOption1* : Reserved. Set to 0

[out] *Response* :

iReturnValue :

- 0: Means the remote function performed OK
- -1: Means an system error occurred
- -2: Channel selection wrong
- -3: Type selection wrong

- -4: Acquisition in progress. Can not change the type

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

2.23.1.4 `int MSXExxxx__TemperatureSetSamplingRate (xsd__unsignedLong ulChannelGroup, xsd__unsignedLong ulBaseSamplingRate, xsd__unsignedLong ulOption1, struct MSXExxxx__Response * Response)`

Parameters

[in] *ulChannelGroup* : Channel group selection.

- 0 for channels 0 and 1
- 1 for channels 2 and 3
- 2 for channels 4 and 5
- 3 for channels 6 and 7
- 4 for channels 8 and 9
- 5 for channels 10 and 11
- 6 for channels 12 and 13
- 7 for channels 14 and 15
- ...
- 255 for all channels

[in] *ulBaseSamplingRate* : Sampling rate selection

- 5 for 5Hz
- 10 for 10Hz
- 20 for 20Hz
- 40 for 40Hz
- 80 for 80Hz
- 160 for 160Hz
- 320 for 320Hz
- 640 for 640Hz
- 1000 for 1000Hz
- 2000 for 2000Hz

If only one channel is used then the real sampling rate is $ulBaseSamplingRate / 2$

If all 2 channels are used then the real sampling rate is $ulBaseSamplingRate / 3$

[in] *ulOption1* : Reserved. Set to 0

[out] *Response* :

iReturnValue :

- 0 : Means the remote function performed OK
- -1 : Means an system error occurred
- -2 : Channel group selection error
- -3 : Sampling rate selection error
- -4 : Acquisition in progress. Can not change the sampling rate
- -100 : IOCTL system call error

syserrno : system-error code (the value of the libc "errno" code)

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

2.23.1.5 `int MSXExxxx__TemperatureGetConfiguration (xsd__unsignedLong ulChannel, xsd__unsignedLong ilOption1, struct MSXExxxx__TemperatureGetConfigurationResponse * Response)`

Parameters

[in] *ulChannel* : Channel selection (0 to 15)

[in] *ilOption1* : Reserved. Set to 0

[out] *Response* :

sResponse.iReturnValue :

- 0: Means the remote function performed OK
- -1: Means an system error occurred
- -2: Channel selection wrong

sResponse.syserrno : system-error code (the value of the libc "errno" code)

ulClass : 0 : RTD / 1 : TC

ulType : Type selection

- For TC
 - 1: Type B
 - 4: Type E
 - 9: Type J
 - 10: Type K
 - 13: Type N
 - 18: Type R
 - 19: Type S
 - 20: Type T
- For RTD type PT
 - 100: PT100
 - 200: PT200
 - 500: PT500
 - 1000: PT1000
 - ...
- For RTD type Ni
 - 101: Ni100
 - 201: Ni200
 - 501: Ni500
 - 1001: Ni1000
 - ...
- For NTC
 - 1: G10K4D453

ulBaseSamplingRate : Sampling rate selection

- 5 for 5Hz
- 10 for 10Hz

- 20 for 20Hz
- 40 for 40Hz
- 80 for 80Hz
- 160 for 160Hz
- 320 for 320Hz
- 640 for 640Hz
- 1000 for 1000Hz
- 2000 for 2000Hz

Returns

- 0: Means the remote function performed OK
- -1: Means an system error occurred
- -2: Channel selection wrong

2.24 MSX-E321x Temperature diagnostic functions

Contain the temperature diagnostic functions.

Functions

- int [MSXExxxx__TemperatureDiagnostic](#) (xsd__unsignedLong ulChannel, xsd__unsignedLong ulOption1, struct [MSXExxxx__unsignedLongResponse](#) *Response)
Temperature line diagnostic.

2.24.1 Function Documentation

2.24.1.1 int [MSXExxxx__TemperatureDiagnostic](#) (xsd__unsignedLong ulChannel, xsd__unsignedLong ulOption1, struct [MSXExxxx__unsignedLongResponse](#) * Response)

Parameters

[in] *ulChannel* : Channel selection (0 to 15)

[in] *ulOption1* : Reserved. Set to 0

[out] *Response* :

sResponse.iReturnValue :

- 0: Means the remote function performed OK
- -1: Means an system error occurred

sResponse.syserrno : system-error code (the value of the libc "errno" code)

ulValue : Diagnostic status

- 0 : OK
- 1 : RTD voltage line open
- 2 : RTD voltage line short circuit
- 3 : RTD current line open
- 4 : RTD current line short circuit

- 5 : TC disconnected
- 6 : CJC disconnected (M12 connector not present)
- 7 : RTD sensor front-end disconnected (wiring properly linked)

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

Chapter 3

Data Structure Documentation

3.1 ByteArray Struct Reference

Dynamic Array of byte - encapsulates C-type strings.

Data Fields

- `xsd__unsignedByte * __ptr`
pointer of byte
- `int __size`
size of the byte array in bytes
- `int __offset`
not used

3.1.1 Field Documentation

3.1.1.1 `xsd__unsignedByte* ByteArray::__ptr`

3.1.1.2 `int ByteArray::__size`

3.1.1.3 `int ByteArray::__offset`

3.2 DefaultResponse Struct Reference

Data Fields

- `xsd__int iReturnValue`
return value of the call :
- `xsd__int syserrno`
system-error code (the value of the libc "errno" code)

3.2.1 Field Documentation

3.2.1.1 xsd__int DefaultResponse::iReturnValue

- 0 means the remote function performed OK
- -1 means a system error occurred, the meaning of other values is function dependant and should be defined in the related header

3.2.1.2 xsd__int DefaultResponse::syserrno

3.3 MSXExxxx__AcquisitionAutoRefreshGetValuesResponse Struct Reference

Data Fields

- struct [DefaultResponse](#) sResponse

Default return values.

- [xsd__unsignedLong](#) ulTimeStampLow

The meaning of this field is defined in the related header of the function who use this type.

- [xsd__unsignedLong](#) ulTimeStampHigh

The meaning of this field is defined in the related header of the function who use this type.

- [xsd__unsignedLong](#) ulCounterValue

The meaning of this field is defined in the related header of the function who use this type.

- [xsd__double](#) dValue [16]

The meaning of this field is defined in the related header of the function who use this type.

3.3.1 Field Documentation

- 3.3.1.1 **struct DefaultResponse MSXExxxx__AcquisitionAutoRefreshGetValuesResponse::sResponse**
- 3.3.1.2 **xsd__unsignedLong MSXExxxx__AcquisitionAutoRefreshGetValuesResponse::ulTimeStampLow**
- 3.3.1.3 **xsd__unsignedLong MSXExxxx__AcquisitionAutoRefreshGetValuesResponse::ulTimeStampHigh**
- 3.3.1.4 **xsd__unsignedLong MSXExxxx__AcquisitionAutoRefreshGetValuesResponse::ulCounterValue**
- 3.3.1.5 **xsd__double MSXExxxx__AcquisitionAutoRefreshGetValuesResponse::dValue[16]**

3.4 MSXExxxx__AcquisitionGetChannelInfoResponse Struct Reference

Data Fields

- struct [DefaultResponse sResponse](#)
Default return values.
- [xsd__unsignedLong ulType](#)
Acquisition channel type
.
- [xsd__unsignedLong ulHwPosition](#)
Hardware position index (0 to 7).
- [xsd__unsignedLong ulChannelIndex](#)
Return the functionality channel index.

3.4.1 Field Documentation

- 3.4.1.1 **struct DefaultResponse MSXExxxx__AcquisitionGetChannelInfoResponse::sResponse**
- 3.4.1.2 **xsd__unsignedLong MSXExxxx__AcquisitionGetChannelInfoResponse::ulType**
 - 0 : Not available
 - 1 : Temperature channel
 - 2 : Pressure channel
 - 3 : Transducer channel
 - 4 : Analog input channel
 - 5 : Analog input ICP channel

- 6 : Digital I/O port
- 7 : Incremental counter channel

3.4.1.3 `xsd__unsignedLong MSXExxxx__AcquisitionGetChannelInfoResponse::ulHwPosition`

3.4.1.4 `xsd__unsignedLong MSXExxxx__AcquisitionGetChannelInfoResponse::ulChannelIndex`

3.5 MSXExxxx__AcquisitionSequenceInitAndStartChannelListParam Struct Reference

Data Fields

- `xsd__unsignedLong ulChannelList [16]`

The meaning of this field is defined in the related header of the function who use this type.

3.5.1 Field Documentation

3.5.1.1 `xsd__unsignedLong MSXExxxx__AcquisitionSequenceInitAndStartChannelListParam::ulChannelList[16]`

3.6 MSXExxxx__FileResponse Struct Reference

Data Fields

- struct `DefaultResponse sResponse`

return values.

- struct `ByteArray sArray`

Dynamic Array of byte.

- `xsd__unsignedLong ulEOF`

flag indicating end of file.

3.6.1 Field Documentation

3.6.1.1 struct DefaultResponse MSXExxxx__FileResponse::sResponse

3.6.1.2 struct ByteArray MSXExxxx__FileResponse::sArray

3.6.1.3 xsd__unsignedLong MSXExxxx__FileResponse::ulEOF

3.7 MSXExxxx__Response Struct Reference

Data Fields

- [xsd__int iReturnValue](#)

return value of the call :

- [xsd__int syserrno](#)

System-error code (the value of the libc "errno" code).

3.7.1 Field Documentation

3.7.1.1 xsd__int MSXExxxx__Response::iReturnValue

- 0 means the remote function performed OK
- -1 means a system error occurred, the meaning of other values is function dependant and should be defined in the related header

3.7.1.2 xsd__int MSXExxxx__Response::syserrno

3.8 MSXExxxx__TemperatureGetChannelSensorClassResponse Struct Reference

Data Fields

- struct [DefaultResponse sResponse](#)

Default return values.

- [xsd__unsignedLong ulType](#) [16]

The meaning of this field is defined in the related header of the function who use this type.

3.8.1 Field Documentation

3.8.1.1 struct `DefaultResponse` `MSXExxxx__TemperatureGetChannelSensorClassResponse::sResponse`

3.8.1.2 `xsd__unsignedLong` `MSXExxxx__TemperatureGetChannelSensorClassResponse::ulType[16]`

3.9 MSXExxxx__TemperatureGetConfigurationResponse Struct Reference

Data Fields

- struct `DefaultResponse` `sResponse`
Default return values.
- `xsd__unsignedLong` `ulClass`
The meaning of this field is defined in the related header of the function who use this type.
- `xsd__unsignedLong` `ulType`
The meaning of this field is defined in the related header of the function who use this type.
- `xsd__unsignedLong` `ulBaseSamplingRate`
The meaning of this field is defined in the related header of the function who use this type.

3.9.1 Field Documentation

3.9.1.1 struct `DefaultResponse` `MSXExxxx__TemperatureGetConfigurationResponse::sResponse`

3.9.1.2 `xsd__unsignedLong` `MSXExxxx__TemperatureGetConfigurationResponse::ulClass`

3.9.1.3 `xsd__unsignedLong` `MSXExxxx__TemperatureGetConfigurationResponse::ulType`

3.9.1.4 `xsd__unsignedLong` `MSXExxxx__TemperatureGetConfigurationResponse::ulBaseSamplingRate`

3.10 MSXExxxx__unsignedLongResponse Struct Reference

Data Fields

- struct `DefaultResponse` `sResponse`
Default return values.
- `xsd__unsignedLong` `ulValue`
The meaning of this value is defined in the related header of the function who use this type.

3.10.1 Field Documentation

3.10.1.1 struct [DefaultResponse](#) [MSXExxxx__unsignedLongResponse::sResponse](#)

3.10.1.2 [xsd__unsignedLong](#) [MSXExxxx__unsignedLongResponse::ulValue](#)

3.11 MSXExxxx__unsignedLongTimeStampResponse Struct Reference

Data Fields

- struct [DefaultResponse](#) [sResponse](#)
Default return values.
- [xsd__unsignedLong](#) [ulValue](#)
the meaning of this value is defined in the related header of the function who use this type
- [xsd__unsignedLong](#) [ulTimeStampLow](#)
the meaning of this value is defined in the related header of the function who use this type
- [xsd__unsignedLong](#) [ulTimeStampHigh](#)
the meaning of this value is defined in the related header of the function who use this type

3.11.1 Field Documentation

3.11.1.1 struct [DefaultResponse](#) [MSXExxxx__unsignedLongTimeStampResponse::sResponse](#)

3.11.1.2 [xsd__unsignedLong](#) [MSXExxxx__unsignedLongTimeStampResponse::ulValue](#)

3.11.1.3 [xsd__unsignedLong](#) [MSXExxxx__unsignedLongTimeStampResponse::ulTimeStampLow](#)

3.11.1.4 [xsd__unsignedLong](#) [MSXExxxx__unsignedLongTimeStampResponse::ulTimeStampHigh](#)

3.12 MXCommon__ByteArrayResponse Struct Reference

Response containing a C-type string.

Data Fields

- struct [DefaultResponse](#) [sResponse](#)
Default return values.
- struct [ByteArray](#) [sArray](#)
Dynamic Array of byte - encapsulates C-type strings.

3.12.1 Field Documentation

3.12.1.1 struct `DefaultResponse MXCommon__ByteArrayResponse::sResponse`

3.12.1.2 struct `ByteArray MXCommon__ByteArrayResponse::sArray`

3.13 MXCommon__FileResponse Struct Reference

Response containing a chunk of a file.

Data Fields

- struct `DefaultResponse sResponse`
return values.
- struct `ByteArray sArray`
Dynamic Array of byte.
- `xsd__unsignedLong ulEOF`
flag indicating end of file.

3.13.1 Field Documentation

3.13.1.1 struct `DefaultResponse MXCommon__FileResponse::sResponse`

3.13.1.2 struct `ByteArray MXCommon__FileResponse::sArray`

3.13.1.3 `xsd__unsignedLong MXCommon__FileResponse::ulEOF`

3.14 MXCommon__GetAutoConfigurationFileResponse Struct Reference

Data Fields

- struct `DefaultResponse sResponse`
Default return values.
- struct `ByteArray bArray`
Array of byte of the file.
- `xsd__unsignedLong ulEOF`
End of file flag.

3.14.1 Field Documentation

3.14.1.1 struct DefaultResponse MXCommon__GetAutoConfigurationFileResponse::sResponse

3.14.1.2 struct ByteArray MXCommon__GetAutoConfigurationFileResponse::bArray

3.14.1.3 xsd__unsignedLong MXCommon__GetAutoConfigurationFileResponse::ulEOF

3.15 MXCommon__GetEthernetLinksStatesResponse Struct Reference

Data Fields

- struct [DefaultResponse](#) sResponse
Default return values.
- struct [sGetEthernetLinksStatesPort](#) sPort0
- struct [sGetEthernetLinksStatesPort](#) sPort1

3.15.1 Field Documentation

3.15.1.1 struct DefaultResponse MXCommon__GetEthernetLinksStatesResponse::sResponse

3.15.1.2 struct sGetEthernetLinksStatesPort MXCommon__-
GetEthernetLinksStatesResponse::sPort0

3.15.1.3 struct sGetEthernetLinksStatesPort MXCommon__-
GetEthernetLinksStatesResponse::sPort1

3.16 MXCommon__GetHardwareTriggerFilterTimeResponse Struct Reference

Data Fields

- struct [DefaultResponse](#) sResponse
Default return values.
- [xsd__unsignedLong](#) ulFilterTime
Hardware filter time (step of 250ns).
- [xsd__unsignedLong](#) ulInfo01
Reserved.
- [xsd__unsignedLong](#) ulInfo02
Reserved.

3.16.1 Field Documentation

- 3.16.1.1 struct `DefaultResponse MXCommon__GetHardwareTriggerFilterTimeResponse::sResponse`
- 3.16.1.2 `xsd__unsignedLong MXCommon__GetHardwareTriggerFilterTimeResponse::ulFilterTime`
- 3.16.1.3 `xsd__unsignedLong MXCommon__GetHardwareTriggerFilterTimeResponse::ulInfo01`
- 3.16.1.4 `xsd__unsignedLong MXCommon__GetHardwareTriggerFilterTimeResponse::ulInfo02`

3.17 MXCommon__GetHardwareTriggerStateResponse Struct Reference

Data Fields

- struct `DefaultResponse sResponse`
Default return values.
- `xsd__unsignedLong ulState`
0 : Trigger input is low / 1 : Trigger input is high
- `xsd__unsignedLong ulInfo01`
Reserved.
- `xsd__unsignedLong ulInfo02`
Reserved.

3.17.1 Field Documentation

- 3.17.1.1 struct `DefaultResponse MXCommon__GetHardwareTriggerStateResponse::sResponse`
- 3.17.1.2 `xsd__unsignedLong MXCommon__GetHardwareTriggerStateResponse::ulState`
- 3.17.1.3 `xsd__unsignedLong MXCommon__GetHardwareTriggerStateResponse::ulInfo01`
- 3.17.1.4 `xsd__unsignedLong MXCommon__GetHardwareTriggerStateResponse::ulInfo02`

3.18 MXCommon__GetModuleTemperatureValueAndStatusResponse Struct Reference

Data Fields

- struct `DefaultResponse sResponse`
Default return value.
- `xsd__double dTemperatureValue`

Temperature value.

- [xsd__unsignedLong ulTemperatureStatus](#)

Temperature status.

- [xsd__unsignedLong ulInfo](#)

Reserved.

3.18.1 Field Documentation

3.18.1.1 `struct DefaultResponse MXCommon__ - GetModuleTemperatureValueAndStatusResponse::sResponse`

3.18.1.2 `xsd__double MXCommon__ - GetModuleTemperatureValueAndStatusResponse::dTemperatureValue`

3.18.1.3 `xsd__unsignedLong MXCommon__ - GetModuleTemperatureValueAndStatusResponse::ulTemperatureStatus`

3.18.1.4 `xsd__unsignedLong MXCommon__ - GetModuleTemperatureValueAndStatusResponse::ulInfo`

3.19 MXCommon__GetTimeResponse Struct Reference

Data Fields

- `struct DefaultResponse sResponse`

Default return values.

- [xsd__unsignedLong ulLowTime](#)

Number of microseconds since the begin of the second.

- [xsd__unsignedLong ulHighTime](#)

Number of seconds since the Epoch (1st January,1970).

3.19.1 Field Documentation

3.19.1.1 `struct DefaultResponse MXCommon__GetTimeResponse::sResponse`

3.19.1.2 `xsd__unsignedLong MXCommon__GetTimeResponse::ulLowTime`

3.19.1.3 `xsd__unsignedLong MXCommon__GetTimeResponse::ulHighTime`

3.20 MXCommon__GetUpTimeResponse Struct Reference

Data Fields

- `struct DefaultResponse sResponse`

Default return value.

- [xsd__unsignedLong ulUpTime](#)

Reserved.

3.20.1 Field Documentation

3.20.1.1 [struct DefaultResponse MXCommon__GetUpTimeResponse::sResponse](#)

3.20.1.2 [xsd__unsignedLong MXCommon__GetUpTimeResponse::ulUpTime](#)

3.21 MXCommon__Response Struct Reference

contains return values

Data Fields

- [xsd__int iReturnValue](#)

return value of the call :

- 0 success
- -1 a system error occurred, the meaning of other values is function dependent and should be defined in the related header.

- [xsd__int syserrno](#)

system-error code (the value of the libc "errno" code, see [MXCommon__Strerror\(\)](#)).

3.21.1 Field Documentation

3.21.1.1 [xsd__int MXCommon__Response::iReturnValue](#)

3.21.1.2 [xsd__int MXCommon__Response::syserrno](#)

3.22 MXCommon__TestCustomerIDResponse Struct Reference

Data Fields

- [struct DefaultResponse sResponse](#)

Default return values.

- [struct ByteArray bValueArray](#)

non encrypted value

- [struct ByteArray bCryptedValueArray](#)

encrypted value

3.22.1 Field Documentation

3.22.1.1 struct DefaultResponse MXCommon__TestCustomerIDResponse::sResponse

3.22.1.2 struct ByteArray MXCommon__TestCustomerIDResponse::bValueArray

3.22.1.3 struct ByteArray MXCommon__TestCustomerIDResponse::bCryptedValueArray

3.23 MXCommon__unsignedLongResponse Struct Reference

Response containing a numerical value (ex: return code).

Data Fields

- struct [DefaultResponse](#) sResponse

Default return values.

- [xsd__unsignedLong](#) ulValue

The meaning of this value is defined in the related header of the function who use this type.

3.23.1 Field Documentation

3.23.1.1 struct DefaultResponse MXCommon__unsignedLongResponse::sResponse

3.23.1.2 [xsd__unsignedLong](#) MXCommon__unsignedLongResponse::ulValue

3.24 sGetEthernetLinksStatesPort Struct Reference

Data Fields

- [xsd__unsignedLong](#) ulState
- [xsd__unsignedLong](#) ulSpeed
- [xsd__unsignedLong](#) ulDuplex
- [xsd__unsignedLong](#) ulInfo1
- [xsd__unsignedLong](#) ulInfo2

3.24.1 Field Documentation

3.24.1.1 `xsd__unsignedLong sGetEthernetLinksStatesPort::ulState`

3.24.1.2 `xsd__unsignedLong sGetEthernetLinksStatesPort::ulSpeed`

3.24.1.3 `xsd__unsignedLong sGetEthernetLinksStatesPort::ulDuplex`

3.24.1.4 `xsd__unsignedLong sGetEthernetLinksStatesPort::ulInfo1`

3.24.1.5 `xsd__unsignedLong sGetEthernetLinksStatesPort::ulInfo2`

3.25 UnsignedLongArray Struct Reference

Dynamic Array of unsigned long.

Data Fields

- `xsd__unsignedLong * __ptr`
pointer of unsigned Long
- `int __size`
size of the unsigned Long array in Bytes
- `int __offset`
not used

3.25.1 Field Documentation

3.25.1.1 `xsd__unsignedLong* UnsignedLongArray::__ptr`

3.25.1.2 `int UnsignedLongArray::__size`

3.25.1.3 `int UnsignedLongArray::__offset`

3.26 UnsignedShortArray Struct Reference

Dynamic Array of unsigned short.

Data Fields

- `xsd__unsignedShort * __ptr`
pointer of unsigned short
- `int __size`
size of the unsigned short array in Bytes

- int [__offset](#)
not used

3.26.1 Field Documentation

3.26.1.1 `xsd__unsignedShort* UnsignedShortArray::__ptr`

3.26.1.2 `int UnsignedShortArray::__size`

3.26.1.3 `int UnsignedShortArray::__offset`

3.27 xsd__base64Binary Struct Reference

Dynamic Array of byte for input use.

Data Fields

- unsigned char * [__ptr](#)
pointer of byte
- int [__size](#)
size of the byte array

3.27.1 Field Documentation

3.27.1.1 `unsigned char* xsd__base64Binary::__ptr`

3.27.1.2 `int xsd__base64Binary::__size`

Chapter 4

File Documentation

4.1 MSXE321x_public_doc.h File Reference

Data Structures

- struct [xsd__base64Binary](#)
Dynamic Array of byte for input use.
- struct [UnsignedShortArray](#)
Dynamic Array of unsigned short.
- struct [UnsignedLongArray](#)
Dynamic Array of unsigned long.
- struct [ByteArray](#)
Dynamic Array of byte - encapsulates C-type strings.
- struct [DefaultResponse](#)
- struct [MXCommon__Response](#)
contains return values
- struct [MXCommon__ByteArrayResponse](#)
Response containing a C-type string.
- struct [MXCommon__FileResponse](#)
Response containing a chunk of a file.
- struct [MXCommon__unsignedLongResponse](#)
Response containing a numerical value (ex: return code).
- struct [sGetEthernetLinksStatesPort](#)
- struct [MXCommon__GetEthernetLinksStatesResponse](#)
- struct [MXCommon__GetModuleTemperatureValueAndStatusResponse](#)
- struct [MXCommon__GetHardwareTriggerFilterTimeResponse](#)
- struct [MXCommon__GetHardwareTriggerStateResponse](#)

- struct [MXCommon__TestCustomerIDResponse](#)
- struct [MXCommon__GetTimeResponse](#)
- struct [MXCommon__GetUpTimeResponse](#)
- struct [MXCommon__GetAutoConfigurationFileResponse](#)
- struct [MSXExxxx__Response](#)
- struct [MSXExxxx__unsignedLongResponse](#)
- struct [MSXExxxx__FileResponse](#)
- struct [MSXExxxx__unsignedLongTimeStampResponse](#)
- struct [MSXExxxx__AcquisitionGetChannelInfoResponse](#)
- struct [MSXExxxx__AcquisitionAutoRefreshGetValuesResponse](#)
- struct [MSXExxxx__AcquisitionSequenceInitAndStartChannelListParam](#)
- struct [MSXExxxx__TemperatureGetChannelSensorClassResponse](#)
- struct [MSXExxxx__TemperatureGetConfigurationResponse](#)

Typedefs

- typedef char * [xsd__string](#)
encode xsd__string value as the xsd:string schema type
- typedef char [xsd__char](#)
encode xsd__string value as the xsd:char schema type
- typedef float [xsd__float](#)
encode xsd__float value as the xsd:float schema type
- typedef double [xsd__double](#)
encode xsd__double value as the xsd:double schema type
- typedef int [xsd__int](#)
encode xsd__int value as the xsd:int schema type
- typedef long [xsd__long](#)
encode xsd__long value as the xsd:long schema type
- typedef unsigned char [xsd__unsignedByte](#)
encode xsd__unsignedByte value as the xsd:unsignedByte schema type
- typedef unsigned int [xsd__unsignedInt](#)
encode xsd__unsignedInt value as the xsd:unsignedInt schema type
- typedef unsigned short int [xsd__unsignedShort](#)
encode xsd__unsignedShort value as the xsd:unsignedShort schema type
- typedef unsigned long [xsd__unsignedLong](#)
encode xsd__unsignedLong value as the xsd:unsignedLong schema type

Functions

- `int MXCommon__GetModuleType (void *__, struct MXCommon__ByteArrayResponse *Response)`
This function return the type of the MSX-E Module.
- `int MXCommon__GetHostname (void *__, struct MXCommon__ByteArrayResponse *Response)`
This function return the hostname of the MSX-E Module.
- `int MXCommon__SetHostname (struct xsd__base64Binary *bHostname, struct MXCommon__Response *Response)`
This function allows to set the hostname of the MSX-E Module.
- `int MXCommon__GetClientConnections (void *__, struct MXCommon__ByteArrayResponse *Response)`
This function return the client connection list.
- `int MXCommon__Sterror (xsd__int errnum, struct MXCommon__ByteArrayResponse *Response)`
Call the libc strerror() on the remote device (actually this is a call to strerror_r()).
- `int MXCommon__Reboot (void *__, struct MXCommon__Response *Response)`
Ask the MSX-E module to reboot.
- `int MXCommon__ResetAllIOFunctionalities (xsd__unsignedLong ulOption, struct MXCommon__Response *Response)`
Reset the I/O functionalities of the MSX-E system.
- `int MXCommon__DataseverRestart (xsd__unsignedLong ulAction, xsd__unsignedLong ulOption, struct MXCommon__Response *Response)`
Restart the data-server service.
- `int MXCommon__GetEthernetLinksStates (void *__, struct MXCommon__GetEthernetLinksStatesResponse *Response)`
Get MSX-E Ethernet links states.
- `int MXCommon__GetModuleTemperatureValueAndStatus (xsd__unsignedLong ulOption, struct MXCommon__GetModuleTemperatureValueAndStatusResponse *Response)`
Read the temperature on the module.
- `int MXCommon__SetModuleTemperatureWarningLevels (xsd__double dMinimalWarningLevel, xsd__double dMaximalWarningLevel, xsd__unsignedLong ulOption, struct MXCommon__Response *Response)`
Set the temperature warning level on the module.
- `int MXCommon__SetHardwareTriggerFilterTime (xsd__unsignedLong ulFilterTime, xsd__unsignedLong ulOption, struct MXCommon__Response *Response)`
Sets the filter time for the hardware trigger input in steps of 250 ns (max value: 65535).
- `int MXCommon__GetHardwareTriggerFilterTime (xsd__unsignedLong ulOption, struct MXCommon__GetHardwareTriggerFilterTimeResponse *Response)`

Get the filter time for the hardware trigger input.

- `int MXCommon__GetHardwareTriggerState (xsd__unsignedLong ulOption, struct MXCommon__GetHardwareTriggerStateResponse *Response)`

Get the hardware trigger state after the filter.

- `int MXCommon__SetCustomerKey (struct xsd__base64Binary *bKey, struct xsd__base64Binary *bPublicKey, struct MXCommon__Response *Response)`

Set the Customer key.

- `int MXCommon__TestCustomerID (void *_ , struct MXCommon__TestCustomerIDResponse *Response)`

Test the Customer ID (if the module has the right customer Key).

- `int MXCommon__SetTime (xsd__unsignedLong ulLowTime, xsd__unsignedLong ulHighTime, struct MXCommon__Response *Response)`

Set the time on the module.

- `int MXCommon__SysToHardwareClock (void *_ , struct MXCommon__Response *Response)`

Set the hardware clock (if present) to the current system time.

- `int MXCommon__HardwareClockToSys (void *_ , struct MXCommon__Response *Response)`

Set the system time from the hardware clock (if present).

- `int MXCommon__GetTime (void *_ , struct MXCommon__GetTimeResponse *Response)`

Get the time on the module.

- `int MXCommon__GetUpTime (void *_ , struct MXCommon__GetUpTimeResponse *Response)`

Ask the MSX-E module uptime (number of seconds since the last boot).

- `int MXCommon__GetAutoConfigurationFile (void *_ , struct MXCommon__GetAutoConfigurationFileResponse *Response)`

Get the auto configuration file of the module.

- `int MXCommon__SetAutoConfigurationFile (struct xsd__base64Binary *ByteArrayInput, xsd__unsignedLong ulEOF, struct MXCommon__Response *Response)`

Set the auto configuration file of the module.

- `int MXCommon__StartAutoConfiguration (void *_ , struct MXCommon__ByteArrayResponse *Response)`

start/Restart the auto configuration

- `int MXCommon__InitAndStartSynchroTimer (xsd__unsignedLong ulTimeBase, xsd__unsignedLong ulReloadValue, xsd__unsignedLong ulNbrOfCycle, xsd__unsignedLong ulGenerateTriggerMode, xsd__unsignedLong ulOption01, xsd__unsignedLong ulOption02, xsd__unsignedLong ulOption03, xsd__unsignedLong ulOption04, struct MXCommon__Response *Response)`

Initialises and starts the synchronisation timer of the module (not already available on all module).

- `int MXCommon__StopAndReleaseSynchroTimer (xsd__unsignedLong ulOption01, struct MXCommon__Response *Response)`

start/Restart the synchronisation timer (not already available on all module)

- `int MXCommon__GetConfigurationBackupFile (void ___, struct MXCommon__FileResponse *Response)`
Download a configuration backup file from the module.
- `int MXCommon__ApplyConfigurationBackupFile (struct xsd__base64Binary *ByteArrayInput, xsd__unsignedLong ulEOF, struct MXCommon__Response *Response)`
Upload a new configuration on the module.
- `int MXCommon__ChangePassword (struct xsd__base64Binary *PreviousUser, struct xsd__base64Binary *PreviousPassword, struct xsd__base64Binary *NewUser, struct xsd__base64Binary *NewPassword, struct MXCommon__Response *Response)`
Set a new id/password.
- `int MXCommon__GetSubSystemState (xsd__unsignedLong SubsystemID, struct MXCommon__unsignedLongResponse *Response)`
Returns the current state of the specified sub-system.
- `int MXCommon__GetSubsystemIDFromName (struct xsd__base64Binary *SubsystemName, struct MXCommon__unsignedLongResponse *Response)`
Returns the ID of the sub-system of symbolic name "SubsystemName".
- `int MXCommon__GetStateIDFromName (xsd__unsignedLong SubsystemID, struct xsd__base64Binary *StateName, struct MXCommon__unsignedLongResponse *Response)`
Returns the ID of the state of symbolic name "StateName" of the sub-system of ID "SubsystemID".
- `int MXCommon__GetSubsystemNameFromID (xsd__unsignedLong SubsystemID, struct MXCommon__ByteArrayResponse *Response)`
Returns the symbolic name of the sub-system of numerical ID "SubsystemName".
- `int MXCommon__GetStateNameFromID (xsd__unsignedLong SubsystemID, xsd__unsignedLong StateID, struct MXCommon__ByteArrayResponse *Response)`
Returns the symbolic name of the state of numerical ID "StateID" of the sub-system of ID "SubsystemID".
- `int MXCommon__GetOptionInformation (void ___, xsd__unsignedLong ulOption01, xsd__unsignedLong ulOption02, struct MXCommon__ByteArrayResponse *Response)`
Enables to get information about the options available on the system.
- `int MXCommon__SetToMaster (void ___, xsd__unsignedLong ulState, xsd__unsignedLong ulOption01, xsd__unsignedLong ulOption02, struct MXCommon__Response *Response)`
Writes if the MSXE has to be always set to master The master mode (when enabled) make the system always detected as master.
- `int MXCommon__GetSynchronizationStatus (void ___, xsd__unsignedLong ulOption01, xsd__unsignedLong ulOption02, struct MXCommon__unsignedLongResponse *Response)`
Reads the status of the synchronization for the corresponding MSXE The master mode (when enabled) make the system always detected as master.
- `int MSXExxxx__AcquisitionGetNumberOfChannels (xsd__unsignedLong ulOption1, struct MSXExxxx__unsignedLongResponse *Response)`

Return the number of acquisition channels.

- `int MSXExxxx__AcquisitionGetChannelInfo (xsd__unsignedLong ulChannel, xsd__unsignedLong ulOption1, struct MSXExxxx__AcquisitionGetChannelInfoResponse *Response)`

Return the selected acquisition channel type and hardware position.

- `int MSXExxxx__AcquisitionAutoRefreshInitAndStart (xsd__unsignedLong ulChannelMask, xsd__unsignedLong ulAverageValue, xsd__unsignedLong ulRefreshTime, xsd__unsignedLong ulRefreshTimeUnit, xsd__unsignedLong ulTriggerMask, xsd__unsignedLong ulTriggerMode, xsd__unsignedLong ulHardwareTriggerEdge, xsd__unsignedLong ulHardwareTriggerCount, xsd__unsignedLong ulByTriggerNbrOfSeqToAcquire, xsd__unsignedLong ulDataFormat, xsd__unsignedLong ulForceStart, xsd__unsignedLong ulOption1, xsd__unsignedLong ulOption2, xsd__unsignedLong ulOption3, struct MSXExxxx__Response *Response)`

Starts an autorefresh acquisition using provided configuration.

- `int MSXExxxx__AcquisitionAutoRefreshGetValues (xsd__unsignedLong ulBlocking, struct MSXExxxx__AcquisitionAutoRefreshGetValuesResponse *Response)`

Reads the values acquired in auto refresh mode.

- `int MSXExxxx__AcquisitionAutoRefreshStopAndRelease (void *_ , struct MSXExxxx__Response *Response)`

Stops the current auto refresh acquisition.

- `int MSXExxxx__AcquisitionSequenceInitAndStart (xsd__unsignedLong ulNbrOfChannel, struct MSXExxxx__AcquisitionSequenceInitAndStartChannelListParam *psChannelList, xsd__unsignedLong ulAcquisitionTime, xsd__unsignedLong ulAcquisitionTimeUnit, xsd__unsignedLong ulNbrOfSequence, xsd__unsignedLong ulNbrMaxSequenceToTransfer, xsd__unsignedLong ulTriggerMask, xsd__unsignedLong ulTriggerMode, xsd__unsignedLong ulHardwareTriggerEdge, xsd__unsignedLong ulHardwareTriggerCount, xsd__unsignedLong ulByTriggerNbrOfSeqToAcquire, xsd__unsignedLong ulDataFormat, xsd__unsignedLong ulForceStart, xsd__unsignedLong ulOption1, xsd__unsignedLong ulOption2, xsd__unsignedLong ulOption3, struct MSXExxxx__Response *Response)`

Initialises and starts the sequence acquisition mode.

- `int MSXExxxx__AcquisitionSequenceStopAndRelease (void *_ , struct MSXExxxx__Response *Response)`

Stop and release the sequence acquisition mode.

- `int MSXExxxx__TemperatureGetNumberOfChannels (xsd__unsignedLong ulOption1, struct MSXExxxx__unsignedLongResponse *Response)`

Return the number of temperature channels.

- `int MSXExxxx__TemperatureGetChannelSensorClass (xsd__unsignedLong ulOption1, struct MSXExxxx__TemperatureGetChannelSensorClassResponse *Response)`

Return the type of the temperature channels.

- `int MSXExxxx__TemperatureSetChannelType (xsd__unsignedLong ulChannel, xsd__unsignedLong ulType, xsd__unsignedLong ulOption1, struct MSXExxxx__Response *Response)`

Temperature sensor type selection for the selected channel.

- int [MSXExxxx__TemperatureSetSamplingRate](#) (xsd__unsignedLong ulChannelGroup, [xsd__unsignedLong](#) ulBaseSamplingRate, [xsd__unsignedLong](#) ulOption1, struct [MSXExxxx__Response](#) *Response)
Temperature acquisition sampling rate selection.
- int [MSXExxxx__TemperatureGetConfiguration](#) (xsd__unsignedLong ulChannel, [xsd__unsignedLong](#) ilOption1, struct [MSXExxxx__TemperatureGetConfigurationResponse](#) *Response)
Get the selected temperature channel current configuration.
- int [MSXExxxx__TemperatureDiagnostic](#) (xsd__unsignedLong ulChannel, [xsd__unsignedLong](#) ulOption1, struct [MSXExxxx__unsignedLongResponse](#) *Response)
Temperature line diagnostic.

4.1.1 Typedef Documentation

- 4.1.1.1 typedef char* [xsd__string](#)
- 4.1.1.2 typedef char [xsd__char](#)
- 4.1.1.3 typedef float [xsd__float](#)
- 4.1.1.4 typedef double [xsd__double](#)
- 4.1.1.5 typedef int [xsd__int](#)
- 4.1.1.6 typedef long [xsd__long](#)
- 4.1.1.7 typedef unsigned char [xsd__unsignedByte](#)
- 4.1.1.8 typedef unsigned int [xsd__unsignedInt](#)
- 4.1.1.9 typedef unsigned short int [xsd__unsignedShort](#)
- 4.1.1.10 typedef unsigned long [xsd__unsignedLong](#)

4.1.2 Function Documentation

- 4.1.2.1 int [MXCommon__GetModuleType](#) (void * _, struct [MXCommon__ByteArrayResponse](#) * *Response*)

Parameters

- [in] _ : no input parameter
- [out] *Response*
 - sArray : Module type string
 - sResponse Composed of iReturnValue and syserrno

Return values

- SOAP_OK* SOAP call success
- otherwise* SOAP protocol error

4.1.2.2 int MXCommon__GetHostname (void * __, struct MXCommon__ByteArrayResponse * Response)

Parameters

- [in] *__* : no input parameter
- [out] **Response** • sArray : Hostname of the module
- iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

4.1.2.3 int MXCommon__SetHostname (struct xsd__base64Binary * bHostname, struct MXCommon__Response * Response)

Parameters

- [in] **bHostname** : Hostname
- [out] **Response** • iReturnValue : Return value
- 0 : success
 - -1: system error (see syserrno)
 - syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

4.1.2.4 int MXCommon__GetClientConnections (void * __, struct MXCommon__ByteArrayResponse * Response)

Parameters

- [in] *__* : no input parameter
- [out] **Response** • sArray : string containing the list of connected clients.
- sResponse Composed of iReturnValue and syserrno

The sArray string is of the form IP-Address:first connection-second connection---- IP-Address:first connection-second connection----

Sample: 172.16.3.43:8989-5555 172.16.3.200:8989

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

4.1.2.5 int MXCommon__Strerror (xsd__int *errnum*, struct MXCommon__ByteArrayResponse * *Response*)

Usually SOAP functions return this value in a variable named syserror, which is meaningful only when the function return value, usually called iReturnValue, indicate an error (that is, have a value of -1 or -100, depending of the case).

Parameters

[in] **errnum** : Error number

[out] **Response** • sArray : See the description below.

- sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno).
- sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

STRERROR(3)
STRERROR(3)

Linux Programmer's Manual

NAME

strerror, strerror_r - return string describing error code

SYNOPSIS

```
#include <string.h>
```

```
char *strerror(int errnum);
```

```
#define _XOPEN_SOURCE 600
#include <string.h>
```

```
int strerror_r(int errnum, char *buf, size_t n);
```

DESCRIPTION

The `strerror()` function returns a string describing the error code passed in the argument `errnum`, possibly using the `LC_MESSAGES` part of the current locale to select the appropriate language.

This string must not be modified by the application, but may be modified by a subsequent call to `perror()` or `strerror()`. No library function will modify this string.

The `strerror_r()` function is similar to `strerror()`, but is thread safe. It returns the string in the user-supplied buffer `buf` of length `n`.

RETURN VALUE

The `strerror()` function returns the appropriate error description string, or an unknown error message if the error code is unknown.

The value of `errno` is not changed for a successful call, and is set to a non-zero value upon error.

The `strerror_r()` function returns 0 on success and -1 on failure, setting `errno`.

ERRORS

EINVAL The value of `errnum` is not a valid error number.

ERANGE Insufficient storage was supplied to contain the error description string.

CONFORMING TO

SVID 3, POSIX, 4.3BSD, ISO/IEC 9899:1990 (C89).

`strerror_r()` with prototype as given above is specified by SUSv3, and was in use under Digital Unix and HP Unix. An incompatible function, with prototype

```
char *strerror_r(int errnum, char *buf, size_t n);
```

is a GNU extension used by glibc (since 2.0), and must be regarded as obsolete in view of SUSv3.
 The GNU version may, but need not, use the user-supplied buffer.
 If it does, the result may be truncated in case the supplied buffer is too small.
 The result is always NUL-terminated.

SEE ALSO
 errno(3), perror(3), strsignal(3)

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

4.1.2.6 int MXCommon__Reboot (void * _, struct MXCommon__Response * *Response*)

Parameters

[in] *_* : no input parameter
 [out] *Response* • *iReturnValue* : Return value
 – 0 : success
 – -1 : system error (see syserrno)
 • *syserrno* : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

4.1.2.7 int MXCommon__ResetAllIOFunctionalities (xsd__unsignedLong *ulOption*, struct MXCommon__Response * *Response*)

The behavior of the function depends on the MSX-E system that is used.

On MSX-E3511: Stop the watchdogs and stop the generators
 On MSX-E3601: Stop the sequence acquisition and stop the calibration
 On MSX-E3701: Stop the acquisition

Parameters

[in] *ulOption* Reserved. Set to 0
 [out] *Response* *iReturnValue*
 • 0 The remote function performed OK
 • -1 Internal system error occurred. See value of syserrno
 • -100 Function not supported by the system
 syserrno system error code (the value of the libc "errno" code)

Return values

0 *SOAP_OK*
Others See SOAP error

4.1.2.8 int MXCommon__DataserverRestart (xsd__unsignedLong ulAction, xsd__unsignedLong ulOption, struct MXCommon__Response * Response)

Parameters

- [in] **ulAction** : action
- 0: normal restart
 - 1: with cache file reset
 - 2: with cache file deletion
- [in] **ulOption** : Reserved
- [out] **Response** • iReturnValue : Return value
- 0 : success
 - -1: system error (see syserrno)
 - syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

Note

(revision>6386) Depending on the system type, can be used to restart the data-recv service as well. In this case, parameter action is ignored.

4.1.2.9 int MXCommon__GetEthernetLinksStates (void * _, struct MXCommon__GetEthernetLinksStatesResponse * Response)

Parameters

- [in] **_** : no input parameter
- [out] **Response** Structure that contains the MSX-E Ethernet links states and errors:
- sResponse.iReturnValue**
- **0** The remote function performed OK
 - **-1** System error occurred
 - **-2** Fail to get Ethernet links states
 - **-100** Internal system error occurred. See value of syserrno
- sResponse.syserrno** system error code (the value of the libc "errno" code)
- sPort0: Fisrt port informations**
- **ulState**
 - **0** Link down
 - **1** Link up
 - **ulSpeed**
 - **10** 10 Mb/s
 - **100** 100 Mb/s
 - **ulDuplex**
 - **0** Half duplex
 - **1** Full duplex

- **ulInfo1** Reserved
- **ulInfo2** Reserved

sPort1: Second port informations

- **ulState**
 - **0** Link down
 - **1** Link up
- **ulSpeed**
 - **10** 10 Mb/s
 - **100** 100 Mb/s
- **ulDuplex**
 - **0** Half duplex
 - **1** Full duplex
- **ulInfo1** Reserved
- **ulInfo2** Reserved

Return values

0 SOAP_OK

Others See SOAP error

4.1.2.10 int MXCommon__GetModuleTemperatureValueAndStatus (xsd__unsignedLong ulOption, struct MXCommon__GetModuleTemperatureValueAndStatusResponse * Response)

Parameters

[in] **ulOption** : Reserved

[out] **Response** • sResponse.iReturnValue : Return value

- **0** : success
- **-1** : system error (see syserrno)
- sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Sterror\(\)](#).
 - dValue : Temperature value in Degree Celsius
- ulTemperatureStatus : Temperature Status :
 - TEMPERATURE_INITIAL = 0 : Temperature not ready
 - TEMPERATURE_TOLOW = 1 : Temperature too low !
 - TEMPERATURE_LOW = 2 : Temperature under the min warning value
 - TEMPERATURE_NOMINAL = 3 : Temperature in the nominal range
 - TEMPERATURE_HIGH = 4 : Temperature over the max warning value
 - TEMPERATURE_TOOHIGH = 5 : Temperature too high !

- ulInfo : Reserved

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

4.1.2.11 `int MXCommon__SetModuleTemperatureWarningLevels (xsd__double dMinimalWarningLevel, xsd__double dMaximalWarningLevel, xsd__unsignedLong ulOption, struct MXCommon__Response * Response)`

Parameters

- [in] *dMinimalWarningLevel* : Minimal temperature warning level in Degree : 5 to 60 Degree Celsius
- [in] *dMaximalWarningLevel* : Maximal temperature warning level in Degree : 5 to 60 Degree Celsius
- [in] *ulOption* : Reserved
- [out] *Response*
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

- SOAP_OK* SOAP call success
- otherwise* SOAP protocol error

4.1.2.12 `int MXCommon__SetHardwareTriggerFilterTime (xsd__unsignedLong ulFilterTime, xsd__unsignedLong ulOption, struct MXCommon__Response * Response)`

Sets the filter time for the hardware trigger input in steps of 250 ns (max value: 65535).

On the MSX-E3011 system, the step of the hardware trigger filter is **622ns**.

Parameters

- [in] *ulFilterTime* Filter time for the hardware trigger input in steps of 250ns (max value : 65535).
 - **0**: Disable the filter
 - **1**: Sets the filter time to 250 ns
 - **2**: Sets the filter time to 500 ns
 - ...
 - **65535**: Sets the filter time to 16 ms
- [in] *ulOption* Reserved. Set to 0
- [out] *Response* Response of the system
 - *sResponse.iReturnValue*
 - **0**: The remote function performed OK
 - **-1**: Internal system error occurred. See value of syserrno
 - *sResponse.syserrno* system error code (the value of the libc "errno" code)

Return values

- 0** SOAP_OK
- Others* See SOAP error

4.1.2.13 `int MXCommon__GetHardwareTriggerFilterTime (xsd__unsignedLong ulOption, struct MXCommon__GetHardwareTriggerFilterTimeResponse * Response)`

Get the filter time for the hardware trigger input in **250ns** step (max value : 65535).

On the MSX-E3011 system, the step of the hardware trigger filter is **622ns**.

Parameters

[in] *ulOption* Reserved. Set to 0

[out] *Response* Response of the system

- *ulFilterTime* filter time for the hardware trigger input
 - 0: filter disabled
 - 1: filter of 250ns
 - 2: filter of 500ns
 - ...
 - 65535: filter of 16ms
- *sResponse.iReturnValue*
 - 0: The remote function performed OK
 - -1: Internal system error occurred. See value of syserrno
- *sResponse.syserrno* system error code (the value of the libc "errno" code)

Return values

0 SOAP_OK

Others See SOAP error

4.1.2.14 `int MXCommon__GetHardwareTriggerState (xsd__unsignedLong ulOption, struct MXCommon__GetHardwareTriggerStateResponse * Response)`

Parameters

[in] *ulOption* : Reserved

[out] *Response* • *ulState* : Hardware trigger input state.

- 0: Hardware trigger input is low
- 1: Hardware trigger input is high.
- *sResponse.iReturnValue* : Return value
 - 0 : success
 - -1: system error (see syserrno)
- *sResponse.syserrno* : System-error code. The value of the libc "errno" code, see [MXCommon__Sterror\(\)](#).

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

4.1.2.15 `int MXCommon__SetCustomerKey (struct xsd__base64Binary * bKey, struct xsd__base64Binary * bPublicKey, struct MXCommon__Response * Response)`

Parameters

- [in] *bKey* : Customer key (only writable on the module) [32 bytes containing a AES key]
- [in] *bPublicKey* : IV (Initialisation vector) for the AES cryptography [16 bytes containing a AES key]
- [out] *Response*
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

4.1.2.16 `int MXCommon__TestCustomerID (void * _, struct MXCommon__TestCustomerIDResponse * Response)`

Parameters

- [in] *_* : No Input
- [out] *Response*
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - bValueArray : non encrypted value array [16 bytes of random data]
 - bCryptedValueArray : Encrypted value array [16 bytes of the encrypted random data]

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

4.1.2.17 `int MXCommon__SetTime (xsd__unsignedLong ulLowTime, xsd__unsignedLong ulHighTime, struct MXCommon__Response * Response)`

Parameters

- [in] *ulLowTime* : Number of microseconds since the begin of the second
- [in] *ulHighTime* : Number of seconds since the Epoch (1st January,1970)
- [out] *Response*
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

4.1.2.18 int MXCommon__SysToHardwareClock (void * _, struct MXCommon__Response * Response)

Parameters

[in] _ No input parameter
 [out] **Response** • sResponse.iReturnValue : Return value
 – 0 : success
 – -1: system error (see syserrno)
 • sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

If this function fails, it means the module does not have a hardware RTC, or the hardware is not functional. Check the "hwclock" subsystem status.

4.1.2.19 int MXCommon__HardwareClockToSys (void * _, struct MXCommon__Response * Response)

When the hardware clock is present, the system time is automatically set to it when the module becomes master on the inter-module synchronisation bus.

Parameters

[in] _ No input parameter
 [out] **Response** • sResponse.iReturnValue : Return value
 – 0 : success
 – -1: system error (see syserrno)
 • sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

If this function fails, it means the module does not have a hardware RTC, or the hardware is not functional. Check the "hwclock" subsystem status.

4.1.2.20 int MXCommon__GetTime (void * __, struct MXCommon__GetTimeResponse * Response)

Parameters

- [in] __ : No input parameter
- [out] **Response** • sResponse.iReturnValue : Return value
- 0 : success
 - -1: system error (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - ulLowTime : Number of microseconds since the begin of the second
 - ulHighTime : Number of seconds since the Epoch (1st January,1970)

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

4.1.2.21 int MXCommon__GetUpTime (void * __, struct MXCommon__GetUpTimeResponse * Response)

Parameters

- [in] __ : no input parameter
- [out] **Response** • sResponse.iReturnValue : Return value
- 0 : success
 - -1: system error (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - ulUpTime : Number of seconds since the last boot of the system.

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

4.1.2.22 int MXCommon__GetAutoConfigurationFile (void * __, struct MXCommon__GetAutoConfigurationFileResponse * Response)

Parameters

- [in] __ : No input parameter
- [out] **Response** • sResponse.iReturnValue : Return value
- 0 : success
 - -1: system error (see syserrno)
 - -100 : Error of the read of the auto configuration file
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - bArray : Array of Bytes of the file

- `ulEOF` : End of file flag

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

4.1.2.23 `int MXCommon__SetAutoConfigurationFile (struct xsd__base64Binary * ByteArrayInput, xsd__unsignedLong ulEOF, struct MXCommon__Response * Response)`

Parameters

[in] *ByteArrayInput* : Array of Bytes of the file

[in] *ulEOF* : End of file flag

[out] *Response* • `sResponse.iReturnValue` : Return value

– 0 : success

– -1: system error (see `syserrno`)

- `sResponse.syserrno` : System-error code. The value of the libc "errno" code, see [MXCommon__Sterror\(\)](#).

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

4.1.2.24 `int MXCommon__StartAutoConfiguration (void * _, struct MXCommon__ByteArrayResponse * Response)`

Parameters

[in] `_` : No input parameter

[out] *Response* • `sResponse.iReturnValue` : Return value

– 0 : success

– -1: system error (see `syserrno`)

- `sResponse.syserrno` : System-error code. The value of the libc "errno" code, see [MXCommon__Sterror\(\)](#).
- `sArray` : message returned by the auto configuration start

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

4.1.2.25 `int MXCommon__InitAndStartSynchroTimer (xsd__unsignedLong ulTimeBase, xsd__unsignedLong ulReloadValue, xsd__unsignedLong ulNbrOfCycle, xsd__unsignedLong ulGenerateTriggerMode, xsd__unsignedLong ulOption01, xsd__unsignedLong ulOption02, xsd__unsignedLong ulOption03, xsd__unsignedLong ulOption04, struct MXCommon__Response * Response)`

Parameters

[in] *ulTimeBase* : Time base of the timer (0 for us, 1 for ms, 2 for s)

- [in] ***ulReloadValue*** : Timer reload value (0 to 0xFFFF), minimum reload time is 5 us
- [in] ***ulNbrOfCycle*** : Number of timer cycle
 - 0: continuous
 - > 0: defined number of cycle
- [in] ***ulGenerateTriggerMode*** :
 - 0: Wait the time overflow to set the synchronisation trigger
 - 1: Set the synchronisation trigger by the start of the timer and after each time overflow
- [in] ***ulOption01*** : Define the source of the trigger
 - 0 : Trigger disabled
 - 1 : Enable the hardware digital input trigger
- [in] ***ulOption02*** : Define the edge of the hardware trigger who generates a trigger action
 - 1 : rising edge (Only if hardware trigger selected)
 - 2 : falling edge (Only if hardware trigger selected)
 - 3 : Both front (Only if hardware trigger selected)
- [in] ***ulOption03*** : Define the number of trigger events before the action occur
 - 1 : all trigger event start the action
 - max value : 65535
- [in] ***ulOption04*** : Reserved
- [out] ***Response***
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - -2: not available time base
 - -3: timer reload value can not be greater than 65535
 - -4: minimum time reload is 5 us
 - -5: Number of cycle can not be greater than 65535
 - -6: Generate trigger mode error
 - -100: Init timer error
 - -101: Start timer error
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#). May be ENOSYS : Function not implemented.

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

4.1.2.26 int MXCommon__StopAndReleaseSynchroTimer (xsd__unsignedLong ulOption01, struct MXCommon__Response * Response)

Parameters

- [in] ***ulOption01*** : Reserved
- [out] ***Response***
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - -100: Start/Stop timer error

- `sResponse.syserrno` : System-error code. The value of the libc "errno" code, see [MXCommon__Sterror\(\)](#). May be `ENOSYS` : Function not implemented.

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

4.1.2.27 `int MXCommon__GetConfigurationBackupFile (void * _, struct MXCommon__FileResponse * Response)`

Parameters

- [in] `_` : No input parameter
- [out] ***Response*** • `sResponse.iReturnValue` : Return value
- 0 : success
 - -1: system error (see `syserrno`) (see `syserrno`)
 - `sResponse.syserrno` : System-error code. The value of the libc "errno" code, see [MXCommon__Sterror\(\)](#).
 - `bArray` : Array of Bytes of the file
 - `ulEOF` : End of file flag

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

This function is designed to be called repeatedly until no more data is available. At this point the flag `ulEOF` is set.

Below is an example in pseudo-C.

```
int dummy;
struct MXCommon__FileResponse Response;
while(1)
{
    if ( MXCommon__GetConfigurationBackupFile(&dummy, &Response) != SOAP_OK)
    {
        // handle soap error
    }
    if (Response.iReturnValue)
    {
        // handle remote error (Response.syserrno contains more information)
    }
    // do something with the data, for example save it in a file
    write(fd, Response.bArray.__ptr, Response.bArray.__size);
    // if this is the end of the file, quit the loop
    if(Response.ulEOF)
        break;
}
*
```

4.1.2.28 `int MXCommon__ApplyConfigurationBackupFile (struct xsd__base64Binary * ByteArrayInput, xsd__unsignedLong ulEOF, struct MXCommon__Response * Response)`

Parameters

- [in] *ByteArrayInput* : Array of Bytes of the file
- [in] *ulEOF* : End of file flag
- [out] *Response*
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: system error (see syserrno)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Sterror\(\)](#).

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

This function is designed to be called repeatedly until all data is transfered. At this point the flag ulEOF must be set to 1. The new configuration is then applied.

4.1.2.29 `int MXCommon__ChangePassword (struct xsd__base64Binary * PreviousUser, struct xsd__base64Binary * PreviousPassword, struct xsd__base64Binary * NewUser, struct xsd__base64Binary * NewPassword, struct MXCommon__Response * Response)`

The changes are immediately active.

Parameters

- [in] *_* : No input parameter
- [out] *Response*
 - sResponse.iReturnValue : Return value
 - 0 : success
 - -1: string PreviousUser is invalid
 - -2: string PreviousPassword is invalid
 - -3: string NewUser is invalid
 - -4: string NewPassword is invalid
 - -5: authentication failed
 - -100: system error while saving tokens (use syserrno for more information)
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Sterror\(\)](#).
 - sArray : message returned by the auto configuration start

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

Warning

The parameters transit in clear text. Use this functionality only on trusted networks.
Given that ADDI-DATA GmbH takes security seriously, there is no way to change the password without knowing it. No "hidden back-door". This function makes it all too easy to lock a module, if you don't remember the password you set on it.

4.1.2.30 `int MXCommon__GetSubSystemState (xsd__unsignedLong SubsystemID, struct MXCommon__unsignedLongResponse * Response)`

Parameters

- [in] *SubsystemID* sub-system numerical ID
- [out] *Response* • sResponse.iReturnValue : Return value
- 0 : success
 - -1: system error while executing the request (see syserrno)
 - -2: invalid parameter SubsystemID
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - Value The state of the sub-system "Id" at the moment of the execution of the request.

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

4.1.2.31 `int MXCommon__GetSubsystemIDFromName (struct xsd__base64Binary * SubsystemName, struct MXCommon__unsignedLongResponse * Response)`

Parameters

- [in] *SubsystemName* sub-system symbolic name.
- [out] *Response* • sResponse.iReturnValue :Return value
- 0 : success
 - -1: system error while executing the request (see syserrno)
 - -2: invalid parameter SubsystemName
 - sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Strerror\(\)](#).
 - Value The numerical ID of the sub-system "SubsystemName".

Return values

SOAP_OK SOAP call success

otherwise SOAP protocol error

4.1.2.32 `int MXCommon__GetStateIDFromName (xsd__unsignedLong SubsystemID, struct xsd__base64Binary * StateName, struct MXCommon__unsignedLongResponse * Response)`

Parameters

- [in] *SubsystemID* sub-system numerical ID
- [in] *StateName* state symbolic name.
- [out] *Response* • sResponse.iReturnValue : Return value
- 0 : success
 - -1: system error while executing the request (see syserrno)
 - -2: invalid parameters SubsystemID or StateName

- sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Sterror\(\)](#).
- Value The numerical ID of the state "StateName".

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

4.1.2.33 int MXCommon__GetSubsystemNameFromID (xsd__unsignedLong SubsystemID, struct MXCommon__ByteArrayResponse * Response)

Parameters

- [in] *SubsystemID* sub-system numerical ID.
- [out] *Response* • sResponse.iReturnValue : Return value
- 0 : success
 - -1: system error while executing the request (see syserrno)
 - -2: invalid parameter SubsystemName
- sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Sterror\(\)](#).
 - sArray : The symbolic name associated with the ID.

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

4.1.2.34 int MXCommon__GetStateNameFromID (xsd__unsignedLong SubsystemID, xsd__unsignedLong StateID, struct MXCommon__ByteArrayResponse * Response)

Parameters

- [in] *SubsystemID* sub-system numerical ID.
- [in] *StateID* sub-system numerical ID.
- [out] *Response* • sResponse.iReturnValue : Return value
- 0 success
 - -1 system error while executing the request (see syserrno)
 - -2 invalid parameters SubsystemID or StateID
- sResponse.syserrno : System-error code. The value of the libc "errno" code, see [MXCommon__Sterror\(\)](#).
 - sArray The symbolic name associated with the state numerical ID.

Return values

SOAP_OK SOAP call success
otherwise SOAP protocol error

4.1.2.35 `int MXCommon__GetOptionInformation (void * _, xsd__unsignedLong ulOption01, xsd__unsignedLong ulOption02, struct MXCommon__ByteArrayResponse * Response)`

Parameters

- [in] *ulOption01*,: not used, set it to 0
- [in] *ulOption02*,: not used, set it to 0
- [out] *Response*
 - sArray : Option information string
 - sResponse Composed of iReturnValue and syserrno

Return values

- SOAP_OK* SOAP call success
- otherwise* SOAP protocol error

4.1.2.36 `int MXCommon__SetToMaster (void * _, xsd__unsignedLong ulState, xsd__unsignedLong ulOption01, xsd__unsignedLong ulOption02, struct MXCommon__Response * Response)`

Parameters

- [in] *ulState* State of the supermaster mode
 - **0** automatic mode (default). The state of the system (master or slave) will be automatically detected by the system
 - **1** Set to master mode at all time. The system will always be detected as master
- [in] *ulOption01* Reserved. Set to 0
- [in] *ulOption02* Reserved. Set to 0
- [out] *Response iReturnValue*
 - **0** The remote function performed OK
 - **-1** System error occurred
 - **-2** The PLD is not working
 - **-3** The ulFilterTime parameter is wrong
 - **-100** Internal system error occurred. See value of syserrno *syserrno* system error code (the value of the libc "errno" code)

Return values

- 0** SOAP_OK
- Others* See SOAP error

4.1.2.37 `int MXCommon__GetSynchronizationStatus (void * _, xsd__unsignedLong ulOption01, xsd__unsignedLong ulOption02, struct MXCommon__unsignedLongResponse * Response)`

Parameters

- [in] *ulOption01* Reserved. Set to 0
- [in] *ulOption02* Reserved. Set to 0
- [out] *Response sResponse.iReturnValue*

- **0** The remote function performed OK
- **-1** System error occurred
- **-2** The PLD is not working
- **-100** Internal system error occurred. See value of syserrno

sResponse.syserrno system error code (the value of the libc "errno" code)

ulValue State of the supermaster mode

- **0** Automatic mode (default). The state of the system (master or slave) will be automatically detected by the system
- **1** MSXE is always set as a master. The system will always be detected as master

Return values

0 SOAP_OK

Others See SOAP error

4.1.2.38 `int MSXExxxx__AcquisitionGetNumberOfChannels (xsd__unsignedLong ulOption1, struct MSXExxxx__unsignedLongResponse * Response)`

Parameters

[in] *ulOption1* : Reserved. Set to 0

[out] *Response* :

sResponse.iReturnValue :

- 0: Means the remote function performed OK
- -1: Means an system error occurred
- -100: Internal system error occurred. See value of syserrno

sResponse.syserrno : system-error code (the value of the libc "errno" code)

ulValue : Number of available acquisition channels

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

4.1.2.39 `int MSXExxxx__AcquisitionGetChannelInfo (xsd__unsignedLong ulChannel, xsd__unsignedLong ulOption1, struct MSXExxxx__AcquisitionGetChannelInfoResponse * Response)`

Parameters

[in] *ulChannel* : Selected acquisition channel

[in] *ulOption1* : Reserved. Set to 0

[out] *Response* :

sResponse.iReturnValue :

- 0: Means the remote function performed OK
- -1: Means an system error occurred
- -2: Channel selection wrong
- -100: Internal system error occurred. See value of syserrno

sResponse.syserrno : system-error code (the value of the libc "errno" code)

ulType : Acquisition channel type

- 0 : Not available
- 1 : Temperature channel
- 2 : Pressure channel
- 3 : Transducer channel
- 4 : Analog input channel
- 5 : Analog input ICP channel
- 6 : Digital I/O port

ulHwPosition : Hardware position index (0 to 7) ***ulChannelIndex*** : Return the functionality channel index

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

4.1.2.40 `int MSXExxxx__AcquisitionAutoRefreshInitAndStart (xsd__unsignedLong ulChannelMask, xsd__unsignedLong ulAverageValue, xsd__unsignedLong ulRefreshTime, xsd__unsignedLong ulRefreshTimeUnit, xsd__unsignedLong ulTriggerMask, xsd__unsignedLong ulTriggerMode, xsd__unsignedLong ulHardwareTriggerEdge, xsd__unsignedLong ulHardwareTriggerCount, xsd__unsignedLong ulByTriggerNbrOfSeqToAcquire, xsd__unsignedLong ulDataFormat, xsd__unsignedLong ulForceStart, xsd__unsignedLong ulOption1, xsd__unsignedLong ulOption2, xsd__unsignedLong ulOption3, struct MSXExxxx__Response * Response)`

Parameters

[in] ***ulChannelMask*** Mask of the channel to acquire by the auto refresh (1 bit = 1 Channel). 0 for all available acquisition channels

[in] ***ulAverageValue*** Set the average value :

- 1 : not used
- max value : 255

[in] ***ulRefreshTimeUnit*** Refresh Time Unit

- 0 : microsecond
- 1 : millisecond
- 2 : second

[in] ***ulRefreshTime*** Refresh Time

- range from min 1000 to 65535 when the unit is the microsecond
- range from min 1 to 65535 when the unit is the millisecond
- range from min 1 to 65535 when the unit is the second

[in] ***ulTriggerMask*** Define the source of the trigger

- 0 : trigger disabled
- 1 : Enable Hardware Digital Input Trigger
- 2 : Enable Synchro Trigger
- 4 : Enable Compare Trigger (only useful if your system has incremental counter or Sine/-Cosine input)

- 8 : Enable Index Trigger (only useful if your system has Sine/Cosine input)
- [in] **ulTriggerMode** Define the trigger mode
- 1 : One shot trigger
 - 2 : Sequence trigger
- [in] **ulHardwareTriggerEdge** Define the edge of the hardware trigger who generates a trigger action
- 1 : rising edge (Only if hardware trigger selected)
 - 2 : falling edge (Only if hardware trigger selected)
 - 3 : Both front (Only if hardware trigger selected)
- [in] **ulHardwareTriggerCount** Define the number of trigger events before the action occur
- 1 : all trigger event start the action
 - max value : 65535
- [in] **ulByTriggerNbrOfSeqToAcquire** Define the number of sequence to acquire by each trigger event
- 0 : continuous mode
 - <> 0 : number of sequence : (1..0xFFFFFFFF)
- D0 : Absolute Time stamp information
- [in] **ulDataFormat** • 0 : no time stamp information
- 1 : time stamp information
- D1 : Relative Time stamp information
- 0 : no time stamp information
 - 1 : time stamp information
- D2 : Auto refresh counter information
- 0 : No auto refresh counter information
 - 1 : Auto refresh counter information
- D3 : System status information
- 0 : No system status information required
 - 1 : System status information required
- D4 : Data format
- 0: Digital value (see technical description)
 - 1: Analog value (see technical description)
- You can not select both absolute and relative time stamp simultaneously
- [in] **ulForceStart** :
- 0 : Function return a error if any acquisition already in progress
 - 1 : If any acquisition in progress then stop this
- [in] **ulOption1** Reserved. Set to 0
- [in] **ulOption2** Reserved. Set to 0
- [in] **ulOption3** Reserved. Set to 0
- [out] **Response** :
- iReturnValue** :
- 0: Means the remote function performed OK
 - -1: Means an system error occurred
 - -2: Any acquisition already in progress
 - -3: Any selected channel not OK, call the diagnostic function for more information

- -4: Channel Mask error
- -5: Not available average value
- -6: Not available refresh time unit
- -7: The minimal refresh time is 1000 us !
- -8: The maximal refresh time is 65535 !
- -9: Trigger mask not available
- -10: Trigger mask : 2 different trigger source cannot be simultaneously be activated
- -11: Trigger mode not available
- -12: Trigger mask : 2 trigger mode cannot be simultaneously activated
- -13: Hardware trigger : front definition error
- -14: Hardware trigger count value not available
- -15: Nbr of sequence to acquire by trigger mode not available
- -16: Data format not available
- -17: Selected channels combination not available
- -100: Kernel function error

syserrno : system-error code (the value of the libc "errno" code)

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

4.1.2.41 int MSXExxxx__AcquisitionAutoRefreshGetValues (xsd__unsignedLong ulBlocking, struct MSXExxxx__AcquisitionAutoRefreshGetValuesResponse * Response)

Reads the values acquired in auto refresh mode.

Parameters

[in] **ulBlocking** Wait a new value or read the actual value

- **0**: Get the current auto refresh values
- **1**: Wait a new auto refresh value cycle

[out] **Response** Response of the system

- **iReturnValue**
 - **0**: The remote function performed OK
 - **-1**: Means an system error occurred
 - **-2**: No Acquisition in progress
 - **-3**: 2s timeout occurred. This if you have enabled the blocking mode.
 - **-4**: 2s timeout occurred. This if you do not have enabled the blocking mode, and if the first value is not available.
 - **-100**: Internal system error occurred. See value of syserrno
- **syserrno** system error code (the value of the libc "errno" code)
- **ulTimeStampLow** number of microseconds since the Epoch
- **ulTimeStampHigh** number of seconds since the Epoch
- **ulCounterValue** counter value
- **dValue** Array that contains the channels values
 - **dValue[0]** Value of channel 0

- ...
- *dValue[15]* Value of channel 15

Return values

0 SOAP_OK

Others See SOAP error

4.1.2.42 `int MSXExxxx__AcquisitionAutoRefreshStopAndRelease (void * _, struct MSXExxxx__Response * Response)`

Parameters

[in] *_* Dummy parameter

[out] *Response* :

iReturnValue :

- 0: Means the remote function performed OK
- -1: Means an system error occurred
- -100: Kernel function error

syserrno : system-error code (the value of the libc "errno" code)

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

Must be called before any another call to MSXExxxx__AcquisitionAutoRefreshInitAndStart.

4.1.2.43 `int MSXExxxx__AcquisitionSequenceInitAndStart (xsd__unsignedLong ulNbrOfChannel, struct MSXExxxx__AcquisitionSequenceInitAndStartChannelListParam * psChannelList, xsd__unsignedLong ulAcquisitionTime, xsd__unsignedLong ulAcquisitionTimeUnit, xsd__unsignedLong ulNbrOfSequence, xsd__unsignedLong ulNbrMaxSequenceToTransfer, xsd__unsignedLong ulTriggerMask, xsd__unsignedLong ulTriggerMode, xsd__unsignedLong ulHardwareTriggerEdge, xsd__unsignedLong ulHardwareTriggerCount, xsd__unsignedLong ulByTriggerNbrOfSeqToAcquire, xsd__unsignedLong ulDataFormat, xsd__unsignedLong ulForceStart, xsd__unsignedLong ulOption1, xsd__unsignedLong ulOption2, xsd__unsignedLong ulOption3, struct MSXExxxx__Response * Response)`

Initialises and starts the sequence acquisition mode.

Parameters

[in] *ulNbrOfChannel* : Nbr of channel in the sequence

[in] *psChannelList* : List of the channel who compose the sequence.

[in] *ulAcquisitionTime* : Acquisition Time

- range from min 1000 to 65535 when the unit is the microsecond
- range from min 1 to 65535 when the unit is the millisecond
- range from min 1 to 65535 when the unit is the second

- [in] ***ulAcquisitionTimeUnit*** : Acquisition Time Unit
- 0 : us
 - 1 : ms
 - 2 : s
- [in] ***ulNbrOfSequence*** : Number of sequence to acquire :
- 0 : continuous mode
 - <> 0 : number of sequence
- [in] ***ulNbrMaxSequenceToTransfer*** : Max nbr of sequence to acquire before a data transfer : (1,4096)
- [in] ***ulTriggerMask*** : Define the source of the trigger
- 0 : trigger disabled
 - 1 : Enable Hardware Digital Input Trigger
 - 2 : Enable Synchro Trigger
 - 4 : Enable Compare Trigger (only useful if your system has incremental counter or Sine/-Cosine input)
 - 8 : Enable Index Trigger (only useful if your system has Sine/Cosine input)
- [in] ***ulTriggerMode*** : Define the trigger mode
- 1 : One shot trigger
 - 2 : Sequence trigger
- [in] ***ulHardwareTriggerEdge*** : Define the edge of the hardware trigger who generate a trigger action
- 1 : rising front (Only if hardware trigger selected)
 - 2 : falling front (Only if hardware trigger selected)
 - 3 : Both front (Only if hardware trigger selected)
- [in] ***ulHardwareTriggerCount*** Define the number of trigger events before the action occur
- 1 : all trigger event start the action
 - max value : 65535
- [in] ***ulByTriggerNbrOfSeqToAcquire*** : define the number of sequence to acquire by each trigger event
- 0 : continuous mode
 - <> 0 : number of sequence : (1..0xFFFFFFFF)
- [in] ***ulDataFormat*** : Data format option
- D0 : Absolute Time stamp information
- 0 : no time stamp information
 - 1 : time stamp information
- D1 : Relative Time stamp information
- 0 : no time stamp information
 - 1 : time stamp information
- D2 : Sequence counter information
- 0 : No sequence counter information
 - 1 : Sequence counter information
- D3 : System status information
- 0 : No system status information required

- 1 : System status information required

D4 : Data format

- 0: Digital value (see technical description)
- 1: Analog value (see technical description)

You can not select both absolute and relative time stamp simultaneously

[in] **ulForceStart** :

- 0 : Function return a error if any acquisition already in progress
- 1 : If any acquisition in progress then stop this

[in] **ulOption1** : Reserved. Set to 0

[in] **ulOption2** : Reserved. Set to 0

[in] **ulOption3** : Reserved. Set to 0

[out] **Response** :

iReturnValue :

- 0: Means the remote function performed OK
- -1: Means an system error occurred
- -2: Any acquisition already in progress
- -3: The nbr of channel in the sequence is null or too high
- -4: Channel index selection error
- -5: Channel already selected
- -6: Any selected channel not OK, call the diagnostic function for more information
- -7: Not available acquisition time unit
- -8: The minimal acquisition time is 1000 us !
- -9: The maximal acquisition time is 65535 !
- -10: Transfer sequence size error (1 to 4096) !
- -11: The total number of sequences is not a multiple from number of sequences to transfer
- -12: Trigger mask not available
- -13: Trigger mask : 2 different trigger source cannot be simultaneously be activated
- -14: Trigger mode not available
- -15: Trigger mask : 2 trigger mode cannot be simultaneously be activated
- -16: Hardware trigger : front definition error
- -17: Hardware trigger count value not available
- -18: Nbr of sequence to acquire by trigger mode not available
- -19: Data format not available
- -20: Selected channels combination not available
- -100: Start sequence kernel function error

syserrno : system-error code (the value of the libc "errno" code)

Return values

0 SOAP_OK

Others See SOAP error

4.1.2.44 `int MSXEXxxx__AcquisitionSequenceStopAndRelease (void * _ , struct MSXEXxxx__Response * Response)`

Parameters

[in] `_` : no input parameter

[out] *Response* :

iReturnValue :

- 0: Means the remote function performed OK
- -1: Means an system error occurred
- -2: No sequence acquisition in progress
- -100: Kernel function error

syserrno : system-error code (the value of the libc "errno" code)

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

4.1.2.45 `int MSXEXxxx__TemperatureGetNumberOfChannels (xsd__unsignedLong ulOption1, struct MSXEXxxx__unsignedLongResponse * Response)`

Parameters

[in] *ulOption1* : Reserved. Set to 0

[out] *Response* :

sResponse.iReturnValue :

- 0: Means the remote function performed OK
- -1: Means an system error occurred

sResponse.syserrno : system-error code (the value of the libc "errno" code)

ulValue : Number of available temperature channels

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

4.1.2.46 `int MSXEXxxx__TemperatureGetChannelSensorClass (xsd__unsignedLong ulOption1, struct MSXEXxxx__TemperatureGetChannelSensorClassResponse * Response)`

Parameters

[in] *ulOption1* : Reserved. Set to 0

[out] *Response* :

iReturnValue :

- 0: Means the remote function performed OK
- -1: Means an system error occurred

syserrno : system-error code (the value of the libc "errno" code)

ulType : Array that contain the channels class (0 : RTD, 1 : TC, 2 : NTC)

- ulType [0] : Channel 0 type
- ...
- ulType [15] : Channel 15 type

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

4.1.2.47 `int MSXExxxx_TemperatureSetChannelType (xsd__unsignedLong
ulChannel, xsd__unsignedLong ulType, xsd__unsignedLong ulOption1, struct
MSXExxxx_Response * Response)`

Parameters

[in] *ulChannel* : Channel selection (0 to 15 or 255 for all channels)

[in] *ulType* : Type selection

- For TC
 - 1: Type B
 - 4: Type E
 - 9: Type J
 - 10: Type K
 - 13: Type N
 - 18: Type R
 - 19: Type S
 - 20: Type T
- For RTD type PT
 - 100: PT100
 - 200: PT200
 - 500: PT500
 - 1000: PT1000
 - ...
- For RTD type Ni
 - 101: Ni100
 - 201: Ni200
 - 501: Ni500
 - 1001: Ni1000
 - ...
- For NTC
 - 1: G10K4D453

[in] *ulOption1* : Reserved. Set to 0

[out] *Response* :

iReturnValue :

- 0: Means the remote function performed OK
- -1: Means an system error occurred
- -2: Channel selection wrong
- -3: Type selection wrong

- -4: Acquisition in progress. Can not change the type

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

4.1.2.48 `int MSXExxxx__TemperatureSetSamplingRate (xsd__unsignedLong ulChannelGroup, xsd__unsignedLong ulBaseSamplingRate, xsd__unsignedLong ulOption1, struct MSXExxxx__Response * Response)`

Parameters

[in] *ulChannelGroup* : Channel group selection.

- 0 for channels 0 and 1
- 1 for channels 2 and 3
- 2 for channels 4 and 5
- 3 for channels 6 and 7
- 4 for channels 8 and 9
- 5 for channels 10 and 11
- 6 for channels 12 and 13
- 7 for channels 14 and 15
- ...
- 255 for all channels

[in] *ulBaseSamplingRate* : Sampling rate selection

- 5 for 5Hz
- 10 for 10Hz
- 20 for 20Hz
- 40 for 40Hz
- 80 for 80Hz
- 160 for 160Hz
- 320 for 320Hz
- 640 for 640Hz
- 1000 for 1000Hz
- 2000 for 2000Hz

If only one channel is used then the real sampling rate is $ulBaseSamplingRate / 2$

If all 2 channels are used then the real sampling rate is $ulBaseSamplingRate / 3$

[in] *ulOption1* : Reserved. Set to 0

[out] *Response* :

iReturnValue :

- 0 : Means the remote function performed OK
- -1 : Means an system error occurred
- -2 : Channel group selection error
- -3 : Sampling rate selection error
- -4 : Acquisition in progress. Can not change the sampling rate
- -100 : IOCTL system call error

syserrno : system-error code (the value of the libc "errno" code)

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

4.1.2.49 `int MSXExxxx_TemperatureGetConfiguration (xsd_unsignedLong ulChannel, xsd_unsignedLong ilOption1, struct MSXExxxx_TemperatureGetConfigurationResponse * Response)`

Parameters

[in] *ulChannel* : Channel selection (0 to 15)

[in] *ilOption1* : Reserved. Set to 0

[out] *Response* :

sResponse.iReturnValue :

- 0: Means the remote function performed OK
- -1: Means an system error occurred
- -2: Channel selection wrong

sResponse.syserrno : system-error code (the value of the libc "errno" code)

ulClass : 0 : RTD / 1 : TC

ulType : Type selection

- For TC
 - 1: Type B
 - 4: Type E
 - 9: Type J
 - 10: Type K
 - 13: Type N
 - 18: Type R
 - 19: Type S
 - 20: Type T
- For RTD type PT
 - 100: PT100
 - 200: PT200
 - 500: PT500
 - 1000: PT1000
 - ...
- For RTD type Ni
 - 101: Ni100
 - 201: Ni200
 - 501: Ni500
 - 1001: Ni1000
 - ...
- For NTC
 - 1: G10K4D453

ulBaseSamplingRate : Sampling rate selection

- 5 for 5Hz
- 10 for 10Hz

- 20 for 20Hz
- 40 for 40Hz
- 80 for 80Hz
- 160 for 160Hz
- 320 for 320Hz
- 640 for 640Hz
- 1000 for 1000Hz
- 2000 for 2000Hz

Returns

- 0: Means the remote function performed OK
- -1: Means an system error occurred
- -2: Channel selection wrong

4.1.2.50 `int MSXExxxx_TemperatureDiagnostic (xsd__unsignedLong ulChannel, xsd__unsignedLong ulOption1, struct MSXExxxx__unsignedLongResponse * Response)`

Parameters

[in] *ulChannel* : Channel selection (0 to 15)

[in] *ulOption1* : Reserved. Set to 0

[out] *Response* :

sResponse.iReturnValue :

- 0: Means the remote function performed OK
- -1: Means an system error occurred

sResponse.syserrno : system-error code (the value of the libc "errno" code)

ulValue : Diagnostic status

- 0 : OK
- 1 : RTD voltage line open
- 2 : RTD voltage line short circuit
- 3 : RTD current line open
- 4 : RTD current line short circuit
- 5 : TC disconnected
- 6 : CJC disconnected (M12 connector not present)
- 7 : RTD sensor front-end disconnected (wiring properly linked)

Returns

- 0: SOAP_OK
- <> 0: See SOAP error

Index

- __offset
 - ByteArray, [55](#)
 - UnsignedLongArray, [68](#)
 - UnsignedShortArray, [69](#)
 - __ptr
 - ByteArray, [55](#)
 - UnsignedLongArray, [68](#)
 - UnsignedShortArray, [69](#)
 - xsd__base64Binary, [69](#)
 - __size
 - ByteArray, [55](#)
 - UnsignedLongArray, [68](#)
 - UnsignedShortArray, [69](#)
 - xsd__base64Binary, [69](#)
- bArray
 - MXCommon__-
 - GetAutoConfigurationFileResponse, [63](#)
- bCryptedValueArray
 - MXCommon__TestCustomerIDResponse, [67](#)
- bValueArray
 - MXCommon__TestCustomerIDResponse, [67](#)
- ByteArray, [55](#)
 - __offset, [55](#)
 - __ptr, [55](#)
 - __size, [55](#)
- Common functions, [11](#)
- Common general functions, [12](#)
- Common hardware trigger functions, [19](#)
- Common I/O auto configuration functions, [26](#)
- Common security functions, [21](#)
- Common synchronisation timer functions, [28](#)
- Common temperature functions, [17](#)
- Common time functions, [23](#)
- Common_autoconf
 - MXCommon__GetAutoConfigurationFile, [27](#)
 - MXCommon__SetAutoConfigurationFile, [27](#)
 - MXCommon__StartAutoConfiguration, [27](#)
- Common_configuration
 - MXCommon__-
 - ApplyConfigurationBackupFile, [31](#)
 - MXCommon__ChangePassword, [31](#)
 - MXCommon__GetConfigurationBackupFile, [30](#)
- Common_general
 - MXCommon__DataseverRestart, [16](#)
 - MXCommon__GetClientConnections, [13](#)
 - MXCommon__GetEthernetLinksStates, [16](#)
 - MXCommon__GetHostname, [13](#)
 - MXCommon__GetModuleType, [13](#)
 - MXCommon__Reboot, [15](#)
 - MXCommon__ResetAllIOFunctionalities, [15](#)
 - MXCommon__SetHostname, [13](#)
 - MXCommon__Sterror, [14](#)
- Common_hardware_trigger
 - MXCommon__-
 - GetHardwareTriggerFilterTime, [20](#)
 - MXCommon__GetHardwareTriggerState, [21](#)
 - MXCommon__-
 - SetHardwareTriggerFilterTime, [20](#)
- Common_security
 - MXCommon__SetCustomerKey, [22](#)
 - MXCommon__TestCustomerID, [23](#)
- Common_synchrotimer
 - MXCommon__InitAndStartSynchroTimer, [28](#)
 - MXCommon__-
 - StopAndReleaseSynchroTimer, [29](#)
- Common_temperature
 - MXCommon__-
 - GetModuleTemperatureValueAndStatus, [18](#)
 - MXCommon__-
 - SetModuleTemperatureWarningLevels, [18](#)
- Common_time
 - MXCommon__GetTime, [25](#)
 - MXCommon__GetUpTime, [25](#)
 - MXCommon__HardwareClockToSys, [25](#)
 - MXCommon__SetTime, [24](#)
 - MXCommon__SysToHardwareClock, [24](#)
- Customer option management, [35](#)
- CustomerOption
 - MXCommon__GetOptionInformation, [35](#)
- DefaultResponse, [55](#)
 - iReturn Value, [56](#)
 - syserrno, [56](#)

- dTemperatureValue
 - MXCommon__-
 - GetModuleTemperatureValueAndStatusResponse, 99
- dValue
 - MSXExxxx__-
 - AcquisitionAutoRefreshGetValuesResponse, 57
- iReturnValue
 - DefaultResponse, 56
 - MSXExxxx__Response, 59
 - MXCommon__Response, 66
- MSX-E systems servers, 10
- MSX-E321x Acquisition functions, 37
- MSX-E321x Acquisition information functions, 37
- MSX-E321x Autorefresh functions, 39
- MSX-E321x functions, 3
- MSX-E321x Sequence functions, 43
- MSX-E321x Temperature diagnostic functions, 52
- MSX-E321x Temperature functions, 47
- MSX-E321x Temperature initialisation/information functions, 47
- MSXE321x_Acquisition_Info
 - MSXExxxx__AcquisitionGetChannelInfo, 38
 - MSXExxxx__-
 - AcquisitionGetNumberOfChannels, 38
- MSXE321x_Autorefresh
 - MSXExxxx__-
 - AcquisitionAutoRefreshGetValues, 42
 - MSXExxxx__-
 - AcquisitionAutoRefreshInitAndStart, 40
 - MSXExxxx__-
 - AcquisitionAutoRefreshStopAndRelease, 43
- MSXE321x_public_doc.h, 71
 - MSXExxxx__-
 - AcquisitionAutoRefreshGetValues, 98
 - MSXExxxx__-
 - AcquisitionAutoRefreshInitAndStart, 96
 - MSXExxxx__-
 - AcquisitionAutoRefreshStopAndRelease, 99
 - MSXExxxx__AcquisitionGetChannelInfo, 95
 - MSXExxxx__-
 - AcquisitionGetNumberOfChannels, 95
 - MSXExxxx__-
 - AcquisitionSequenceInitAndStart, 99
 - MSXExxxx__-
 - AcquisitionSequenceStopAndRelease, 101
 - MSXExxxx__TemperatureDiagnostic, 106
 - MSXExxxx__-
 - TemperatureGetChannelSensorClass, 102
 - MSXExxxx__TemperatureGetConfiguration, 105
 - MSXExxxx__-
 - TemperatureGetNumberOfChannels, 102
 - MSXExxxx__TemperatureSetChannelType, 103
 - MSXExxxx__TemperatureSetSamplingRate, 104
 - MXCommon__-
 - ApplyConfigurationBackupFile, 90
 - MXCommon__ChangePassword, 91
 - MXCommon__DataseverRestart, 80
 - MXCommon__GetAutoConfigurationFile, 87
 - MXCommon__GetClientConnections, 78
 - MXCommon__GetConfigurationBackupFile, 90
 - MXCommon__GetEthernetLinksStates, 81
 - MXCommon__-
 - GetHardwareTriggerFilterTime, 83
 - MXCommon__GetHardwareTriggerState, 84
 - MXCommon__GetHostname, 77
 - MXCommon__-
 - GetModuleTemperatureValueAndStatus, 82
 - MXCommon__GetModuleType, 77
 - MXCommon__GetOptionInformation, 93
 - MXCommon__GetStateIDFromName, 92
 - MXCommon__GetStateNameFromID, 93
 - MXCommon__GetSubsystemIDFromName, 92
 - MXCommon__GetSubsystemNameFromID, 93
 - MXCommon__GetSubSystemState, 91
 - MXCommon__GetSynchronizationStatus, 94
 - MXCommon__GetTime, 86
 - MXCommon__GetUpTime, 87
 - MXCommon__HardwareClockToSys, 86
 - MXCommon__InitAndStartSynchroTimer, 88
 - MXCommon__Reboot, 80
 - MXCommon__ResetAllIOFunctionalities, 80
 - MXCommon__SetAutoConfigurationFile, 88
 - MXCommon__SetCustomerKey, 84

- MXCommon__-
 - SetHardwareTriggerFilterTime, [83](#)
- MXCommon__SetHostname, [78](#)
- MXCommon__-
 - SetModuleTemperatureWarningLevels, [82](#)
- MXCommon__SetTime, [85](#)
- MXCommon__SetToMaster, [94](#)
- MXCommon__StartAutoConfiguration, [88](#)
- MXCommon__-
 - StopAndReleaseSynchroTimer, [89](#)
- MXCommon__Sterror, [78](#)
- MXCommon__SysToHardwareClock, [86](#)
- MXCommon__TestCustomerID, [85](#)
- xsd__char, [77](#)
- xsd__double, [77](#)
- xsd__float, [77](#)
- xsd__int, [77](#)
- xsd__long, [77](#)
- xsd__string, [77](#)
- xsd__unsignedByte, [77](#)
- xsd__unsignedInt, [77](#)
- xsd__unsignedLong, [77](#)
- xsd__unsignedShort, [77](#)
- MSXE321x_Sequence
 - MSXExxxx__-
 - AcquisitionSequenceInitAndStart, [44](#)
 - MSXExxxx__-
 - AcquisitionSequenceStopAndRelease, [46](#)
- MSXE321x_Temperature_Diagnostic
 - MSXExxxx__TemperatureDiagnostic, [52](#)
- MSXE321x_Temperature_Init
 - MSXExxxx__-
 - TemperatureGetChannelSensorClass, [48](#)
 - MSXExxxx__TemperatureGetConfiguration, [51](#)
 - MSXExxxx__-
 - TemperatureGetNumberOfChannels, [48](#)
 - MSXExxxx__TemperatureSetChannelType, [49](#)
 - MSXExxxx__TemperatureSetSamplingRate, [50](#)
- MSXExxxx__AcquisitionAutoRefreshGetValues
 - MSXE321x_Autorefresh, [42](#)
 - MSXE321x_public_doc.h, [98](#)
- MSXExxxx__AcquisitionAutoRefreshGetValuesResponse, [56](#)
 - dValue, [57](#)
 - sResponse, [57](#)
 - ulCounterValue, [57](#)
 - ulTimeStampHigh, [57](#)
 - ulTimeStampLow, [57](#)
- MSXExxxx__AcquisitionAutoRefreshInitAndStart
 - MSXE321x_Autorefresh, [40](#)
 - MSXE321x_public_doc.h, [96](#)
- MSXExxxx__AcquisitionAutoRefreshStopAndRelease
 - MSXE321x_Autorefresh, [43](#)
 - MSXE321x_public_doc.h, [99](#)
- MSXExxxx__AcquisitionGetChannelInfo
 - MSXE321x_Acquisition_Info, [38](#)
 - MSXE321x_public_doc.h, [95](#)
- MSXExxxx__AcquisitionGetChannelInfoResponse, [57](#)
 - sResponse, [57](#)
 - ulChannelIndex, [58](#)
 - ulHwPosition, [58](#)
 - ulType, [57](#)
- MSXExxxx__AcquisitionGetNumberOfChannels
 - MSXE321x_Acquisition_Info, [38](#)
 - MSXE321x_public_doc.h, [95](#)
- MSXExxxx__AcquisitionSequenceInitAndStart
 - MSXE321x_public_doc.h, [99](#)
 - MSXE321x_Sequence, [44](#)
- MSXExxxx__AcquisitionSequenceInitAndStartChannelListParam, [58](#)
 - ulChannelList, [58](#)
- MSXExxxx__AcquisitionSequenceStopAndRelease
 - MSXE321x_public_doc.h, [101](#)
 - MSXE321x_Sequence, [46](#)
- MSXExxxx__FileResponse, [58](#)
 - sArray, [59](#)
 - sResponse, [59](#)
 - ulEOF, [59](#)
- MSXExxxx__Response, [59](#)
 - iReturnValue, [59](#)
 - syserrno, [59](#)
- MSXExxxx__TemperatureDiagnostic
 - MSXE321x_public_doc.h, [106](#)
 - MSXE321x_Temperature_Diagnostic, [52](#)
- MSXExxxx__TemperatureGetChannelSensorClass
 - MSXE321x_public_doc.h, [102](#)
 - MSXE321x_Temperature_Init, [48](#)
- MSXExxxx__TemperatureGetChannelSensorClassResponse, [59](#)
 - sResponse, [60](#)
 - ulType, [60](#)
- MSXExxxx__TemperatureGetConfiguration
 - MSXE321x_public_doc.h, [105](#)
 - MSXE321x_Temperature_Init, [51](#)
- MSXExxxx__TemperatureGetConfigurationResponse, [60](#)
 - sResponse, [60](#)
 - ulBaseSamplingRate, [60](#)
 - ulClass, [60](#)

- ulType, 60
- MSXExxxx__TemperatureGetNumberOfChannels
 - MSXE321x_public_doc.h, 102
 - MSXE321x_Temperature_Init, 48
- MSXExxxx__TemperatureSetChannelType
 - MSXE321x_public_doc.h, 103
 - MSXE321x_Temperature_Init, 49
- MSXExxxx__TemperatureSetSamplingRate
 - MSXE321x_public_doc.h, 104
 - MSXE321x_Temperature_Init, 50
- MSXExxxx__unsignedLongResponse, 60
 - sResponse, 61
 - ulValue, 61
- MSXExxxx__unsignedLongTimeStampResponse, 61
 - sResponse, 61
 - ulTimeStampHigh, 61
 - ulTimeStampLow, 61
 - ulValue, 61
- MXCommon__ApplyConfigurationBackupFile
 - Common_configuration, 31
 - MSXE321x_public_doc.h, 90
- MXCommon__ByteArrayResponse, 61
 - sArray, 62
 - sResponse, 62
- MXCommon__ChangePassword
 - Common_configuration, 31
 - MSXE321x_public_doc.h, 91
- MXCommon__DataseverRestart
 - Common_general, 16
 - MSXE321x_public_doc.h, 80
- MXCommon__FileResponse, 62
 - sArray, 62
 - sResponse, 62
 - ulEOF, 62
- MXCommon__GetAutoConfigurationFile
 - Common_autoconf, 27
 - MSXE321x_public_doc.h, 87
- MXCommon__GetAutoConfigurationFileResponse, 62
 - bArray, 63
 - sResponse, 63
 - ulEOF, 63
- MXCommon__GetClientConnections
 - Common_general, 13
 - MSXE321x_public_doc.h, 78
- MXCommon__GetConfigurationBackupFile
 - Common_configuration, 30
 - MSXE321x_public_doc.h, 90
- MXCommon__GetEthernetLinksStates
 - Common_general, 16
 - MSXE321x_public_doc.h, 81
- MXCommon__GetEthernetLinksStatesResponse, 63
 - sPort0, 63
 - sPort1, 63
 - sResponse, 63
- MXCommon__GetHardwareTriggerFilterTime
 - Common_hardware_trigger, 20
 - MSXE321x_public_doc.h, 83
- MXCommon__GetHardwareTriggerFilterTimeResponse, 63
 - sResponse, 64
 - ulFilterTime, 64
 - ulInfo01, 64
 - ulInfo02, 64
- MXCommon__GetHardwareTriggerState
 - Common_hardware_trigger, 21
 - MSXE321x_public_doc.h, 84
- MXCommon__GetHardwareTriggerStateResponse, 64
 - sResponse, 64
 - ulInfo01, 64
 - ulInfo02, 64
 - ulState, 64
- MXCommon__GetHostname
 - Common_general, 13
 - MSXE321x_public_doc.h, 77
- MXCommon__GetModuleTemperatureValueAndStatus
 - Common_temperature, 18
 - MSXE321x_public_doc.h, 82
- MXCommon__GetModuleTemperatureValueAndStatusResponse, 64
 - dTemperatureValue, 65
 - sResponse, 65
 - ulInfo, 65
 - ulTemperatureStatus, 65
- MXCommon__GetModuleType
 - Common_general, 13
 - MSXE321x_public_doc.h, 77
- MXCommon__GetOptionInformation
 - CustomerOption, 35
 - MSXE321x_public_doc.h, 93
- MXCommon__GetStateIDFromName
 - MSXE321x_public_doc.h, 92
 - SystemStatemanagement, 34
- MXCommon__GetStateNameFromID
 - MSXE321x_public_doc.h, 93
 - SystemStatemanagement, 34
- MXCommon__GetSubsystemIDFromName
 - MSXE321x_public_doc.h, 92
 - SystemStatemanagement, 33
- MXCommon__GetSubsystemNameFromID
 - MSXE321x_public_doc.h, 93
 - SystemStatemanagement, 34
- MXCommon__GetSubSystemState
 - MSXE321x_public_doc.h, 91
 - SystemStatemanagement, 33

- MXCommon__GetSynchronizationStatus
 - MSXE321x_public_doc.h, [94](#)
 - Synchronisation, [36](#)
- MXCommon__GetTime
 - Common_time, [25](#)
 - MSXE321x_public_doc.h, [86](#)
- MXCommon__GetTimeResponse, [65](#)
 - sResponse, [65](#)
 - ulHighTime, [65](#)
 - ulLowTime, [65](#)
- MXCommon__GetUpTime
 - Common_time, [25](#)
 - MSXE321x_public_doc.h, [87](#)
- MXCommon__GetUpTimeResponse, [65](#)
 - sResponse, [66](#)
 - ulUpTime, [66](#)
- MXCommon__HardwareClockToSys
 - Common_time, [25](#)
 - MSXE321x_public_doc.h, [86](#)
- MXCommon__InitAndStartSynchroTimer
 - Common_synchrotimer, [28](#)
 - MSXE321x_public_doc.h, [88](#)
- MXCommon__Reboot
 - Common_general, [15](#)
 - MSXE321x_public_doc.h, [80](#)
- MXCommon__ResetAllIOFunctionalities
 - Common_general, [15](#)
 - MSXE321x_public_doc.h, [80](#)
- MXCommon__Response, [66](#)
 - iReturnValue, [66](#)
 - syserrno, [66](#)
- MXCommon__SetAutoConfigurationFile
 - Common_autoconf, [27](#)
 - MSXE321x_public_doc.h, [88](#)
- MXCommon__SetCustomerKey
 - Common_security, [22](#)
 - MSXE321x_public_doc.h, [84](#)
- MXCommon__SetHardwareTriggerFilterTime
 - Common_hardware_trigger, [20](#)
 - MSXE321x_public_doc.h, [83](#)
- MXCommon__SetHostname
 - Common_general, [13](#)
 - MSXE321x_public_doc.h, [78](#)
- MXCommon__SetModuleTemperatureWarningLevels
 - Common_temperature, [18](#)
 - MSXE321x_public_doc.h, [82](#)
- MXCommon__SetTime
 - Common_time, [24](#)
 - MSXE321x_public_doc.h, [85](#)
- MXCommon__SetToMaster
 - MSXE321x_public_doc.h, [94](#)
 - Synchronisation, [36](#)
- MXCommon__StartAutoConfiguration
 - Common_autoconf, [27](#)
 - MSXE321x_public_doc.h, [88](#)
- MXCommon__StopAndReleaseSynchroTimer
 - Common_synchrotimer, [29](#)
 - MSXE321x_public_doc.h, [89](#)
- MXCommon__Sterror
 - Common_general, [14](#)
 - MSXE321x_public_doc.h, [78](#)
- MXCommon__SysToHardwareClock
 - Common_time, [24](#)
 - MSXE321x_public_doc.h, [86](#)
- MXCommon__TestCustomerID
 - Common_security, [23](#)
 - MSXE321x_public_doc.h, [85](#)
- MXCommon__TestCustomerIDResponse, [66](#)
 - bCryptedValueArray, [67](#)
 - bValueArray, [67](#)
 - sResponse, [67](#)
- MXCommon__unsignedLongResponse, [67](#)
 - sResponse, [67](#)
 - ulValue, [67](#)
- sArray
 - MSXExxxx__FileResponse, [59](#)
 - MXCommon__ByteArrayResponse, [62](#)
 - MXCommon__FileResponse, [62](#)
- Set/Backup/Restore general system configuration, [30](#)
- sGetEthernetLinksStatesPort, [67](#)
 - ulDuplex, [68](#)
 - ulInfo1, [68](#)
 - ulInfo2, [68](#)
 - ulSpeed, [68](#)
 - ulState, [68](#)
- SOAP function calls in C/C++ language, [3](#)
- Software hints, [3](#)
- sPort0
 - MXCommon__ -
 - GetEthernetLinksStatesResponse, [63](#)
- sPort1
 - MXCommon__ -
 - GetEthernetLinksStatesResponse, [63](#)
- sResponse
 - MSXExxxx__ -
 - AcquisitionAutoRefreshGetValuesResponse, [57](#)
 - MSXExxxx__ -
 - AcquisitionGetChannelInfoResponse, [57](#)
 - MSXExxxx__FileResponse, [59](#)
 - MSXExxxx__ -
 - TemperatureGetChannelSensorClassResponse, [60](#)
 - MSXExxxx__ -
 - TemperatureGetConfigurationResponse, [60](#)

- 60
- MSXExxxx__unsignedLongResponse, 61
- MSXExxxx__-
 - unsignedLongTimeStampResponse, 61
- MXCommon__ByteArrayResponse, 62
- MXCommon__FileResponse, 62
- MXCommon__-
 - GetAutoConfigurationFileResponse, 63
- MXCommon__-
 - GetEthernetLinksStatesResponse, 63
- MXCommon__-
 - GetHardwareTriggerFilterTimeResponse, 64
- MXCommon__-
 - GetHardwareTriggerStateResponse, 64
- MXCommon__-
 - GetModuleTemperatureValueAndStatusResponse, 65
- MXCommon__GetTimeResponse, 65
- MXCommon__GetUpTimeResponse, 66
- MXCommon__TestCustomerIDResponse, 67
- MXCommon__unsignedLongResponse, 67
- Synchronisation
 - MXCommon__GetSynchronizationStatus, 36
 - MXCommon__SetToMaster, 36
- Synchronisation management, 35
- syserrno
 - DefaultResponse, 56
 - MSXExxxx__Response, 59
 - MXCommon__Response, 66
- System state management, 32
- SystemStatemanagement
 - MXCommon__GetStateIDFromName, 34
 - MXCommon__GetStateNameFromID, 34
 - MXCommon__GetSubsystemIDFromName, 33
 - MXCommon__GetSubsystemNameFromID, 34
 - MXCommon__GetSubSystemState, 33
- Temperature diagnostic, 11
- ulBaseSamplingRate
 - MSXExxxx__-
 - TemperatureGetConfigurationResponse, 60
- ulChannelIndex
 - MSXExxxx__-
 - AcquisitionGetChannelInfoResponse, 58
- ulChannelList
 - MSXExxxx__-
 - AcquisitionSequenceInitAndStartChannelListParam, 58
- ulClass
 - MSXExxxx__-
 - TemperatureGetConfigurationResponse, 60
- ulCounterValue
 - MSXExxxx__-
 - AcquisitionAutoRefreshGetValuesResponse, 57
- ulDuplex
 - sGetEthernetLinksStatesPort, 68
- ulEOF
 - MSXExxxx__FileResponse, 59
 - MXCommon__FileResponse, 62
 - MXCommon__-
 - GetAutoConfigurationFileResponse, 63
 - MXCommon__-
 - GetHardwareTriggerFilterTimeResponse, 64
- ulHighTime
 - MXCommon__GetTimeResponse, 65
- ulHwPosition
 - MSXExxxx__-
 - AcquisitionGetChannelInfoResponse, 58
- ulInfo
 - MXCommon__-
 - GetModuleTemperatureValueAndStatusResponse, 65
- ulInfo01
 - MXCommon__-
 - GetHardwareTriggerFilterTimeResponse, 64
 - MXCommon__-
 - GetHardwareTriggerStateResponse, 64
- ulInfo02
 - MXCommon__-
 - GetHardwareTriggerFilterTimeResponse, 64
 - MXCommon__-
 - GetHardwareTriggerStateResponse, 64
- ulInfo1
 - sGetEthernetLinksStatesPort, 68
- ulInfo2
 - sGetEthernetLinksStatesPort, 68
- ulLowTime
 - MXCommon__GetTimeResponse, 65
- ulSpeed

- sGetEthernetLinksStatesPort, [68](#)
- ulState
 - MXCommon__-
 - GetHardwareTriggerStateResponse, [64](#)
 - sGetEthernetLinksStatesPort, [68](#)
- ulTemperatureStatus
 - MXCommon__-
 - GetModuleTemperatureValueAndStatusResponse, [65](#)
- ulTimeStampHigh
 - MSXExxxx__-
 - AcquisitionAutoRefreshGetValuesResponse, [57](#)
 - MSXExxxx__-
 - unsignedLongTimeStampResponse, [61](#)
- ulTimeStampLow
 - MSXExxxx__-
 - AcquisitionAutoRefreshGetValuesResponse, [57](#)
 - MSXExxxx__-
 - unsignedLongTimeStampResponse, [61](#)
- ulType
 - MSXExxxx__-
 - AcquisitionGetChannelInfoResponse, [57](#)
 - MSXExxxx__-
 - TemperatureGetChannelSensorClassResponse, [60](#)
 - MSXExxxx__-
 - TemperatureGetConfigurationResponse, [60](#)
- ulUpTime
 - MXCommon__GetUpTimeResponse, [66](#)
- ulValue
 - MSXExxxx__unsignedLongResponse, [61](#)
 - MSXExxxx__-
 - unsignedLongTimeStampResponse, [61](#)
 - MXCommon__unsignedLongResponse, [67](#)
- UnsignedLongArray, [68](#)
 - __offset, [68](#)
 - __ptr, [68](#)
 - __size, [68](#)
- UnsignedShortArray, [68](#)
 - __offset, [69](#)
 - __ptr, [69](#)
 - __size, [69](#)
- xsd__base64Binary, [69](#)
 - __ptr, [69](#)
 - __size, [69](#)
- xsd__char
 - MSXE321x_public_doc.h, [77](#)
- xsd__double
 - MSXE321x_public_doc.h, [77](#)
- xsd__float
 - MSXE321x_public_doc.h, [77](#)
- xsd__int
 - MSXE321x_public_doc.h, [77](#)
- xsd__long
 - MSXE321x_public_doc.h, [77](#)
- xsd__string
 - MSXE321x_public_doc.h, [77](#)
- xsd__unsignedByte
 - MSXE321x_public_doc.h, [77](#)
- xsd__unsignedInt
 - MSXE321x_public_doc.h, [77](#)
- xsd__unsignedLong
 - MSXE321x_public_doc.h, [77](#)
- xsd__unsignedShort
 - MSXE321x_public_doc.h, [77](#)